


DATASHEET - DILM32-XSP(RDC24)



**Replacement coil, Tool-less plug connection, RDC 24: 24 - 27 V DC, DC,
For use with: DILM17, DILM25, DILM32, DILM38, DILMP32 - DILMP45**



Part no. DILM32-XSP(RDC24)
Catalog No. 281155
Alternate Catalog No. XTCERENCOILCTD
EL-Nummer (Norway) 4130506

Delivery program

Connection technique			Tool-less plug connection
Actuating voltage			RDC 24: 24 - 27 V DC
Voltage AC/DC			DC
For use with			DILM17 DILM25 DILM32 DILM38 DILMP32 - DILMP45
For use with			DILM17 - DILM38

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	60

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Coil for relay (EC001043)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Reel for contactor (ecl@ss10.0.1-27-37-10-12 [AKF021013])			
Rated control supply voltage Us at AC 50HZ		V	0 - 0
Rated control supply voltage Us at AC 60HZ		V	0 - 0
Rated control supply voltage Us at DC		V	24 - 27
Voltage type for actuating			DC

Approvals

Product Standards			IEC/EN 60947-4-1; UL 508; CSA-C22.2 No. 14-05; CE marking
UL File No.			E29096
UL Category Control No.			NLDX
CSA File No.			012528
CSA Class No.			2411-03, 3211-04
North America Certification			UL listed, CSA certified
Specially designed for North America			No

Assets (links)

Declaration of CE Conformity

00002870

Instruction Leaflets

IL03407036Z2018_04