Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norw egian Bokmål

Worldwide English



Powering Business Worldwide

DILM150-XS1 - Star-point bridge, For use with DILM80 - DILM170, DILMF80 - DILMF150



284768 DILM150-XS1

Overview Specifications Resources



Delivery program

Design verification as per IEC/EN 61439

• Technical data ETIM 7.0

Approvals

284768 DILM150-XS1

Star-point bridge, For use with DILM80 - DILM170, DILMF80 - DILMF150
Alternate Catalog No. XTCEXSDBG
EL-Nurmer (Norway) 4110364

Star-point bridge, Product range: Accessories, Wiring accessories, For use with: DILM80 - DILM170, DILMF80 - DILMF150

Delivery program

Contact sequence



Product range Accessories

Accessories

Wiring accessories

For use with

DILM80 - DILM170

DILMF80 - DILMF150

For use with

Star-point bridge for DILM80 up to DILM170

Design verification as per IEC/EN 61439

Technical data for design verification

Rated operational current for specified heat dissipation [In]

225 A

Heat dissipation per pole, current-dependent [P_{vid}]

0 W

Equipment heat dissipation, current-dependent [Pvid]

0 W

Static heat dissipation, non-current-dependent [P_{vs}]

0 W

Heat dissipation capacity [Pdiss]

0 W

Operating ambient temperature min.

-25 °C

Operating ambient temperature max.

+60 °C

IEC/EN 61439 design verification

10.2 Strength of materials and parts 10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of ASSEVBLIES

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Accessories for low-voltage switch technology (EC002498)

Bectric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Component for low-voltage switch technology (accessories) (ecl@ss10.0.1-27-37-13-92 [AKN570013])

Type of accessory

Connecting bridge

Approvals

Product Standards

IEC/EN 60947-4-1; UL 508; CSA-C22.2 No. 14-05; CE marking

UL File No.

E36332

UL Category Control No.

NI RV

CSA File No.

012528

CSA Class No.

3211-03

North America Certification

CAD data

- Product-specific CAD data (Web)
- 3D Preview (Web)

DWG files

DA-CD-dil_m150_xs1 File (Web)

edz files

DA-CE-ETN.DILM150-XS1
 File
 (Web)

Step files

DA-CS-dil_m150_xs1 File (Web)


Additional product information

- Motor starters and "Special Purpose Ratings" for the North American market (PDF)
- Switchgear of Power Factor Correction Systems
 (PDE)
- X-Start Modern Switching Installations Efficiently Fitted and Wired Securely (PDF)
- Mrror Contacts for Highly-Reliable Information Relating to Safety-Related Control Functions (PDF)
- Effect of the Cabel Capacitance of Long Control Cables on the Actuation of Contactors (PDF)
- Switchgear for Luminaires
- Standard Compliant and Functionally Safe Engineering Design with Mechanical Auxiliary Contacts (PDF)
- The Interaction of Contactors with PLCs
 (PDF)
- Busbar Component Adapters for modern Industrial control panels (PDF)

Product photo




Wiring diagram



Line drawing Star-point bridge

3D drawing



Standards

• **XStart** 000Z153 Logo xStart logo

Download-Center

Download-Center (this item)
 Eaton BMEA Download-Center - download data for this item

Dow nload-Center
 Eaton EMEA Dow nload-Center

Cenerate data sheet in PDF format

Cenerate data sheet in Excel format

Cenerate data sheet in Excel format

Write a comment Imprint Privacy Policy Legal Disclaimer Terms and Conditions © 2021 by Eaton Industries GmbH