### DATASHEET - DILM95-XSP(230V50HZ,240V60HZ)



Replacement coil, Tool-less plug connection, 230 V 50 Hz, 240 V 60 Hz, AC, For use with: DILM80, DILM95



Powering Business Worldwide

1/1

Part no. DILM95-XSP(230V50HZ,240V60HZ)

Catalog No. 230062

Alternate Catalog XTCERENCOILFF

No.

EL-Nummer 4130504

(Norway)

#### **Delivery program**

Connection technique	Tool-less plug connection
Actuating voltage	230 V 50 Hz, 240 V 60 Hz
Voltage AC/DC	AC
For use with	DILM80 DILM95
For use with	DILM80 - DILM170

## Design verification as per IEC/EN 61439

Technical data for design verification		
Operating ambient temperature min.	°C	-25
Operating ambient temperature max.	°C	60

# **Technical data ETIM 7.0**

Low-voltage industrial components (EG000017) / Coil for relay (EC001043)				
Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Reel for contactor (ecl@ss10.0.1-27-37-10-12 [AKF021013])				
Rated control supply voltage Us at AC 50HZ	V	'	230 - 230	
Rated control supply voltage Us at AC 60HZ	V	,	240 - 240	
Rated control supply voltage Us at DC	V	,	0 - 0	
Voltage type for actuating			AC	

### **Approvals**

IEC/EN 60947-4-1; UL 508; CSA-C22.2 No. 14-05; CE marking
E29096
NLDX
012528
2411-03, 3211-04
UL listed, CSA certified
No

### **Assets (links)**

**Instruction Leaflets** 

IL03407042Z2018\_05