

Select your language

- [German](#)
- [English](#)
- [Spanish](#)
- [French](#)
- [Dutch](#)
- [Italian](#)
- [Polish](#)
- [Czech](#)
- [Russian](#)
- [Norwegian Bokmål](#)

Worldwide English



DILM65-XSP(230V50HZ,240V60HZ) - Replacement coil, Tool-less plug connection, 230 V 50 Hz, 240 V 60 Hz, AC, For use with: DILM40, DILM50, DILM65, DILM72, DILM63, DILM80



281171 DILM65-XSP(230V50HZ,240V60HZ)

[Overview](#) [Specifications](#) [Resources](#)



281171 DILM65-XSP(230V50HZ,240V60HZ)

Replacement coil, Tool-less plug connection, 230 V 50 Hz, 240 V 60 Hz, AC, For use with: DILM40, DILM50, DILM65, DILM72, DILM63, DILM80

Alternate Catalog No.

XTCERENCOILDF

EL-Nummer (Norway)

4130503

Replacement coil, Connection technique: Tool-less plug connection, Actuating voltage: 230 V 50 Hz, 240 V 60 Hz, Voltage AC/DC: AC, For use with: DILM40, DILM50, DILM65, DILM72, DILM63, DILM80, DILM40 - DILM72

- [Delivery program](#)

Design verification as per IEC/EN 61439

- [Technical data ETIM 7.0](#)

- [Approvals](#)

Delivery program

Actuating voltage

230 V 50 Hz, 240 V 60 Hz

Voltage AC/DC

AC

For use with

DILM40

DILM50

DILM65

DILM72

DILM63

DILM80

For use with

DILM40 - DILM72

Design verification as per IEC/EN 61439

Operating ambient temperature min.

-25 °C

Operating ambient temperature max.

+60 °C

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Coil for relay (EC001043)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Reel for contactor (ecl@ss10.0.1-27-37-10-12 [AKF021013])

Rated control supply voltage U_s at AC 50Hz

230 - 230 V

Rated control supply voltage U_s at AC 60Hz

240 - 240 V

Rated control supply voltage U_s at DC

0 - 0 V

Voltage type for actuating

AC

Approvals

Product Standards

IEC/EN 60947-4-1; UL 508; CSA-C22.2 No. 14-05; CE marking

UL File No.

E29096

UL Category Control No.

NLDX

CSA File No.

012528

CSA Class No.

2411-03, 3211-04

North America Certification

UL listed, CSA certified

Specially designed for North America

No

Additional product information

- [Motor starters and "Special Purpose Ratings" for the North American market](#)
(PDF)
- [Switchgear of Power Factor Correction Systems](#)
(PDF)
- [X-Start - Modern Switching Installations Efficiently Fitted and Wired Securely](#)
(PDF)
- [Mirror Contacts for Highly-Reliable Information Relating to Safety-Related Control Functions](#)
(PDF)
- [Effect of the Cable Capacitance of Long Control Cables on the Actuation of Contactors](#)
(PDF)
- [Switchgear for Luminaires](#)
(PDF)
- [Standard Compliant and Functionally Safe Engineering Design with Mechanical Auxiliary Contacts](#)
(PDF)
- [The Interaction of Contactors with PLCs](#)
(PDF)
- [Busbar Component Adapters for modern Industrial control panels](#)
(PDF)


Product photo



2100PIC-48

Photo
Individual coil

3D drawing



2100DRV-102

Line drawing
Individual coil

Standards

- 
000Z153
Logo
xStart logo

Instruction Leaflet

- Coil exchange: DILM(C)40 to DILM(C)65, DILMP63 to DILMP80 (IL03407041Z)
Asset
(PDF, multilingual)

Declaration of Conformity

EU

- DILM40-DILM72 - Contactors & contactor combinations (DA-DC-00004070)
Asset
(PDF)

Download-Center

- [Download-Center \(this item\)](#)
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)
Eaton EMEA Download-Center

 [Generate data sheet in PDF format](#)

 [Generate data sheet in Excel format](#)

 [Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)
© 2021 by Eaton Industries GmbH