

DATASHEET - DILM65-XSP(230V50HZ,240V60HZ)



**Replacement coil, Tool-less plug connection, 230 V 50 Hz, 240 V 60 Hz, AC,
For use with: DILM40, DILM50, DILM65, DILM72, DILMP63, DILMP80**



Part no. DILM65-XSP(230V50HZ,240V60HZ)
Catalog No. 281171
Alternate Catalog No. XTCERENCOILDF
EL-Nummer (Norway) 4130503

Delivery program

Connection technique			Tool-less plug connection
Actuating voltage			230 V 50 Hz, 240 V 60 Hz
Voltage AC/DC			AC
For use with			DILM40 DILM50 DILM65 DILM72 DILMP63 DILMP80
For use with			DILM40 - DILM72

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	60

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Coil for relay (EC001043)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Reel for contactor (ecl@ss10.0.1-27-37-10-12 [AKF021013])			
Rated control supply voltage Us at AC 50HZ		V	230 - 230
Rated control supply voltage Us at AC 60HZ		V	240 - 240
Rated control supply voltage Us at DC		V	0 - 0
Voltage type for actuating			AC

Approvals

Product Standards			IEC/EN 60947-4-1; UL 508; CSA-C22.2 No. 14-05; CE marking
UL File No.			E29096
UL Category Control No.			NLDX
CSA File No.			012528
CSA Class No.			2411-03, 3211-04
North America Certification			UL listed, CSA certified
Specially designed for North America			No

Assets (links)

Declaration of CE Conformity

00002872

Instruction Leaflets

IL03407041Z2018_05