



051650  
DILEEM-01-G(24VDC)

[Overview](#)

[Specifications](#)

[Resources](#)



[Delivery program](#)

[Technical data](#)

[Design verification as  
per IEC/EN 61439](#)

[Technical data ETIM 7.0](#)

[Approvals](#)

[Characteristics](#)

[Dimensions](#)

## DELIVERY PROGRAM

Product range  
Contactors

Application  
Mini Contactors for Motors and Resistive Loads

Subrange  
Contactors DILEEM

Utilization category  
AC-1: Non-inductive or slightly inductive loads,  
resistance furnaces  
AC-3/AC-3e: Normal AC induction motors: Starting,  
switching off while running  
AC-4: Normal AC induction motors: starting,  
plugging, reversing, inching



Notes  
Also suitable for motors with efficiency class IE3.  
Also tested according to AC-3e.

Connection technique  
Screw terminals

Description  
With auxiliary contact

Number of poles  
3 pole

### Rated operational current

AC-3  
380 V 400 V [I<sub>e</sub>]  
6.6 A

AC-1  
Conventional free air thermal current, 3 pole, 50 -  
60 Hz  
Open  
at 40 °C [I<sub>th</sub> = I<sub>e</sub>]  
22 A

### Max. rating for three-phase motors, 50 - 60 Hz

AC-3  
220 V 230 V [P]  
1.5 kW

AC-3  
380 V 400 V [P]  
3 kW

AC-3  
660 V 690 V [P]  
3 kW

AC-4  
220 V 230 V [P]  
1.1 kW

AC-4  
380 V 400 V [P]  
2.2 kW

AC-4

660 V 690 V [F]  
2.2 kW

## Contacts

N/C = Normally closed  
1 NC

Contact sequence



## Instructions

Integrated diode-resistor combination

For use with  
...DILE

Actuating voltage  
24 V DC

Voltage AC/DC  
DC operation

# TECHNICAL DATA

## General

Standards  
IEC/EN 60947, VDE 0660, CSA, UL

Lifespan, mechanical [Operations]  
20 x 10<sup>6</sup>

Maximum operating frequency  
Mechanical  
9000 Ops./h

Maximum operating frequency  
electrical (Contactors without overload relay)  
[Operations/h]  
Page 05/070

Climatic proofing  
Damp heat, constant, to IEC 60068-2-78  
Damp heat, cyclic, to IEC 60068-2-30

Ambient temperature  
Open  
-25 - +50 °C


Ambient temperature  
Enclosed  
- 25 - 40 °C

Ambient temperature  
Storage  
Min. ambient temperature, storage  
- 40 °C

Ambient temperature  
Storage  
Ambient temperature, storage max.  
+ 80 °C

Mounting position  
As required, except vertical with terminals A1/A2  
at the bottom

Mounting position



Mechanical shock resistance (IEC/EN 60068-2-27)  
Half-sinusoidal shock, 10 ms  
Basic unit without auxiliary contact module  
Main contacts, make contacts  
10 g

Mechanical shock resistance (IEC/EN 60068-2-27)  
Half-sinusoidal shock, 10 ms  
Basic unit without auxiliary contact module  
Main contacts Make/break contacts  
Break contact  
10 g

Mechanical shock resistance (IEC/EN 60068-2-27)  
Half-sinusoidal shock, 10 ms  
Basic unit with auxiliary contact module  
Main contacts make contact

Make  
10 g

Mechanical shock resistance (IEC/EN 60068-2-27)  
Half-sinusoidal shock, 10 ms  
Basic unit with auxiliary contact module  
Auxiliary contacts Make/break contacts  
20/20 g

Degree of Protection  
IP20

Protection against direct contact when actuated  
from front (EN 50274)  
Finger and back-of-hand proof

Altitude  
Max. 2000 m

Weight  
0.206 kg

Terminal capacity of auxiliary and main contacts  
Screw terminals  
Solid  
1 x (0.75 - 2.5)  
2 x (0.75 - 2.5) mm<sup>2</sup>

Terminal capacity of auxiliary and main contacts  
Screw terminals  
Flexible with ferrule  
1 x (0.75 - 1.5)  
2 x (0.75 - 1.5) mm<sup>2</sup>

Terminal capacity of auxiliary and main contacts  
Screw terminals  
Solid or stranded  
18 - 14 AWG

Terminal capacity of auxiliary and main contacts  
Screw terminals  
Stripping length  
8 mm

Terminal capacity of auxiliary and main contacts  
Screw terminals  
Terminal screw  
M3.5

Terminal capacity of auxiliary and main contacts  
Screw terminals  
Pozidriv screwdriver  
2 Size

Terminal capacity of auxiliary and main contacts  
Screw terminals  
Standard screwdriver  
0.8 x 5.5  
1 x 6 mm

Terminal capacity of auxiliary and main contacts  
Screw terminals  
Max. tightening torque  
1.2 Nm

### Main conducting paths

Rated impulse withstand voltage [ $U_{imp}$ ]  
6000 V AC

Overvoltage category/pollution degree  
III/3

Rated insulation voltage [ $U_i$ ]  
690 V AC

Rated operational voltage [ $U_e$ ]  
690 V AC

Safe isolation to EN 61140  
between coil and contacts  
300 V AC

Safe isolation to EN 61140  
between the contacts  
300 V AC

Making capacity ( $\cos \phi$  to IEC/EN 60947)  
110 A

Breaking capacity  
220 V 230 V  
90 A

Breaking capacity  
380 V 400 V

90 A

Breaking capacity  
500 V  
64 A

Breaking capacity  
660 V 690 V  
42 A

Short-circuit protection maximum fuse  
Type "2", 500 V [gL/gG]  
10 A

Short-circuit protection maximum fuse  
Type "1", 500 V [gL/gG]  
20 A

## AC

AC-1  
Rated operational current  
Conventional free air thermal current, 3 pole, 50 -  
60 Hz  
Open  
at 40 °C [ $I_{th} = I_n$ ]  
22 A

AC-1  
Rated operational current  
Conventional free air thermal current, 3 pole, 50 -  
60 Hz  
Open  
at 50 °C [ $I_{th} = I_n$ ]  
20 A

AC-1  
Rated operational current  
Conventional free air thermal current, 3 pole, 50 -  
60 Hz  
Open  
at 55 °C [ $I_{th} = I_n$ ]  
19 A

AC-1  
Rated operational current  
Conventional free air thermal current, 3 pole, 50 -  
60 Hz  
enclosed [ $I_{th}$ ]  
16 A

AC-1  
Rated operational current  
Conventional free air thermal current, 3 pole, 50 -  
60 Hz  
Notes  
At maximum permissible ambient air temperature.

AC-1  
Rated operational current  
Conventional free air thermal current, 1 pole  
Notes  
At maximum permissible ambient air temperature.

AC-1  
Rated operational current  
Conventional free air thermal current, 1 pole  
open [ $I_{th}$ ]  
50 A

AC-1  
Rated operational current  
Conventional free air thermal current, 1 pole  
enclosed [ $I_{th}$ ]  
40 A

AC-3  
Rated operational current  
Open, 3-pole: 50 – 60 Hz  
Notes  
At maximum permissible ambient temperature  
(open.)  
Also tested according to AC-3e.

AC-3  
Rated operational current  
Open, 3-pole: 50 – 60 Hz  
220 V 230 V [ $I_e$ ]  
6.6 A

AC-3  
Rated operational current  
Open, 3-pole: 50 – 60 Hz  
240 V [ $I_e$ ]  
6.6 A

AC-3  
Rated operational current  
Open, 3-pole: 50 – 60 Hz  
380 V 400 V [ $I_e$ ]  
6.6 A

AC-3



Rated operational current  
Open, 3-pole: 50 – 60 Hz  
415 V [I<sub>e</sub>]  
6.6 A

AC-3  
Rated operational current  
Open, 3-pole: 50 – 60 Hz  
440V [I<sub>e</sub>]  
6.6 A

AC-3  
Rated operational current  
Open, 3-pole: 50 – 60 Hz  
500 V [I<sub>e</sub>]  
5 A

AC-3  
Rated operational current  
Open, 3-pole: 50 – 60 Hz  
660 V 690 V [I<sub>e</sub>]  
3.5 A

AC-3  
Motor rating [P]  
220 V 230 V [P]  
1.5 kW

AC-3  
Motor rating [P]  
240V [P]  
1.8 kW

AC-3  
Motor rating [P]  
380 V 400 V [P]  
3 kW

AC-3  
Motor rating [P]  
415 V [P]  
3.1 kW

AC-3  
Motor rating [P]  
440 V [P]  
3.3 kW

AC-3  
Motor rating [P]  
500 V [P]  
3 kW

AC-3  
Motor rating [P]  
660 V 690 V [P]  
3 kW

AC-4  
Rated operational current  
Open, 3-pole: 50 – 60 Hz  
Notes  
At maximum permissible ambient air temperature.

AC-4  
Rated operational current  
Open, 3-pole: 50 – 60 Hz  
220 V 230 V [ $I_e$ ]  
5 A

AC-4  
Rated operational current  
Open, 3-pole: 50 – 60 Hz  
240 V [ $I_e$ ]  
5 A

AC-4  
Rated operational current  
Open, 3-pole: 50 – 60 Hz  
380 V 400 V [ $I_e$ ]  
5 A

AC-4  
Rated operational current  
Open, 3-pole: 50 – 60 Hz  
415 V [ $I_e$ ]  
5 A

AC-4  
Rated operational current  
Open, 3-pole: 50 – 60 Hz  
440 V [ $I_e$ ]  
5 A

AC-4  
Rated operational current  
Open, 3-pole: 50 – 60 Hz  
500 V [ $I_e$ ]  
3.7 A

AC-4  
Rated operational current  
Open, 3-pole: 50 – 60 Hz

660 V 690 V [ $I_e$ ]  
2.9 A

AC-4  
Motor rating [P]  
220 V 230 V [P]  
1.1 kW

AC-4  
Motor rating [P]  
240 V [P]  
1.3 kW

AC-4  
Motor rating [P]  
380 V 400 V [P]  
2.2 kW

AC-4  
Motor rating [P]  
415 V [P]  
2.3 kW

AC-4  
Motor rating [P]  
440 V [P]  
2.4 kW

AC-4  
Motor rating [P]  
500 V [P]  
2.2 kW

AC-4  
Motor rating [P]  
660 V 690 V [P]  
2.2 kW

## DC

Rated operational current open  
DC-1  
12 V [ $I_e$ ]  
20 A

Rated operational current open  
DC-1  
24 V [ $I_e$ ]  
20 A

Rated operational current open  
DC-1  
60 V [ $I_e$ ]  
20 A

Rated operational current open  
DC-1  
110 V [ $I_e$ ]  
20 A

Rated operational current open  
DC-1  
220 V [ $I_e$ ]  
20 A

## Magnet systems

Voltage tolerance  
DC operated  
Pick-up voltage  
0.8 - 1.1

Power consumption  
DC operation  
Power consumption Pick-up = Sealing  
2.3 VA/W

Power consumption  
DC operation  
Notes  
Smoothed DC voltage or three-phase bridge  
rectifier

Duty factor  
100 % DF

Switching times at 100 %  $U_c$   
Make contact  
Closing delay  
Closing delay min.  
26 ms

Switching times at 100 %  $U_c$   
Make contact  
Closing delay  
Closing delay max.  
35 ms

Switching times at 100 %  $U_c$

Make contact  
Opening delay  
Opening delay min.  
15 ms

Switching times at 100 %  $U_c$   
Make contact  
Opening delay  
Opening delay max.  
25 ms

Switching times at 100 %  $U_c$   
Make contact  
Closing delay with top mounting auxiliary contact  
70 ms

Switching times at 100 %  $U_c$   
Reversing contactors  
Changeover time at 110 %  $U_c$   
Changeover time min.  
40 ms

Switching times at 100 %  $U_c$   
Reversing contactors  
Changeover time at 110 %  $U_c$   
Changeover time max.  
50 ms

Switching times at 100 %  $U_c$   
Reversing contactors  
Arcing time at 690 V AC  
12 ms

### Current heat losses (3- or 4-pole)

at  $I_{th}$ , 50 °C  
5.5 W

at  $I_c$  to AC-3/400 V  
0.6 W

Impedance per pole  
7.86 mΩ

### Auxiliary contacts

Positive operating contacts to EN 60947-5-1  
appendix L, including auxiliary contact module  
Yes

Rated impulse withstand voltage [ $U_{mp}$ ]  
6000 V AC

Overvoltage category/pollution degree  
III/3

Rated insulation voltage [ $U_i$ ]  
690 V AC

Rated operational voltage [ $U_e$ ]  
600 V AC

Safe isolation to EN61140  
between coil and auxiliary contacts  
300 V AC

Safe isolation to EN61140  
between the auxiliary contacts  
300 V AC

Rated operational current  
AC-15  
220 V 240 V [ $I_e$ ]  
6 A

Rated operational current  
AC-15  
380 V 415 V [ $I_e$ ]  
3 A

Rated operational current  
AC-15  
500 V [ $I_e$ ]  
1.5 A

Rated operational current  
DC L/R  $\square$  15 ms  
Contacts in series:  
1 [24 V]  
2.5 A

Rated operational current  
DC L/R  $\square$  15 ms  
Contacts in series:  
2 [60 V]  
2.5 A

Rated operational current  
DC L/R  $\square$  15 ms  
Contacts in series:  
3 [100 V]  
1.5 A

Rated operational current  
DC L/R  $\square$  15 ms  
Contacts in series:  
3 [220 V]  
0.5 A

Conv. thermal current [ $I_{th}$ ]  
10 A

Control circuit reliability [Failure rate]  
 $<10^{-8}$ , < one failure at 100 million operations  
(at  $U_e = 24$  V DC,  $U_{min} = 17$  V,  $I_{min} = 5.4$  mA)  $\lambda$

Component lifespan at  $U_e = 240$  V  
AC-15 [Operations]  
 $0.2 \times 10^6$

Component lifespan at  $U_e = 240$  V  
DC current  
L/R = 50 ms: 2 contacts in series at  $I_e = 0.5$  A  
[Operations]  
 $0.15 \times 10^6$

Component lifespan at  $U_e = 240$  V  
DC current  
Notes  
Switch-on and switch-off conditions based on  
DC-13, time constant as specified

Short-circuit rating without welding  
Maximum overcurrent protective device  
Short-circuit protection only  
PKZM0-4

Short-circuit rating without welding  
Short-circuit protection maximum fuse  
500 V  
6 A gG/gL

Short-circuit rating without welding  
Short-circuit protection maximum fuse  
500 V  
10 A fast

Current heat loss at a load of  $I_{th}$  per contact  
1.1 W

### Rating data for approved types

Switching capacity  
Maximum motor rating  
Three-phase  
200 V  
208 V  
1.5 HP

Switching capacity  
Maximum motor rating  
Three-phase  
230 V  
240 V  
2 HP

Switching capacity  
Maximum motor rating  
Three-phase  
460 V  
480 V  
3 HP

Switching capacity  
Maximum motor rating  
Three-phase  
575 V  
600 V  
3 HP

Switching capacity  
Maximum motor rating  
Single-phase  
115 V  
120 V  
0.25 HP

Switching capacity  
Maximum motor rating  
Single-phase  
230 V  
240 V  
1 HP

Switching capacity  
General use  
15 A



Auxiliary contacts  
Pilot Duty  
AC operated  
A600

Auxiliary contacts  
Pilot Duty  
DC operated  
P300

Auxiliary contacts  
General Use  
AC  
600 V

Auxiliary contacts  
General Use  
AC  
10 A

Auxiliary contacts  
General Use  
DC  
250 V

Auxiliary contacts  
General Use  
DC  
0.5 A

Short Circuit Current Rating  
Basic Rating  
SCCR  
5 kA

Short Circuit Current Rating  
Basic Rating  
max. Fuse  
45 A

## DESIGN VERIFICATION AS PER IEC/EN 61439

### Technical data for design verification

Rated operational current for specified heat  
dissipation [ $I_n$ ]

Heat dissipation per pole, current-dependent [ $P_{\text{vd}}$ ]  
0.2 W

Equipment heat dissipation, current-dependent  
[ $P_{\text{vd}}$ ]  
0.6 W

Static heat dissipation, non-current-dependent [ $P_{\text{vs}}$ ]  
2.3 W

Heat dissipation capacity [ $P_{\text{diss}}$ ]  
0 W

Operating ambient temperature min.  
-25 °C

Operating ambient temperature max.  
+50 °C

### IEC/EN 61439 design verification

10.2 Strength of materials and parts  
10.2.2 Corrosion resistance  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.1 Verification of thermal stability of  
enclosures  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.2 Verification of resistance of insulating  
materials to normal heat  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.3 Verification of resistance of insulating  
materials to abnormal heat and fire due to internal  
electric effects  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.4 Resistance to ultra-violet (UV) radiation  
Meets the product standard's requirements.

10.2 Strength of materials and parts

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9 Insulation properties

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9 Insulation properties

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9 Insulation properties

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

#### 10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

#### 10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

#### 10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

#### 10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## TECHNICAL DATA ETIM 7.0

Low-voltage industrial components (EG000017) / Power contactor, AC switching (EC000066)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Power contactor, AC switching (ecl@ss10.0.1-27-37-10-03 [AAB718015])

Rated control supply voltage  $U_s$  at AC 50-HZ  
0 - 0 V

Rated control supply voltage  $U_s$  at AC 60-HZ  
0 - 0 V

Rated control supply voltage  $U_s$  at DC  
24 - 24 V

Voltage type for actuating  
DC

Rated operation current  $I_e$  at AC-1, 400 V  
22 A

Rated operation current  $I_e$  at AC-3, 400 V  
6.6 A

Rated operation power at AC-3, 400 V  
3 kW

Rated operation current  $I_e$  at AC-4, 400 V  
5 A

Rated operation power at AC-4, 400 V  
2.2 kW

Rated operation power NEMA  
2.2 kW

Modular version  
No

Number of auxiliary contacts as normally open  
contact  
0

Number of auxiliary contacts as normally closed  
contact  
1

Type of electrical connection of main circuit  
Screw connection

Number of normally closed contacts as main  
contact  
0

Number of main contacts as normally open contact  
3

## APPROVALS

Product Standards  
IEC/EN 60947-4-1; UL 508; CSA-C22.2 No. 14-05;  
CE marking

UL File No.  
E29096

UL Category Control No.  
NLDX


CSA File No.  
012528

CSA Class No.  
3211-04

North America Certification  
UL listed, CSA certified

Specially designed for North America  
No

## CHARACTERISTICS



### Accessories

- 1: Overload relay
  - 2: Suppressor
  - 3: Auxiliary contact modules
- Enclosure totally insulated

### Characteristic curve



Switching duty for non-motor loads, 3-pole, 4-pole  
Operating characteristics  
Non-inductive or slightly inductive loads  
Electrical characteristics  
Make: 1 x rated current  
Break: 1 x rated current  
Utilization category  
100 % AC-1  
Typical applications

Electric heat

Characteristic curve

Short-time loading, 3-pole  
Time interval between two loading cycles: 15  
minutes

**DIMENSIONS**

2DILE... + M/DILE + ...DILE  
2DILE...-G + M/DILE + ...DILE

2DILE... + M/DILE + ...DILE  
2DILE...-G + M/DILE + ...DILE

2DILE... + M/DILE  
2DILE...-G + M/DILE



