



139559
DILM 300A-S/22(220-240V50/60HZ)

[Overview](#)

[Specifications](#)

[Resources](#)



[Delivery program](#)

[Technical data](#)

[Design verification as per
IEC/EN 61439](#)

[Technical data ETIM 7.0](#)

[Approvals](#)

[Characteristics](#)

[Dimensions](#)

DELIVERY PROGRAM

Product range
Contactors

Application
Contactors for Motors

Subrange
Standard devices greater than 170 A

Utilization category
AC-1: Non-inductive or slightly inductive loads, resistance
furnaces
NAC-3: Normal AC induction motors: starting, switch off
during running
AC-4: Normal AC induction motors: starting, plugging,
reversing, inching

Connection technique
Screw connection

Rated operational current

AC-3
380 V 400 V [I_n]
300 A

AC-1
Conventional free air thermal current, 3 pole, 50 - 60 Hz
Open
at 40 °C [$I_{th} = I_n$]
490 A

AC-1
Conventional free air thermal current, 3 pole, 50 - 60 Hz
enclosed [I_{th}]

315 A

AC-1
Conventional free air thermal current, 1 pole
open [I_{th}]
875 A

AC-1
Conventional free air thermal current, 1 pole
enclosed [I_{th}]
785 A

Max. rating for three-phase motors, 50 - 60 Hz

AC-3
220 V 230 V [F]
90 kW

AC-3
380 V 400 V [F]
160 kW

AC-3
660 V 690 V [F]
170 kW

AC-3
1000 V [F]
132 kW

AC-4
220 V 230 V [F]
75 kW

AC-4
380 V 400 V [F]
132 kW

AC-4
660 V 690 V [F]
137 kW

AC-4
1000 V [F]
108 kW

Contact sequence



Can be combined with auxiliary contact
DILM820-XH...

Actuating voltage
220 - 240 V 50/60 Hz

Voltage AC/DC
AC operation

Contacts


N/O = Normally open
2 N/O

N/C = Normally closed
2 NC

Auxiliary contacts

possible variants at auxiliary contact module fitting options
on the side: 2 x DILM820-XH11(V)-SI; 2 x DILM820-XH11-
SA

Side mounting auxiliary contacts



Instructions

Interlocked opposing contacts according to IEC/EN 60947-5-
1 Appendix L, inside the auxiliary contact module
Auxiliary contacts used as mirror contacts according to
IEC/EN 60947-4-1 Appendix F (not NC late open)

Instructions

integrated suppressor circuit in actuating electronics
660 V, 690 V or 1000 V: not directly reversing

Notes

DILM...-S power contactors are actuated traditionally
<input type="checkbox"/> Stopping in the event of an emergency (emergency switching off)

TECHNICAL DATA

General

Standards
IEC/EN 60947, VDE 0660, UL, CSA

Lifespan, mechanical
AC operated [Operations]
10 x 10⁶

Operating frequency, mechanical
AC operated [Operations/h]
3000

Climatic proofing
Damp heat, constant, to IEC 60068-2-78


Damp heat, cyclic, to IEC 60068-2-30

Ambient temperature
Open
-40 - +60 °C

Ambient temperature
Enclosed
- 40 - + 40 °C

Ambient temperature
Storage
- 40 - + 80 °C

Mounting position



Mechanical shock resistance (IEC/EN 60068-2-27)
Half-sinusoidal shock, 10 ms
Main contacts
N/O contact
10 g

Mechanical shock resistance (IEC/EN 60068-2-27)
Half-sinusoidal shock, 10 ms
Auxiliary contacts
N/O contact
10 g

Mechanical shock resistance (IEC/EN 60068-2-27)
Half-sinusoidal shock, 10 ms
Auxiliary contacts
N/C contact
8 g

Degree of Protection
IP00

Protection against direct contact when actuated from front
(EN 50274)
Finger and back-of-hand proof with terminal shroud or
terminal block

Altitude
Max. 2000 m

Weight
AC operated
7.1 kg

Weight
DC operated
7.1 kg

Weight
Weight
7.1 kg

Terminal capacity main cable
Flexible with cable lug
50 - 240 mm²

Terminal capacity main cable
Stranded with cable lug
70 - 240 mm²

Terminal capacity main cable
Solid or stranded
2/0 - 500 MCM AWG

Terminal capacity main cable
Flat conductor [Lamellenzahl x Breite x Dicke]
Fixing with flat cable terminal or cable terminal blocks
See terminal capacity for cable terminal blocks mm

Terminal capacity main cable
Busbar [Width]
25 mm

Main cable connection screw/bolt
M10

Tightening torque
24 Nm

Terminal capacity control circuit cables
Solid
1 x (0.75 - 2.5)
2 x (0.75 - 2.5) mm²

Terminal capacity control circuit cables
Flexible with ferrule
1 x (0.75 - 2.5)
2 x (0.75 - 2.5) mm²

Terminal capacity control circuit cables
Solid or stranded
18 - 14 AWG

Control circuit cable connection screw/bolt
M3.5

Tightening torque
1.2 Nm

Tool
Main cable
Width across flats
16 mm

Tool
Control circuit cables
Pozidriv screw driver
2 Size

Main conducting paths

Rated impulse withstand voltage [U_{imp}]
8000 V AC

Overvoltage category/pollution degree
III/3

Rated insulation voltage [U_i]
1000 V AC

Rated operational voltage [U_o]
1000 V AC

Safe isolation to EN 61140
between coil and contacts
500 V AC

Safe isolation to EN 61140
between the contacts
500 V AC

Making capacity (p.f. to IEC/EN 60947)
3600 A

Breaking capacity
220 V 230 V
3000 A

Breaking capacity
380 V 400 V
3000 A

Breaking capacity
500 V
3000 A

Breaking capacity
660 V 690 V
3000 A

Breaking capacity
1000 V
950 A

Component lifespan
AC1: See → Engineering, characteristic curves
AC3: See → Engineering, characteristic curves
AC4: See → Engineering, characteristic curves

Short-circuit rating
Short-circuit protection maximum fuse
Type "2" coordination
400 V [gG/gL 500 V]
400 A

Short-circuit rating
Short-circuit protection maximum fuse
Type "2" coordination
690 V [gG/gL 690 V]
315 A

Short-circuit rating
Short-circuit protection maximum fuse
Type "2" coordination
1000 V [gG/gL 1000 V]
160 A

Short-circuit rating
Short-circuit protection maximum fuse
Type "1" coordination
400 V [gG/gL 500 V]
400 A

Short-circuit rating
Short-circuit protection maximum fuse
Type "1" coordination
690 V [gG/gL 690 V]
400 A

Short-circuit rating
Short-circuit protection maximum fuse
Type "1" coordination
1000 V [gG/gL 1000 V]
200 A

AC

AC-1
Rated operational current
Conventional free air thermal current, 3 pole, 50 - 60 Hz
Open
at 40 °C [$I_{th} = I_e$]
490 A

AC-1
Rated operational current
Conventional free air thermal current, 3 pole, 50 - 60 Hz
Open
at 50 °C [$I_{th} = I_e$]
438 A

AC-1
Rated operational current
Conventional free air thermal current, 3 pole, 50 - 60 Hz
Open
at 55 °C [$I_{th} = I_e$]
418 A

AC-1
Rated operational current
Conventional free air thermal current, 3 pole, 50 - 60 Hz
Open
at 60 °C [$I_{th} = I_e$]
400 A

AC-1
Rated operational current
Conventional free air thermal current, 3 pole, 50 - 60 Hz
enclosed [I_{th}]
315 A

AC-1
Rated operational current
Conventional free air thermal current, 3 pole, 50 - 60 Hz
Notes
At maximum permissible ambient air temperature.

AC-1
Rated operational current
Conventional free air thermal current, 1 pole
Note
at maximum permissible ambient air temperature

AC-1
Rated operational current
Conventional free air thermal current, 1 pole
open [I_{th}]
875 A

AC-1
Rated operational current
Conventional free air thermal current, 1 pole
enclosed [I_{th}]
785 A

AC-3
Rated operational current
Open, 3-pole: 50 – 60 Hz
Notes
At maximum permissible ambient temperature (open.)

AC-3
Rated operational current
Open, 3-pole: 50 – 60 Hz
220 V 230 V [I_e]
300 A

AC-3
Rated operational current
Open, 3-pole: 50 – 60 Hz
240 V [I_e]
300 A

AC-3
Rated operational current
Open, 3-pole: 50 – 60 Hz
380 V 400 V [I_e]
300 A

AC-3
Rated operational current
Open, 3-pole: 50 – 60 Hz
415 V [I_e]
300 A

AC-3
Rated operational current
Open, 3-pole: 50 – 60 Hz
440 V [I_e]
300 A

AC-3
Rated operational current
Open, 3-pole: 50 – 60 Hz
500 V [I_e]
300 A

AC-3
Rated operational current
Open, 3-pole: 50 – 60 Hz
660 V 690 V [I_e]

185 A

AC-3
Rated operational current
Open, 3-pole: 50 – 60 Hz
1000 V [I_b]
95 A

AC-3
Motor rating [P]
220 V 230 V [P]
90 kW

AC-3
Motor rating [P]
240V [P]
100 kW

AC-3
Motor rating [P]
380 V 400 V [P]
160 kW

AC-3
Motor rating [P]
415 V [P]
175 kW

AC-3
Motor rating [P]
440 V [P]
185 kW

AC-3
Motor rating [P]
500 V [P]
210 kW

AC-3
Motor rating [P]
660 V 690 V [P]
170 kW

AC-3
Motor rating [P]
1000 V [P]
132 kW

AC-4
Rated operational current
Open, 3-pole: 50 – 60 Hz
220 V 230 V [I_b]
240 A

AC-4
Rated operational current
Open, 3-pole: 50 – 60 Hz
240 V [I_b]
240 A

AC-4
Rated operational current
Open, 3-pole: 50 – 60 Hz

380 V 400 V [I_e]
240 A

AC-4
Rated operational current
Open, 3-pole: 50 – 60 Hz
415 V [I_e]
240 A

AC-4
Rated operational current
Open, 3-pole: 50 – 60 Hz
440 V [I_e]
240 A

AC-4
Rated operational current
Open, 3-pole: 50 – 60 Hz
500 V [I_e]
240 A

AC-4
Rated operational current
Open, 3-pole: 50 – 60 Hz
660 V 690 V [I_e]
150 A

AC-4
Rated operational current
Open, 3-pole: 50 – 60 Hz
1000 V [I_e]
76 A

AC-4
Motor rating [P]
220 V 230 V [P]
75 kW

AC-4
Motor rating [P]
240 V [P]
82 kW

AC-4
Motor rating [P]
380 V 400 V [P]
132 kW

AC-4
Motor rating [P]
415 V [P]
142 kW

AC-4
Motor rating [P]
440 V [P]
150 kW

AC-4
Motor rating [P]
500 V [P]
170 kW

AC-4
Motor rating [P]
660 V 690 V [P]
137 kW

AC-4
Motor rating [P]
1000 V [P]
108 kW

Condensor operation

Individual compensation, rated operational current I_b of
three-phase capacitors
Open
up to 525 V
307 A

Individual compensation, rated operational current I_b of
three-phase capacitors
Open
690 V
177 A

Max. inrush current peak
 $30 \times I_b$

Component lifespan [Operations]
 0.1×10^6

Max. operating frequency
200 Ops/h

DC

Rated operational current, open
DC-1
Notes
see DILDC300/DILDC600 or on request

Current heat loss

3 pole, at I_{th} (60°)
37 W

Current heat loss at I_b to AC-3/400 V
21 W

Magnet systems

Voltage tolerance
 U_S
220 - 240 V 50/60 Hz

Voltage tolerance
AC operated [Pick-up]
 $0.85 \times U_{Smin} - 1.1 \times U_{Smax}$

Voltage tolerance
AC operated [Drop-out]
 $0.2 \times U_{S\min} - 0.4 \times U_{S\max}$

Power consumption of the coil in a cold state and $1.0 \times U_S$
Note on power consumption
Control transformer with $u_k \leq 10\%$

Power consumption of the coil in a cold state and $1.0 \times U_S$
Pull-in power [Pick-up]
360 VA

Power consumption of the coil in a cold state and $1.0 \times U_S$
Pull-in power [Pick-up]
325 W

Power consumption of the coil in a cold state and $1.0 \times U_S$
Sealing power [Sealing]
7.3 VA

Power consumption of the coil in a cold state and $1.0 \times U_S$
Sealing power [Sealing]
4.8 W

Duty factor
100 % DF

Changeover time at 100 % U_S (recommended value)
Main contacts
Closing delay
55 ms

Changeover time at 100 % U_S (recommended value)
Main contacts
Opening delay
40 ms

Behaviour in marginal and transitional conditions
Sealing
Voltage interruptions
($0 \dots 0.2 \times U_{c\min}$) ≤ 10 ms
Time is bridged successfully

Behaviour in marginal and transitional conditions
Sealing
Voltage interruptions
($0 \dots 0.2 \times U_{c\min}$) > 10 ms
Drop-out of the contactor

Behaviour in marginal and transitional conditions
Sealing
Voltage drops
($0.2 \dots 0.6 \times U_{c\min}$) ≤ 12 ms
Time is bridged successfully

Behaviour in marginal and transitional conditions
Sealing
Voltage drops
($0.2 \dots 0.6 \times U_{c\min}$) > 12 ms
Drop-out of the contactor

Behaviour in marginal and transitional conditions
Sealing
Voltage drops
($0.6 \dots 0.7 \times U_{c, \min}$)
Contactor remains switched on

Behaviour in marginal and transitional conditions
Sealing
Excess voltage
($1.15 \dots 1.3 \times U_{c, \max}$)
Contactor remains switched on

Behaviour in marginal and transitional conditions
Sealing
Pick-up phase
($0 \dots 0.7 \times U_{c, \min}$)
Contactor does not switch on

Behaviour in marginal and transitional conditions
Sealing
Pick-up phase
($0.7 \times U_{c, \min} \dots 1.15 \times U_{c, \max}$)
Contactor switches on with certainty

Admissible transitional contact resistance (of the external
control circuit device when actuating A11)
☐ 500 mΩ

Electromagnetic compatibility (EMC)

Electromagnetic compatibility
This product is designed for operation in industrial
environments (environment A). Its use in residential
environments (environment B) may cause radio-frequency
interference, requiring additional noise suppression
measures.

Rating data for approved types

Switching capacity
Maximum motor rating
Three-phase
200 V
208 V
100 HP

Switching capacity
Maximum motor rating
Three-phase
230 V
240 V
125 HP

Switching capacity
Maximum motor rating
Three-phase
460 V
480 V
250 HP

Switching capacity
Maximum motor rating
Three-phase
575 V
600 V

300 HP

Switching capacity
General use
350 A

Auxiliary contacts
Flot Duty
AC operated
A600

Auxiliary contacts
Flot Duty
DC operated
P300

Auxiliary contacts
General Use
AC
600 V

Auxiliary contacts
General Use
AC
15 A

Auxiliary contacts
General Use
DC
250 V

Auxiliary contacts
General Use
DC
1 A

Short Circuit Current Rating
Basic Rating
SCCR
18 kA

Short Circuit Current Rating
Basic Rating
max. Fuse
700 A

Short Circuit Current Rating
Basic Rating
max. CB
600 A

Short Circuit Current Rating
480 V High Fault
SCCR (fuse)
18 kA

Short Circuit Current Rating
480 V High Fault
max. Fuse
700 Class L A

Short Circuit Current Rating

480 V High Fault
SCCR (CB)
65 kA

Short Circuit Current Rating
480 V High Fault
max. CB
250 A

Short Circuit Current Rating
600 V High Fault
SCCR (fuse)
18 kA

Short Circuit Current Rating
600 V High Fault
max. Fuse
700 Class J A

Short Circuit Current Rating
600 V High Fault
SCCR (CB)
18 kA

Short Circuit Current Rating
600 V High Fault
max. CB
600 A

Special Purpose Ratings
Definite Purpose Ratings (100,000 cycles acc. to UL 1995)
LRA 480V 60Hz 3phase
2160 A

Special Purpose Ratings
Definite Purpose Ratings (100,000 cycles acc. to UL 1995)
FLA 480V 60Hz 3phase
360 A

Special Purpose Ratings
Definite Purpose Ratings (100,000 cycles acc. to UL 1995)
LRA 600V 60Hz 3phase
1800 A

Special Purpose Ratings
Definite Purpose Ratings (100,000 cycles acc. to UL 1995)
FLA 600V 60Hz 3phase
300 A

DESIGN VERIFICATION AS PER IEC/EN 61439

Technical data for design verification

Rated operational current for specified heat dissipation [I_n]
300 A

Heat dissipation per pole, current-dependent [P_{vd}]
7 W

Equipment heat dissipation, current-dependent [P_{ed}]
0 W

Static heat dissipation, non-current-dependent [P_{st}]
4.8 W

Heat dissipation capacity [P_{diss}]
0 W

Operating ambient temperature min.
-40 °C

Operating ambient temperature max.
+60 °C

IEC/EN 61439 design verification

10.2 Strength of materials and parts
10.2.2 Corrosion resistance
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.1 Verification of thermal stability of enclosures
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.2 Verification of resistance of insulating materials to
normal heat
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.3 Verification of resistance of insulating materials to
abnormal heat and fire due to internal electric effects
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.4 Resistance to ultra-violet (UV) radiation
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.5 Lifting
Does not apply, since the entire switchgear needs to be
evaluated.

10.2 Strength of materials and parts
10.2.6 Mechanical impact
Does not apply, since the entire switchgear needs to be
evaluated.

10.2 Strength of materials and parts
10.2.7 Inscriptions
Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES
Does not apply, since the entire switchgear needs to be
evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9 Insulation properties

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9 Insulation properties

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9 Insulation properties

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

TECHNICAL DATA ETIM 7.0

Low-voltage industrial components (EG000017) / Power contactor, AC switching (EC000066)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Power contactor, AC switching (ecl@ss10.0.1-27-37-10-03 [AAB718015])

Rated control supply voltage U_s at AC 50Hz

220 - 240 V

Rated control supply voltage U_s at AC 60Hz
220 - 240 V

Rated control supply voltage U_s at DC
0 - 0 V

Voltage type for actuating
AC

Rated operation current I_e at AC-1, 400 V
490 A

Rated operation current I_e at AC-3, 400 V
300 A

Rated operation power at AC-3, 400 V
160 kW

Rated operation current I_e at AC-4, 400 V
240 A

Rated operation power at AC-4, 400 V
132 kW

Rated operation power NEMA
186 kW

Modular version
No

Number of auxiliary contacts as normally open contact
2

Number of auxiliary contacts as normally closed contact
2

Type of electrical connection of main circuit
Rail connection

Number of normally closed contacts as main contact
0

Number of main contacts as normally open contact
3

APPROVALS

Product Standards
IEC/EN 60947-4-1; UL 60947-4-1; CSA - C22.2 No. 60947-4-1-14; CE marking

UL File No.
E29096

UL Category Control No.
NLDX

CSA File No.
1017510


CSA Class No.
3211-04

North America Certification
UL listed, CSA certified

Specially designed for North America
No

CHARACTERISTICS

Side mounting auxiliary contacts



possible variants at auxiliary contact module fitting options
on the side: 2 x DILMB20-XH11(V)-S; 2 x DILMB20-XH11-
SA

Characteristic curve



Normal switching duty
Normal AC induction motor
Operating characteristics
Switch on: from stop
Switch off: during run
Electrical characteristics:
Switch on: up to 6 x Rated motor current
Switch off: up to 1 x Rated motor current
Utility category
100 % AC-3
Typical Applications
Compressors
Lifts
Mixers
Pumps
Escalators
Agitators
fan
Conveyor belts
Centrifuges
Hinged flaps
Bucket-elevator
Air-conditioning systems
General drives for manufacturing and processing machines

Characteristic curve



Extreme switching duty
Squirrel-cage motor

Operating characteristics
Inching, plugging, reversing
Electrical characteristics
Make: up to 6 x rated motor current
Break: up to 6 x rated motor current
Utilization category
100 % AC-4
Typical applications
Printing presses
Wire-drawing machines
Centrifuges
Special drives for manufacturing and processing machines

Characteristic curve



Switching conditions for 3 pole, non-motor loads
Operating characteristics
Non inductive and slightly inductive loads
Electrical characteristics
Switch on: 1 x rated operational current
Switch off: 1 x rated operational current
Utilization category
100 % AC-1
Typical examples of application
Electric heat

Characteristic curve



Short-time loading, 3-pole
Time interval between two loading cycles: 15 minutes

DIMENSIONS



- ☐ DILM820-XH11(V)-SI
- ☐ DILM820-XH11-SA



