



Replacement coil, RA 250: 110 - 250 V 40-60 Hz/110 - 250 V DC, AC operation, For use with: DILM580, DILM650, DILM750, DILM820, DILM1000

Part no. DILM1000-XSP/E(RA250)
Catalog No. 289145
Alternate Catalog No. XTGERENCOILNA
EL-Nummer (Norway) 4130510

Delivery program

Actuating voltage		RA 250: 110 - 250 V 40-60 Hz/110 - 250 V DC
Voltage AC/DC		AC and DC operation
For use with		DILM580 DILM650 DILM750 DILM820 DILM1000

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-40
Operating ambient temperature max.		°C	60

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Coil for relay (EC001043)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Reel for contactor (ecl@ss10.0.1-27-37-10-12 [AKF021013])			
Rated control supply voltage Us at AC 50HZ		V	110 - 250
Rated control supply voltage Us at AC 60HZ		V	110 - 250
Rated control supply voltage Us at DC		V	110 - 250
Voltage type for actuating			AC/DC

Approvals

Product Standards		IEC/EN 60947-4-1; UL 508; CSA-C22.2 No. 14-05; CE marking
UL File No.		E29096
UL Category Control No.		NLDX
CSA File No.		012528
CSA Class No.		3211-04
North America Certification		UL listed, CSA certified
Specially designed for North America		No