

Select your language

- German
- English
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



CI-K4-160-M - Insulated enclosure, HkWxD=240x160x160mm, +mounting plate



206898 CI-K4-160-M

[Overview](#) [Specifications](#) [Resources](#)



- Delivery program
- Technical data
- Design verification as per IEC/EN 61439
- Technical data ETIM 7.0
- Dimensions

# 206898 CI-K4-160-M


Insulated enclosure, HkWxD=240x160x160mm, +mounting plate  
EL-Nummer (Norway)

0004138011

Insulated enclosure, With mounting plate, Product range: CI-K small enclosures, Basic enclosures, Single unit, Degree of Protection: Front IP65, IP65, with push-through cable entry, Material: Glass-fibre reinforced polycarbonate, Colour: Enclosure base RAL 9005, black, Operator only RAL 7035, light gray, Description: Metric cable entry knockouts top, bottom and in the back plate, Control cable entry, Lamp indicator L-... can be mounted in base knock-out M20/M25, Cable entry: hard knockout version, Dimensions Width: 160 mm, Height: 240 mm, Depth: 160 mm, Mounting depth with mounting plate: 133 mm, Standards: IEC/EN 60529, DIN EN 62208

## Delivery program

Product range  
CI-K small enclosures  
Basic function  
Basic enclosures  
Product function  
CI-K empty enclosures  
Single unit/Complete unit  
Single unit  
Degree of Protection  
Front IP65  
IP65, with push-through cable entry  
Degree of Protection  
Front IP65  
IP65, with push-through cable entry  
Material  
Glass-fibre reinforced polycarbonate  
Colour  
Enclosure base RAL 9005, black  
Operator only RAL 7035, light gray  
Description  
Metric cable entry knockouts top, bottom and in the back plate  
Control cable entry  
Lamp indicator L-... can be mounted in base knock-out M20/M25  
Cable entry  
hard knockout version  
Dimensions  
Width  
160 mm  
Height  
240 mm  
Depth  
160 mm  
Dimensions



Enclosure depth  
Legend for the graphic  
Dimensions from top:

Mounting depth with mounting plate  
 Mounting depth for mounting rail 7.5 mm height  
 Mounting depth for mounting rail 15 mm height  
 Enclosure depth



Mounting depth with mounting plate  
 133 mm

Features  
 With mounting plate

#### Notes

|                          |
|--------------------------|
| <b>O</b>                 |
|                          |
| Knockouts                |
| 2 x M32/25               |
| 1 x M20                  |
| <b>V</b>                 |
| <input type="checkbox"/> |
| Back plate:              |
| 2 x M32/25               |

## Technical data

General  
 Standards  
 IEC/EN 60529  
 DIN EN 62208  
 Climatic proofing  
 Damp heat, constant, to IEC 60068-2-78  
 Damp heat, cyclic, to IEC 60068-2-30  
 Ambient temperature  
 -25 - +70  
 -25 - +40 (with push-through cable entry) °C  
 Degree of Protection  
 Front IP65  
 IP65, with push-through cable entry  
 Power lossMax. radiated heat dissipation with separate mounting, ambient air temperature +20 °C  
 29.5 W  
 Material characteristics  
 MaterialBase  
 Glass-fibre reinforced polycarbonate  
 MaterialCover  
 Glass-fibre reinforced polycarbonate  
 Surface treatment  
 Resistant to corrosion  
 ColourBase  
 RAL 9005, black (matt)  
 ColourHousing body  
 Enclosure cover RAL 7035, light grey (matt)  
 Material properties  
 ElectricalTrack resistance  
 CTI 175 (base, to IEC 60112)  
 CTI 175 (cover, to IEC 60112)  
 ElectricalSurface resistance to IEC 60093  
 $1 \Omega \times 10^{13}$   
 ElectricalDielectric strength to IEC 60243-1  
 30 kV/mm  
 ThermalTemperature resistant  
 -40 °C - 120 °C (enclosure)  
 -40 °C - +80 °C (gasket)  
 MechanicalImpact resistance  
 IK06 according to EN 50102  
 Mechanicalmax. assembly weightsMounting plate  
 0.9 kg  
 Mechanicalmax. assembly weightsMounting rail  
 0.9 kg  
 Chemical resistanceChemical resistant  
 Base, Cover  
 Resistant against: Acids < 10 %, mineral oil, alcohol, gasoline, greases, salt solutions  
 Partly resistant to: Acids > 10 %, alcohol  
 Not resistant to: alkalis, benzene  
 Push-through membrane (G-K1/G-K2) and sealing material  
 Resistant against: Acids < 10 %, alkalis, benzene, salt solutions  
 Partly resistant to: Acids > 10 %, greases, benzene  
 Not resistant to: Mineral oil, benzene  
 AtmosphericSaline spray  
 IEC 60068-2-11  
 AtmosphericUV resistance  
 Beneath protective shield  
 AtmosphericWater consumption to DIN EN ISO 62

0.29 %  
 Flammability characteristicsGlow wire testFlammability characteristics  
 960 °C/1mmthickness (base, cover; glow wire to VDE 0471 Part 2)  
 650 °C/1mmthick (push-through membrane) to VDE 0471 Part 2)  
 Flammability characteristicsGlow wire testto UL 94  
 V0/1.5 mmthickness  
 Flammability characteristicsGlow wire testto UL 94  
 HB  
 Flammability characteristicsHalogen free  
 Yes

## Design verification as per IEC/EN 61439

Technical data for design verification  
 Rated operational current for specified heat dissipation [ $I_n$ ]  
 0 A  
 Heat dissipation per pole, current-dependent [ $P_{rd}$ ]  
 0 W  
 Equipment heat dissipation, current-dependent [ $P_{rd}$ ]  
 0 W  
 Static heat dissipation, non-current-dependent [ $P_{rs}$ ]  
 0 W  
 Heat dissipation capacity [ $P_{diss}$ ]  
 29.5 W  
 Operating ambient temperature min.  
 -25 °C  
 Operating ambient temperature max.  
 +70 °C  
 Degree of Protection  
 Front IP65  
 IP65, with push-through cable entry  
 Max. radiated heat dissipation with separate mounting, ambient air temperature +20 °C  
 29.5 W  
 Flammability characteristics  
 960 °C/1mmthickness (base, cover; glow wire to VDE 0471 Part 2)  
 650 °C/1mmthick (push-through membrane) to VDE 0471 Part 2)  
 Track resistance  
 CTI 175 (base, to IEC 60112)  
 CTI 175 (cover, to IEC 60112)  
 Surface treatment  
 Resistant to corrosion  
 Impact resistance  
 IK06 according to EN 50102  
 Temperature resistant  
 -40 °C- 120 °C (enclosure)  
 -40 °C- +80 °C (gasket)  
 UV resistance  
 Beneath protective shield  
 IEC/EN 61439 design verification  
 10.2 Strength of materials and parts10.2.2 Corrosion resistance  
 Meets the product standard's requirements.  
 10.2 Strength of materials and parts10.2.3.1 Verification of thermal stability of enclosures  
 Meets the product standard's requirements.  
 10.2 Strength of materials and parts10.2.3.2 Verification of resistance of insulating materials to normal heat  
 Meets the product standard's requirements.  
 10.2 Strength of materials and parts10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects  
 Meets the product standard's requirements.  
 10.2 Strength of materials and parts10.2.4 Resistance to ultra-violet (UV) radiation  
 Please enquire  
 10.2 Strength of materials and parts10.2.5 Lifting  
 Not applicable.  
 10.2 Strength of materials and parts10.2.6 Mechanical impact  
 Does not apply, since the entire switchgear needs to be evaluated.  
 10.2 Strength of materials and parts10.2.7 Inscriptions  
 Meets the product standard's requirements.  
 10.3 Degree of protection of ASSEMBLIES  
 Meets the product standard's requirements.  
 10.4 Clearances and creepage distances  
 Meets the product standard's requirements.  
 10.5 Protection against electric shock  
 Does not apply, since the entire switchgear needs to be evaluated.  
 10.6 Incorporation of switching devices and components  
 Does not apply, since the entire switchgear needs to be evaluated.  
 10.7 Internal electrical circuits and connections  
 Is the panel builder's responsibility.  
 10.8 Connections for external conductors  
 Is the panel builder's responsibility.  
 10.9 Insulation properties10.9.2 Power-frequency electric strength  
 Is the panel builder's responsibility.  
 10.9 Insulation properties10.9.3 Impulse withstand voltage  
 Is the panel builder's responsibility.  
 10.9 Insulation properties10.9.4 Testing of enclosures made of insulating material  
 Meets the product standard's requirements.  
 10.10 Temperature rise  
 The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.  
 10.11 Short-circuit rating  
 Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility  
Is the panel builder's responsibility. The specifications for the switchgear must be observed.  
10.13 Mechanical function  
The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Empty enclosure for switchgear (EC000712)  
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Empty housing for switch devices (ecl@ss10.0.1-27-37-13-01 [AKN343014])  
Material housing  
Plastic  
Width  
160 mm  
Height  
240 mm  
Depth  
160 mm  
With transparent cover  
No  
Suitable for emergency stop  
Yes  
Model  
Surface mounting  
Degree of protection (IP)  
IP65  
Degree of protection (NEMA)  
Other

## Dimensions



## CAD data

- [Product-specific CAD data](#)  
(Web)
- [3D Preview](#)  
(Web)
- [DA-CD-ci\\_k4\\_m](#)  
CAD data  
DWG files  
(Web)
- [DA-CE-ETN-Q-K4-160-M](#)  
CAD data  
edz files  
(Web)
- [DA-CS-ci\\_k\\_m\\_8](#)  
CAD data  
Step files  
(Web)

## Dimensions single product

-   
[Dimensions](#)  
Dimensions single product  
Line drawing  
Mounting depth
-   
[Enclosure depth](#)  
Dimensions single product  
Line drawing  
Mounting depth
- [461X030](#)  
Dimensions single product  
Line drawing  
Q-K small enclosure

## Product photo



## Instruction Leaflet

- [Insulated small enclosures \(IL01502081Z\)](#)  
Instruction Leaflet  
(PDF, International)

## Declaration of Conformity

- [DA-DC-00002809](#)  
Declaration of Conformity  
(PDF)

## Download-Center

- [Download-Center \(this item\)](#)  
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)  
Eaton EMEA Download-Center

 [Generate data sheet in PDF format](#)  
 [Generate data sheet in Excel format](#)

 [Write a comment](#)  
[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)  
© 2020 by Eaton Industries GmbH