



**229304**  
**CI-K2H-100-TS**

[Overview](#)[Specifications](#)[Resources](#)[Delivery program](#)[Technical data](#)[Design verification as per  
IEC/EN 61439](#)[Technical data ETIM 7.0](#)[Dimensions](#)

## DELIVERY PROGRAM

Product range  
CI-K small enclosures

Basic function  
Basic enclosures

Product function  
CI-K empty enclosures

Single unit/Complete unit  
Single unit

Degree of Protection  
Front IP65  
IP65, with push-through cable entry

Degree of Protection  
Front IP65  
IP65, with push-through cable entry

Material  
Glass-fibre reinforced polycarbonate

Colour  
Enclosure base RAL 9005, black  
Operator only RAL 7035, light gray

Description  
Metric cable entry knockouts top, bottom and in the back plate  
Control cable entry  
Lamp indicator L-... can be mounted in base knock-out  
M20/M25


Cable entry  
hard knockout version

Dimensions

Width  
100 mm

Height  
160 mm

Depth  
100 mm



Enclosure depth

Legend for the graphic  
Dimensions from top:  
Mounting depth with mounting plate  
Mounting depth for mounting rail 7.5 mm height  
Mounting depth for mounting rail 15 mm height

Enclosure depth

Mounting depth for mounting rail 7.5 mm height  
73 mm

Features  
With mounting rail to IEC/EN 60715

Notes

M	q
<input type="checkbox"/>	
Knockouts	Knockouts
2 X M25 or push-through membrane up to max. <input type="checkbox"/> 16 mm	2 x M25 or push-through membrane up to a max. diameter of 16 mm and 1 push-through membrane up to a max. diameter of 8 mm
T	
<input type="checkbox"/>	
Back plate:	
2 x push-through membrane up to max. <input type="checkbox"/> 11mm (not for CI-K2H)	

TECHNICAL DATA

## General

Standards  
IEC/EN 60529  
DIN EN 62208

Climatic proofing  
Damp heat, constant, to IEC 60068-2-78  
Damp heat, cyclic, to IEC 60068-2-30

Ambient temperature  
-25 - +70  
-25 - +40 (with push-through cable entry) °C

Degree of Protection  
Front IP65  
IP65, with push-through cable entry

Power loss  
Max. radiated heat dissipation with separate mounting,  
ambient air temperature +20 °C  
12.5 W

## Material characteristics

Material  
Base  
Glass-fibre reinforced polycarbonate

Material  
Cover  
Glass-fibre reinforced polycarbonate

Surface treatment  
Resistant to corrosion

Colour  
Base  
RAL 9005, black (matt)

Colour  
Housing body  
Enclosure cover RAL 7035, light grey (matt)

## Material properties

Electrical  
Track resistance  
CTI 175 (base, to IEC 60112)  
CTI 175 (cover, to IEC 60112)

Electrical  
Surface resistance to IEC 60093  
 $1 \Omega \times 10^{13}$

Electrical  
Dielectric strength to IEC 60243-1  
30 kV/mm

Thermal  
Temperature resistant  
-40 °C - 120 °C (enclosure)  
-40 °C - +80 °C (gasket)

Mechanical  
Impact resistance  
IK06 according to EN 50102

Mechanical  
max. assembly weights  
Mounting plate  
0.7 kg

Mechanical  
max. assembly weights  
Mounting rail  
0.7 kg

Chemical resistance  
Chemical resistant  
Base, Cover  
Resistant against: Acids < 10 %, mineral oil, alcohol,  
gasoline, greases, salt solutions  
Partly resistant to: Acids > 10 %, alcohol  
Not resistant to: alkalis, benzene  
Push-through membrane (Q-K1/Q-K2) and sealing material  
Resistant against: Acids < 10 %, alkalis, benzene, salt  
solutions  
Partly resistant to: Acids > 10 %, greases, benzene  
Not resistant to: Mineral oil, benzene

Atmospheric  
Saline spray  
IEC 60068-2-11

Atmospheric  
UV resistance  
Beneath protective shield

Atmospheric  
Water consumption to DIN EN ISO 62  
0.29 %

Flammability characteristics  
Glow wire test  
Flammability characteristics  
960 °C/1mm thickness (base, cover; glow wire to VDE 0471  
Part 2)  
650 °C/1mm thick (push-through membrane and seal  
material) to VDE 0471 Part 2)

Flammability characteristics  
Glow wire test  
to UL 94  
V0/1.5 mm thickness

Flammability characteristics  
Glow wire test  
to UL 94  
HB

Flammability characteristics  
Halogen free  
Yes

## DESIGN VERIFICATION AS PER IEC/EN 61439

### Technical data for design verification

Rated operational current for specified heat dissipation [ $I_r$ ]  
0 A

Heat dissipation per pole, current-dependent [ $P_{rd}$ ]  
0 W

Equipment heat dissipation, current-dependent [ $P_{rd}$ ]  
0 W

Static heat dissipation, non-current-dependent [ $P_{vs}$ ]  
0 W

Heat dissipation capacity [ $P_{diss}$ ]  
12.5 W

Operating ambient temperature min.  
-25 °C

Operating ambient temperature max.  
+70 °C

Degree of Protection  
Front IP65  
IP65, with push-through cable entry

Max. radiated heat dissipation with separate mounting,  
ambient air temperature +20 °C  
12.5 W

Flammability characteristics  
960 °C/1mm thickness (base, cover; glow wire to VDE 0471  
Part 2)  
650 °C/1mm thick (push-through membrane and seal  
material) to VDE 0471 Part 2)

Track resistance  
CTI 175 (base, to IEC 60112)  
CTI 175 (cover, to IEC 60112)

Surface treatment  
Resistant to corrosion

Impact resistance  
IK06 according to EN 50102

Temperature resistant  
-40 °C - 120 °C (enclosure)  
-40 °C - +80 °C (gasket)

UV resistance  
Beneath protective shield

## IEC/EN 61439 design verification

10.2 Strength of materials and parts  
10.2.2 Corrosion resistance  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.1 Verification of thermal stability of enclosures  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.2 Verification of resistance of insulating materials to normal heat  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.4 Resistance to ultra-violet (UV) radiation  
Please enquire

10.2 Strength of materials and parts  
10.2.5 Lifting  
Not applicable.

10.2 Strength of materials and parts  
10.2.6 Mechanical impact  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.7 Inscriptions  
Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES  
Meets the product standard's requirements.

10.4 Clearances and creepage distances  
Meets the product standard's requirements.

10.5 Protection against electric shock  
Is the panel builder's responsibility.

10.6 Incorporation of switching devices and components  
Is the panel builder's responsibility.

10.7 Internal electrical circuits and connections  
Is the panel builder's responsibility.

10.8 Connections for external conductors  
Is the panel builder's responsibility.

10.9 Insulation properties  
10.9.2 Power-frequency electric strength  
Is the panel builder's responsibility.

10.9 Insulation properties  
10.9.3 Impulse withstand voltage  
Is the panel builder's responsibility.

10.9 Insulation properties  
10.9.4 Testing of enclosures made of insulating material  
Meets the product standard's requirements.

10.10 Temperature rise  
The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating  
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility  
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function  
The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## TECHNICAL DATA ETIM 7.0

Low-voltage industrial components (EG000017) / Empty enclosure for switchgear (EG000712)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Empty housing for switch devices (ecl@ss10.0.1-27-37-13-01 [AKN343014])

Material housing  
Plastic

Width  
100 mm

Height  
160 mm

Depth  
100 mm

With transparent cover  
No

Suitable for emergency stop  
Yes

Model  
Surface mounting

Degree of protection (IP)  
IP65

Degree of protection (NEMA)  
Other

DIMENSIONS

