

Select your language

- German
- English
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



Powering Business Worldwide

CSDS4A4CY2202 - Connection cable, 4p, DC current, coupling M12 flat, open end, L=2m



136292 CSDS4A4CY2202

[Overview](#) [Specifications](#) [Resources](#)



- [Delivery program](#)
- [Design verification as per IEC/EN 61439](#)
- [Technical data ETIM 7.0](#)
- [Approvals](#)

136292 CSDS4A4CY2202

Connection cable, 4p, DC current, coupling M12 flat, open end, L=2m

Alternate Catalog No.

CSDS4A4CY2202

EL-Nummer (Norway)

0004315399

Connecting cable, Basic function: Accessories, Range: connecting cables, Length: 2000 mm, Voltage type: DC, 4 pole, Style output side: Cable end, open, Style input side: Coupling, straight, For use with: DC sensors, 4 pole, 2, 3 or 4-wire connection, M12, RS2...-02..., RS2...-11..., RS4-02...

Delivery program

Basic function

Accessories

Accessories

Connecting cables

Basic function

Accessories

Range

connecting cables

Length

2000 mm

Pin assignment



Voltage type

DC

Number of poles

4 pole

Style output side

Cable end, open

Style input side

Coupling, straight

For use with

For use with

DC sensors, 4 pole, 2, 3 or 4-wire connection, M12

RS2...-02...

RS2...-11...

RS4-02...

Design verification as per IEC/EN 61439

Operating ambient temperature min.

-25 °C

Operating ambient temperature max.

+70 °C

Technical data ETIM 7.0

Sensors (EG000026) / Sensor-actuator patch cord (EC001855)

Electric engineering, automation, process control engineering / Cable, wire / Ready-made data cable / Assembled sensor actuator-line

(ecl@ss10.0.1-27-06-03-11 [AFR601003])

Number of poles

4

Type of electrical connection, field-sided

M12

Type of plug-in contact, field sided

Female (bus)

Positioning cable feed, field-sided

Straight

Type of electrical connection, box-sided

Other

Type of plug-in contact, box-sided
Positioning cable feed, box-sided
Other
Cable length
2 m
Material of cable sheath
Other
Halogen free
No
Colour cable sheath
Other
With LED indication
No
Screened
No
Type of cable
Multi-core
Vulcanize
No
Material contact body
Other
Material of contact surface
Other
Permitted cable outer temperature after assembling without vibration
40 - 70 °C
Permitted cable outer temperature during assembling/handling
40 - 70 °C
Rated current In
0 A
Rated voltage
0 V
Continuity resistor
0 mOhm
Degree of protection (IP)
Other

Approvals

Product Standards
CE marking

Wiring diagram

- 

1 = Brown
2 = White
3 = Blue
4 = Black

[Pin assignment](#)
[Wiring diagram](#)
[Line drawing](#)

Product photo

- 

[Photo](#)
[Product photo](#)
[Photo](#)

3D drawing

- 

[1360DRW-67](#)
[3D drawing](#)
[Line drawing](#)

Dimensions single product

- 

[1360DIM-282](#)
[Dimensions single product](#)
[Line drawing](#)

Download-Center

- [Download-Center \(this item\)](#)
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)
Eaton EMEA Download-Center

 [Generate data sheet in PDF format](#)

 [Generate data sheet in Excel format](#)



[Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2020 by Eaton Industries GmbH

