

Select your language

- German
- English
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



CSDR4A4CY2205-D - Connection cable, 4p, DC current, coupling M12 flat, plug, angled, L=5m



136283 CSDR4A4CY2205-D

[Overview](#) [Specifications](#) [Resources](#)



• [Delivery program](#)

• [Design verification as per IEC/EN 61439](#)

• [Technical data ETIM 7.0](#)

• [Approvals](#)

## 136283 CSDR4A4CY2205-D

Connection cable, 4p, DC current, coupling M12 flat, plug, angled, L=5m

Alternate Catalog No.

CSDR4A4CY2205-D

EL-Nummer (Norway)

0004315397

Connecting cable, Basic function: Accessories, Length: 5000 mm, Voltage type: DC, 4 pole, Style output side: Plug, angled, Style input side: Coupling, straight, For use with: DC sensors, 4 pole, 2, 3 or 4-wire connection, M12

### Delivery program

Basic function

Accessories


Accessories

Connecting cables

Length

5000 mm

Pin assignment



Voltage type

DC

Number of poles

4 pole

Style output side

Plug, angled

Style input side

Coupling, straight

For use with

For use with

DC sensors, 4 pole, 2, 3 or 4-wire connection, M12

### Design verification as per IEC/EN 61439

Operating ambient temperature min.

-25 °C

Operating ambient temperature max.

+70 °C

### Technical data ETIM 7.0

Sensors (EG000026) / Sensor-actuator patch cord (EC001855)

Electric engineering, automation, process control engineering / Cable, wire / Ready-made data cable / Assembled sensor actuator-line (ecl@ss10.0.1-27-06-03-11 [AFR601003])

Number of poles

4

Type of electrical connection, field-sided

M12

Type of plug-in contact, field sided

Female (bus)

Positioning cable feed, field-sided

Straight

Type of electrical connection, box-sided

M12

Type of plug-in contact, box-sided

Male (plug)

Positioning cable feed, box-sided


Angled

Cable length  
 5 m  
 Material of cable sheath  
 Other  
 Halogen free  
 No  
 Colour cable sheath  
 Other  
 With LED indication  
 No  
 Screened  
 No  
 Type of cable  
 Multi-core  
 Vulcanize  
 No  
 Material contact body  
 Other  
 Material of contact surface  
 Other  
 Permitted cable outer temperature after assembling without vibration  
 40 - 70 °C  
 Permitted cable outer temperature during assembling/handling  
 40 - 70 °C  
 Rated current In  
 0 A  
 Rated voltage  
 0 V  
 Continuity resistor  
 0 mOhm  
 Degree of protection (IP)  
 Other


## Approvals

Product Standards  
 CE marking

## Wiring diagram



## Product photo



## 3D drawing



## Download-Center

- [Download-Center \(this item\)](#)  
 Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)  
 Eaton EMEA Download-Center

[Generate data sheet in PDF format](#)

[Generate data sheet in Excel format](#)

[Write a comment](#)  
[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2020 by Eaton Industries GmbH