



Connection cable, 4p, DC current, coupling m12 angled, open end, L=2m



Powering Business Worldwide™

Part no. CSDR4A4CY2202
Catalog No. 136279
Alternate Catalog No. CSDR4A4CY2202
EL-Nummer (Norway) 0004315395

Delivery program

Basic function		Accessories
Accessories		Connecting cables
Basic function		Accessories
Range		connecting cables
Length	mm	2000
Pin assignment		 1 = Brown 2 = White 3 = Blue 4 = Black
Voltage type		DC
Number of poles		4 pole
Style output side		Cable end, open
Style input side		Coupling, angled
For use with		
For use with		DC sensors, 4 pole, 2, 3 or 4-wire connection, M12 RS2...-02... RS2...-11... RS4-02...

Design verification as per IEC/EN 61439

Technical data for design verification		
Operating ambient temperature min.	°C	-25
Operating ambient temperature max.	°C	70

Technical data ETIM 7.0

Sensors (EG000026) / Sensor-actuator patch cord (EC001855)		
Electric engineering, automation, process control engineering / Cable, wire / Ready-made data cable / Assembled sensor actuator-line (ecl@ss10.0.1-27-06-03-11 [AFR601003])		
Number of poles		4
Type of electrical connection, field-sided		M12
Type of plug-in contact, field sided		Female (bus)
Positioning cable feed, field-sided		Angled
Type of electrical connection, box-sided		Other
Type of plug-in contact, box-sided		Other
Positioning cable feed, box-sided	m	2
Cable length		Other
Material of cable sheath		No
Halogen free		Other
Colour cable sheath		No
With LED indication		No
Screened		No
Type of cable		Multi-core
Vulcanize		No
Material contact body		Other
Material of contact surface		Other
Permitted cable outer temperature after assembling without vibration	°C	40 - 70
Permitted cable outer temperature during assembling/handling	°C	40 - 70
Rated current In	A	0

Rated voltage	V	0
Continuity resistor	mOhm	0
Degree of protection (IP)		Other

Approvals

Product Standards	CE marking
-------------------	------------