



Connection cable, 4p, DC current, coupling M12 flat, plug, angled, L=3m



Powering Business Worldwide™

Part no.	CSDR4A4CY2203-D
Catalog No.	136315
Alternate Catalog No.	CSDR4A4CY2203-D
EL-Nummer (Norway)	0004315405

Delivery program

Basic function		Accessories	
Accessories		Connecting cables	
Length	mm	3000	
Pin assignment		Face view female	Face view male
		(1) (2)	(2) (1)
		(4) (3)	(3) (4)
Voltage type		DC	
Number of poles		4 pole	
Style output side		Plug, angled	
Style input side		Coupling, straight	
For use with		DC sensors, 4 pole, 2, 3 or 4-wire connection, M12	
For use with			

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.	°C	-25	
Operating ambient temperature max.	°C	70	

Technical data ETIM 7.0

Sensors (EG000026) / Sensor-actuator patch cord (EC001855)			
Electric engineering, automation, process control engineering / Cable, wire / Ready-made data cable / Assembled sensor actuator-line (ecl@ss10.0.1-27-06-03-11 [AFR601003])			
Number of poles		4	
Type of electrical connection, field-sided		M12	
Type of plug-in contact, field sided		Female (bus)	
Positioning cable feed, field-sided		Straight	
Type of electrical connection, box-sided		M12	
Type of plug-in contact, box-sided		Male (plug)	
Positioning cable feed, box-sided		Angled	
Cable length	m	3	
Material of cable sheath		Other	
Halogen free		No	
Colour cable sheath		Other	
With LED indication		No	
Screened		No	
Type of cable		Multi-core	
Vulcanize		No	
Material contact body		Other	
Material of contact surface		Other	
Permitted cable outer temperature after assembling without vibration	°C	40 - 70	
Permitted cable outer temperature during assembling/handling	°C	40 - 70	
Rated current In	A	0	
Rated voltage	V	0	
Continuity resistor	mOhm	0	
Degree of protection (IP)		Other	

Approvals

Product Standards

CE marking