

LV HRC fuse element, NH000, In: 125 A, gG, Un AC: 400 V, Un DC: 250 V, Front indicator, live grip lugs



Model	
product brand name	SETRON
Product designation	LV HRC fuse link
Design of the product	With blade contacts
Design of an identification indicator	Front indicators
design of the switching contact	Non-corroding, silver-plated
Design of the fuse link	LV HRC fuse link
General technical data	
Size of fuse system / acc. to DIN EN 60269-1	NH000
Operating class of the fuse link	gG
circuit-breaker / Design	3NA3
type of voltage	AC/DC
Operating current / at AC / rated value	125 A
Supply voltage	
• at AC / rated value	400 V
• at DC	250 V
Protection class	
Protection class IP	IP20, with connected conductors

## Switching capacity

### Switching capacity current

- |   |        |
|---|--------|
| • at DC / acc. to IEC 60947-2 / rated value | 25 kA  |
| • acc. to IEC 60947-2 / rated value         | 120 kA |

## Dissipation

Power loss [W]	6.84 W
Power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	6.84 W

## Current

Tripping residual / rated value / derated current / at 40 Cel	118.75 A
Diken-export / Let-through energy	DE_3NA_00_500_gG_125

## Mechanical Design

• Width / of the enclosure	21 mm
mounting position	Any, preferably vertical
net weight	127 g

## Environmental conditions

Ambient temperature	
• minimum	-5 °C
• maximum	40 °C
Ambient temperature / during storage	Air humidity 90% at 20 °C
Environmental category	-20 to +50 at 95% relative humidity

## Certificates

- |   |   |
|---|---|
| • reference code / acc. to DIN EN 61346-2 | F |
| • Reference code / acc. to DIN EN 81346-2 | F |

**Declaration of Con-  
formity**

**Test Certificates**

**Shipping Approval**

**other**



EG-Konf.

[Special Test Certificate](#)



GL

[Miscellaneous](#)

## Further information

### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NA3832-8>

### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)



<https://support.industry.siemens.com/cs/ww/en/ps/3NA3832-8>

### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3NA3832-8](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NA3832-8)


### CAX-Online-Generator

<http://www.siemens.com/cax>



1

-F1



2

