



118915
DILMP45-01(110V50HZ,120V60HZ)

[Overview](#) [Specifications](#) [Resources](#)



[Delivery program](#)

[Technical data](#)

[Design verification as per
IEC/EN 61439](#)

[Technical data ETIM 7.0](#)

[Approvals](#)

[Characteristics](#)

[Dimensions](#)

DELIVERY PROGRAM

Product range
Contactors

Application
Contactors for 4 pole electric consumers

Subrange
Contactors up to 200 A, 4 pole

Utilization category
AC-1: Non-inductive or slightly inductive loads, resistance
furnaces
NAC-3: Normal AC induction motors: starting, switch off
during running

Connection technique
Screw terminals

Number of poles
4 pole

Rated operational current

AC-1
Conventional free air thermal current, 3 pole, 50 - 60 Hz
at 40 °C [$I_{th} = I_n$]
45 A


AC-1
Conventional free air thermal current, 3 pole, 50 - 60 Hz
at 50 °C [$I_{th} = I_n$]
41 A

AC-1
Conventional free air thermal current, 3 pole, 50 - 60 Hz
at 55 °C [$I_{th} = I_n$]
40 A

AC-1
Conventional free air thermal current, 3 pole, 50 - 60 Hz
at 60 °C [$I_{th} = I_n$]
39 A

Contacts

N/C = Normally closed
1 NC



For use with
DILM32-XH(C)...
DILA-XH(V)(C)...

Actuating voltage
110 V 50 Hz, 120 V 60 Hz

Voltage AC/DC
AC operation

Connection to SmartWire-DT
no

Instructions
Contacts to EN 50 012.
with mirror contact.

TECHNICAL DATA

General

Standards
IEC/EN 60947, VDE 0660, UL, CSA

Lifespan, mechanical
AC operated [Operations]
 10×10^6

Lifespan, mechanical
DC operated [Operations]
 10×10^6

Operating frequency, mechanical
AC operated [Operations/h]
5000


Operating frequency, mechanical
DC operated [Operations/h]
5000

Climatic proofing
Damp heat, constant, to IEC 60068-2-3
Damp heat, cyclic, to IEC 60068-2-30

Ambient temperature
Open
-25 - +60 °C

Ambient temperature
Enclosed
- 25 - 40 °C

Ambient temperature
Storage
- 40 - 80 °C



Mechanical shock resistance (IEC/EN 60068-2-27)
Half-sinusoidal shock, 10 ms
Main contacts
N/O contact
10 g

Mechanical shock resistance (IEC/EN 60068-2-27)
Half-sinusoidal shock, 10 ms
Auxiliary contacts
N/O contact
7 g

Mechanical shock resistance (IEC/EN 60068-2-27)
Half-sinusoidal shock, 10 ms
Auxiliary contacts
N/C contact
5 g

Degree of Protection
IP00

Altitude
Max. 2000 m

Protection against direct contact when actuated from front
(EN 50274)
Finger and back-of-hand proof

Stripping length
10 mm

Terminal capacity main cable

Solid
1 x (0.75 - 16)
2 x (0.75 - 10) mm²

Terminal capacity main cable
Flexible with ferrule
1 x (0.75 - 16)
2 x (0.75 - 10) mm²

Terminal capacity main cable
Stranded
1 x 16 mm²

Terminal capacity main cable
Solid or stranded
18 - 6 AWG

Terminal capacity main cable
Terminal screw
M5

Terminal capacity main cable
Tightening torque
3 Nm

Terminal capacity main cable
Stripping length
10 mm

Terminal capacity control circuit cables
Solid
1 x (0.75 - 4)
2 x (0.75 - 2.5) mm²

Terminal capacity control circuit cables
Flexible with ferrule
1 x (0.75 - 2.5)
2 x (0.75 - 2.5) mm²

Terminal capacity control circuit cables
Solid or stranded
18 - 14 AWG

Terminal capacity control circuit cables
Stripping length
10 mm

Terminal capacity control circuit cables
Terminal screw
M3.5

Terminal capacity control circuit cables
Tightening torque
1.2 Nm

Tool
Main cable
Pozidriv screw driver
2 Size

Tool
Main cable
Standard screw driver
0.8 x 5.5
1 x 6 mm

Tool
Control circuit cables
Pozidriv screw driver
2 Size

Tool
Control circuit cables
Standard screw driver
0.8 x 5.5
1 x 6 mm

Main conducting paths

Rated impulse withstand voltage [U_{imp}]
8000 V AC

Overvoltage category/pollution degree
III/3

Rated insulation voltage [U_i]
690 V AC

Rated operational voltage [U_o]
690 V AC

Safe isolation to EN 61140
between coil and contacts
440 V AC

Safe isolation to EN 61140
between the contacts
440 V AC

Making capacity ($\cos \phi$) [Up to 690 V]
350
According to IEC/EN 60947 A

Breaking capacity
220 V 230 V
250 A

Breaking capacity
380 V 400 V
250 A

Breaking capacity
500 V
250 A

Breaking capacity
660 V 690 V
144 A

Short-circuit rating
Short-circuit protection maximum fuse
Type "2" coordination
400 V [gG/gL 500 V]
35 A

Short-circuit rating
Short-circuit protection maximum fuse
Type "2" coordination
690 V [gG/gL 690 V]
35 A

Short-circuit rating
Short-circuit protection maximum fuse
Type "1" coordination
400 V [gG/gL 500 V]
100 A

Short-circuit rating
Short-circuit protection maximum fuse
Type "1" coordination
690 V [gG/gL 690 V]
50 A

AC

AC-1
Rated operational current
Conventional free air thermal current, 3 pole, 50 - 60 Hz
Open
at 40 °C [$I_{th} = I_e$]
45 A

AC-1
Rated operational current
Conventional free air thermal current, 3 pole, 50 - 60 Hz
Open
at 50 °C [$I_{th} = I_e$]
41 A

AC-1
Rated operational current
Conventional free air thermal current, 3 pole, 50 - 60 Hz
Open
at 55 °C [$I_{th} = I_e$]
40 A

AC-1
Rated operational current
Conventional free air thermal current, 3 pole, 50 - 60 Hz
Open
at 60 °C [$I_{th} = I_e$]
39 A

AC-1
Rated operational current
Conventional free air thermal current, 3 pole, 50 - 60 Hz
enclosed [I_{th}]
36 A

AC-1
Rated operational current
Conventional free air thermal current, 1 pole
open [I_{th}]
117 A

AC-1
Rated operational current
Conventional free air thermal current, 1 pole
enclosed [I_{th}]
105 A

AC-1
Motor rating [P]
220/230 V [P]
16 kW

AC-1
Motor rating [P]
240 V [P]
18 kW

AC-1
Motor rating [P]
380/400 V [P]
28 kW

AC-1
Motor rating [P]
415 V [P]
31 kW

AC-1
Motor rating [P]
440 V [P]
33 kW

AC-1
Motor rating [P]
500 V [P]
37 kW

AC-1
Motor rating [P]
690 V [P]
49 kW

AC-3
Rated operational current
Open, 3-pole: 50 – 60 Hz
Notes
At maximum permissible ambient temperature (open.)

AC-3
Rated operational current
Open, 3-pole: 50 – 60 Hz
220 V 230 V [I_e]
25 A

AC-3
Rated operational current
Open, 3-pole: 50 – 60 Hz
240 V [I_e]
25 A

AC-3
Rated operational current
Open, 3-pole: 50 – 60 Hz
380 V 400 V [I_e]

25 A

AC-3
Rated operational current
Open, 3-pole: 50 – 60 Hz
415 V [I_e]
25 A

AC-3
Rated operational current
Open, 3-pole: 50 – 60 Hz
440V [I_e]
25 A

AC-3
Rated operational current
Open, 3-pole: 50 – 60 Hz
500 V [I_e]
25 A

AC-3
Rated operational current
Open, 3-pole: 50 – 60 Hz
660 V 690 V [I_e]
15 A

AC-3
Motor rating [P]
220 V 230 V [P]
7.5 kW

AC-3
Motor rating [P]
240V [P]
8.5 kW

AC-3
Motor rating [P]
380 V 400 V [P]
11 kW

AC-3
Motor rating [P]
415 V [P]
14.5 kW

AC-3
Motor rating [P]
440 V [P]
15.5 kW

AC-3
Motor rating [P]
500 V [P]
17.5 kW

AC-3
Motor rating [P]
660 V 690 V [P]
14 kW

DC

Rated operational current, open
DC-1
60 V [I_e]
45 A

Rated operational current, open
DC-1
110 V [I_e]
45 A

Rated operational current, open
DC-1
220 V [I_e]
45 A

Current heat loss

3 pole, at I_n (60°)
13.2 W

Impedance per pole
2.7 mΩ

Magnet systems

Voltage tolerance
AC operated 50 Hz [Pick-up]
0.8 - 1.1 x U_e

Voltage tolerance
AC operated 50/60 Hz
0.85 - 1.1 x U_e

Voltage tolerance
Drop-out voltage AC operated [Drop-out]
0.4 - 0.6 x U_e

Power consumption of the coil in a cold state and 1.0 x U_s
AC operated 50/60 Hz [Pick-up]
50 VA

Power consumption of the coil in a cold state and 1.0 x U_s
AC operated 50/60 Hz [Pick-up]
40 W

Power consumption of the coil in a cold state and 1.0 x U_s
AC operated 50/60 Hz [Sealing]
8 VA

Power consumption of the coil in a cold state and 1.0 x U_s
AC operated 50/60 Hz [Sealing]
2.1 W

Duty factor
100 % DF

Changeover time at 100 % U_s (recommended value)
Main contacts

AC operated
Closing delay
16 - 22 ms

Changeover time at 100 % U_N (recommended value)
Main contacts
AC operated
Opening delay
8 - 14 ms

Changeover time at 100 % U_N (recommended value)
Permissible residual current with actuation of A1 - A2 by the electronics (with 0 signal).
☐ 1 mA

Rating data for approved types

Switching capacity
Maximum motor rating
Three-phase
200 V
208 V
7.5 HP

Switching capacity
Maximum motor rating
Three-phase
230 V
240 V
10 HP

Switching capacity
Maximum motor rating
Three-phase
460 V
480 V
15 HP

Switching capacity
Maximum motor rating
Three-phase
575 V
600 V
20 HP

Switching capacity
Maximum motor rating
Single-phase
115 V
120 V
2 HP

Switching capacity
Maximum motor rating
Single-phase
230 V
240 V
5 HP

Switching capacity
General use
40 A

Auxiliary contacts
Pilot Duty

AC operated
A600

Auxiliary contacts
Plot Duty
DC operated
F300

Auxiliary contacts
General Use
AC
600 V

Auxiliary contacts
General Use
AC
10 A

Auxiliary contacts
General Use
DC
250 V

Auxiliary contacts
General Use
DC
1 A

Short Circuit Current Rating
Basic Rating
SCCR
5 kA

Short Circuit Current Rating
Basic Rating
max. Fuse
125 A

Short Circuit Current Rating
Basic Rating
max. CB
125 A

Short Circuit Current Rating
480 V High Fault
SCCR (fuse)
10/100 kA

Short Circuit Current Rating
480 V High Fault
max. Fuse
125/70 Class J A

Short Circuit Current Rating
480 V High Fault
SCCR (CB)
10/65 kA

Short Circuit Current Rating
480 V High Fault
max. CB
50/32 A

Short Circuit Current Rating
600 V High Fault
SCCR (fuse)
10/100 kA

Short Circuit Current Rating
600 V High Fault
max. Fuse
125/100 Class J A

Short Circuit Current Rating
600 V High Fault
SCCR (CB)
10/22 kA

Short Circuit Current Rating
600 V High Fault
max. CB
50/32 A

Special Purpose Ratings
Electrical Discharge Lamps (Ballast)
480V 60Hz 3phase, 277V 60Hz 1phase
40 A

Special Purpose Ratings
Electrical Discharge Lamps (Ballast)
600V 60Hz 3phase, 347V 60Hz 1phase
40 A

Special Purpose Ratings
Incandescent Lamps (Tungsten)
480V 60Hz 3phase, 277V 60Hz 1phase
40 A

Special Purpose Ratings
Incandescent Lamps (Tungsten)
600V 60Hz 3phase, 347V 60Hz 1phase
40 A

Special Purpose Ratings
Resistance Air Heating
480V 60Hz 3phase, 277V 60Hz 1phase
40 A

Special Purpose Ratings
Resistance Air Heating
600V 60Hz 3phase, 347V 60Hz 1phase
40 A

Special Purpose Ratings
Refrigeration Control (CSA only)
LRA 480V 60Hz 3phase
240 A

Special Purpose Ratings
Refrigeration Control (CSA only)
FLA 480V 60Hz 3phase
40 A

Special Purpose Ratings
Refrigeration Control (CSA only)
LRA 600V 60Hz 3phase

180 A

Special Purpose Ratings
Refrigeration Control (CSA only)
FLA 600V 60Hz 3phase
30 A

Special Purpose Ratings
Definite Purpose Ratings (100,000 cycles acc. to UL 1995)
LRA 480V 60Hz 3phase
150 A

Special Purpose Ratings
Definite Purpose Ratings (100,000 cycles acc. to UL 1995)
FLA 480V 60Hz 3phase
25 A

Special Purpose Ratings
Elevator Control
200V 60Hz 3phase
3 HP

Special Purpose Ratings
Elevator Control
200V 60Hz 3phase
11 A

Special Purpose Ratings
Elevator Control
240V 60Hz 3phase
5 HP

Special Purpose Ratings
Elevator Control
240V 60Hz 3phase
15.2 A

Special Purpose Ratings
Elevator Control
480V 60Hz 3phase
10 HP

Special Purpose Ratings
Elevator Control
480V 60Hz 3phase
14 A

Special Purpose Ratings
Elevator Control
600V 60Hz 3phase
15 HP

Special Purpose Ratings
Elevator Control
600V 60Hz 3phase
17 A

DESIGN VERIFICATION AS PER IEC/EN 61439

Technical data for design verification

Rated operational current for specified heat dissipation [I_n]
45 A

Heat dissipation per pole, current-dependent [P_{vd}]
4.4 W

Equipment heat dissipation, current-dependent [P_{vd}]
13.2 W

Static heat dissipation, non-current-dependent [P_{vs}]
2.1 W

Heat dissipation capacity [P_{diss}]
0 W

Operating ambient temperature min.
-25 °C

Operating ambient temperature max.
+60 °C

IEC/EN 61439 design verification

10.2 Strength of materials and parts
10.2.2 Corrosion resistance
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.1 Verification of thermal stability of enclosures
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.2 Verification of resistance of insulating materials to normal heat
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.4 Resistance to ultra-violet (UV) radiation
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.5 Lifting
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts
10.2.6 Mechanical impact
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts
10.2.7 Inscriptions
Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES
Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances
Meets the product standard's requirements.

10.5 Protection against electric shock
Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components
Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections
Is the panel builder's responsibility.

10.8 Connections for external conductors
Is the panel builder's responsibility.

10.9 Insulation properties
10.9.2 Power-frequency electric strength
Is the panel builder's responsibility.

10.9 Insulation properties
10.9.3 Impulse withstand voltage
Is the panel builder's responsibility.

10.9 Insulation properties
10.9.4 Testing of enclosures made of insulating material
Is the panel builder's responsibility.

10.10 Temperature rise
The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function
The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

TECHNICAL DATA ETIM 7.0

Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Power contactor, AC switching (ecl@ss10.0.1-27-37-10-03 [AAB718015])

Rated control supply voltage U_s at AC 50HZ
110 - 110 V

Rated control supply voltage U_s at AC 60HZ
120 - 120 V

Rated control supply voltage U_s at DC
0 - 0 V

Voltage type for actuating
AC

Rated operation current I_e at AC-1, 400 V
45 A

Rated operation current I_e at AC-3, 400 V
25 A

Rated operation power at AC-3, 400 V
11 kW

Rated operation current I_e at AC-4, 400 V
15 A

Rated operation power at AC-4, 400 V
7 kW

Rated operation power NEMA
11 kW

Modular version
No

Number of auxiliary contacts as normally open contact
0

Number of auxiliary contacts as normally closed contact
1

Type of electrical connection of main circuit
Screw connection

Number of normally closed contacts as main contact
0

Number of main contacts as normally open contact
4

APPROVALS

Product Standards
IEC/EN 60947-4-1; UL 60947-4-1; CSA - C22.2 No. 60947-4-1-14; CE marking

UL File No.
E29096

UL Category Control No.
NLDX


CSA File No.
012528

CSA Class No.
2411-03, 3211-04

North America Certification
UL listed, CSA certified

Specially designed for North America
No

CHARACTERISTICS



Accessories
1: Auxiliary contact module
2: Suppressor

Characteristic curve

Switching conditions for 4 pole, non-motor loads
Operating characteristics
Non inductive and slightly inductive loads
Electrical characteristics
Switch on: 1 x rated operational current
Switch off: 1 x rated operational current
Utilization category
100 % AC-1
Typical examples of application
Electric heat

DIMENSIONS



Contactors with auxiliary contact module



distance at side to earthed parts: 6 mm

DILMP32
DILMP45

