

SCALANCE XB124 unmanaged IE switch, 24x 10/100 Mbit/s RJ45 ports; for setting up small star and line topologies; LED diagnostics, IP20, Redundant power supply, 24 V AC/DC Manual available as a download



| | |
|---|-----------------------|
| product type designation | SCALANCE XB124 |
| transfer rate | |
| transfer rate | 10 Mbit/s, 100 Mbit/s |
| interfaces / for communication / integrated | |
| number of electrical connections | |
| • for network components or terminal equipment | 24; RJ45 |
| interfaces / other | |
| number of electrical connections | |
| • for power supply | 1 |
| supply voltage, current consumption, power loss | |
| product component / connection for redundant voltage supply | Yes |
| type of voltage / 1 / of the supply voltage | DC |
| • supply voltage / 1 / rated value | 24 V |
| • power loss [W] / 1 / rated value | 7.2 W |
| • supply voltage / 1 / rated value | 19.2 ... 28.8 V |
| • consumed current / 1 / maximum | 0.3 A |

| | |
|---|--|
| <ul style="list-style-type: none"> product component / 1 / fusing at power supply input | Yes |
| type of voltage / 2 / of the supply voltage | |
| <ul style="list-style-type: none"> supply voltage / 2 / rated value | 19.2 ... 28.8 V |
| ambient conditions | |
| ambient temperature | |
| <ul style="list-style-type: none"> during operation | 0 ... 60 °C |
| <ul style="list-style-type: none"> during storage | -40 ... +80 °C |
| <ul style="list-style-type: none"> during transport | -40 ... +80 °C |
| relative humidity | |
| <ul style="list-style-type: none"> at 25 °C / without condensation / during operation / maximum | 95 % |
| protection class IP | IP20 |
| design, dimensions and weights | |
| design | compact |
| width | 120 mm |
| height | 117 mm |
| depth | 109 mm |
| net weight | 0.535 kg |
| fastening method | |
| <ul style="list-style-type: none"> 35 mm top hat DIN rail mounting | Yes |
| <ul style="list-style-type: none"> wall mounting | No |
| <ul style="list-style-type: none"> S7-300 rail mounting | No |
| <ul style="list-style-type: none"> S7-1500 rail mounting | No |
| product functions / management, configuration, engineering | |
| product function | |
| <ul style="list-style-type: none"> multiport mirroring | No |
| <ul style="list-style-type: none"> CoS | Yes |
| PROFINET conformity class | A |
| product function / switch-managed | No |
| product functions / redundancy | |
| product function | |
| <ul style="list-style-type: none"> Parallel Redundancy Protocol (PRP)/operation in the PRP-network | Yes |
| <ul style="list-style-type: none"> Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA) | No |
| standards, specifications, approvals | |
| standard | |
| <ul style="list-style-type: none"> for FM | FM3611: Class 1, Divison 2, Group A, B, C, D / T4, CL.1, Zone 2, GP. IIC, T4 |

| | |
|---|--|
| <ul style="list-style-type: none"> • for hazardous zone | EN 60079-0:2009, EN60079-15:2010, II 3 G Ex nA IIC T4 Gc, KEMA 07ATEX0145 X |
| <ul style="list-style-type: none"> • for safety / from CSA and UL | UL 60950-1, CSA C22.2 No. 60950-1 |
| <ul style="list-style-type: none"> • for emitted interference | EN 61000-6-4 (Class B) |
| <ul style="list-style-type: none"> • for interference immunity | 61000-6-2 |
| MTBF | 57 y |
| standards, specifications, approvals / CE | |
| certificate of suitability / CE marking | Yes |
| standards, specifications, approvals / hazardous environments | |
| certificate of suitability | |
| <ul style="list-style-type: none"> • IECEx | Yes; IEC 60079-0, IEC 60079-15, IECEx DEK 14.0025X, Ex nA IIC T4 Gc |
| standards, specifications, approvals / other | |
| certificate of suitability | EN 61000-6-2, EN 61000-6-4 |
| <ul style="list-style-type: none"> • Regulatory Compliance Mark (RCM) | Yes |
| <ul style="list-style-type: none"> • KC approval | Yes |
| further information / internet-Links | |
| Internet-Link | |
| <ul style="list-style-type: none"> • to website: Selector TIA Selection Tool | http://www.siemens.com/snst |
| <ul style="list-style-type: none"> • to website: Industrial communication | http://www.siemens.com/simatic-net |
| <ul style="list-style-type: none"> • to website: Industry Mall | https://mall.industry.siemens.com |
| <ul style="list-style-type: none"> • to website: Information and Download Center | http://www.siemens.com/industry/infocenter |
| <ul style="list-style-type: none"> • to website: Image database | http://automation.siemens.com/bilddb |
| <ul style="list-style-type: none"> • to website: CAx-Download-Manager | http://www.siemens.com/cax |
| <ul style="list-style-type: none"> • to website: Industry Online Support | https://support.industry.siemens.com |
| security information | |
| security information | <p>Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)</p> |

last modified:

11/26/2020