

ARGENTA SERIES

IP66 STEEL WALL-MOUNTING CABINETS

Description: IP66 ROLLED STEEL WALL-MOUNTING CABINET 500x500x250 OPAQUE DOOR

Reference:

GN505025

Characteristics:

Product type:	Wall-mounting cabinet
Dimensions cabinet:	(AxBxC) 500x500x250 mm
Installation:	Surface
Type of door:	Single opaque door
Locking:	5-mm double-bit lock - Two 1-point lock
Finish:	Coated with primer, and hardened polyester paint, embossed, with UV protection
Colour:	Grey RAL 7035
Mounting plate:	With flat mounting plate. 2-mm galvanised sheet steel
Weight (Kg):	15,1
Materials:	Cold-rolled steel EN 10130+A1 Sheet thickness. Body: 1,2 mm. Door: 1,2 mm. Cable entry lid: 2 mm. Injected polyurethane sealing gasket
Capacity:	
Maximum acceptable loads:	Total load: 225 Kg. Door: 25 Kg. Plate: 200 Kg.

Technical data:

Degree of protection:	IP66 / NEMA 1, 12, 4
Resistance to impact:	IK10
Ambient temperature range:	-25 °C / +40 °C
Maximum operating voltage:	1000 V AC / 1500 V DC

Certificates and standards:

Directive:	2014/35/EU
Standards:	UNE-EN 62208 and UNE-EN 61439-1-3 (as applicable)
Certificates:	UL508A / Bureau Veritas



Codes:


EAN:	8431044490564
Customs tariff number:	85.38.10.00
ETIM 6.0:	EC000261

ARGENTA SERIES

IP66 STEEL WALL-MOUNTING CABINETS

Description: IP66 ROLLED STEEL WALL-MOUNTING CABINET 500x500x250 OPAQUE DOOR

Reference: GN505025



Standard drawing

Detailed drawing:  <http://www.ide.es/downloads/planos/pdf/GN505025.pdf>

 <http://www.ide.es/downloads/planos/dxf/GN505025.dxf>

 <http://www.ide.es/downloads/planos/stp/GN505025.stp>



Dimensions cabinet: (AxBxC) 500x500x250 mm

Body to be flush-fitted: -

Inside usable space: (HeightxWidthxDepth) 450x450x229 mm

Cable entry: (DxE) 125x385 mm

Wall fixing: (HeightxWidth) 460x460 mm

Glass dorr with transparent panel: -

Sustainability:

RoHS - REACH

Supply:

Supplied in individual packaging containing cabinet, plate and accessory bag. Mounting plate is supplied unassembled inside the packaging.

Product end of life:

It does not require specific recycling operations.

Recommended applications:

Industrial environments, manufacturing companies requiring a high degree of protection against dust, splashes and impacts.