# **SIEMENS**

#### Data sheet

## 6GK5108-0BA00-2AC2

SCALANCE XC108, Unmanaged IE switch, 8x 10/100 Mbit/s RJ45 ports, LED diagnostics, error-signaling contact with set button, redundant Power supply Manual available as a download



product type designation	SCALANCE XC108
transfer rate	
transfer rate	10 Mbit/s, 100 Mbit/s
interfaces / for communication / integrated	
number of electrical connections	
• for network components or terminal equipment	8; RJ45
interfaces / other	
number of electrical connections	
• for signaling contact	1
• for power supply	1
type of electrical connection	
• for signaling contact	2-pole terminal block
• for power supply	4-pole terminal block
signal inputs/outputs	
operating voltage / of the signaling contacts	
• at DC / rated value	24 V
operational current / of the signaling contacts	

•	at DC	/ maximum		
•	albu	IIIaxiiiiuiii		

supply voltage, current consumption, power loss	
product component / connection for redundant	Yes
voltage supply	
type of voltage / 1 / of the supply voltage	DC
<ul><li>supply voltage / 1 / rated value</li></ul>	24 V
• power loss [W] / 1 / rated value	3 W
<ul><li>consumed current / 1 / at rated supply voltage /</li></ul>	0.25 A
maximum	
<ul><li>supply voltage / 1 / rated value</li></ul>	9.6 31.2 V
• type of electrical connection / 1 / for power	4-pole terminal block
supply	
<ul> <li>product component / 1 / fusing at power supply input</li> </ul>	Yes

0.1 A

ambient conditions		
ambient temperature		
<ul><li>during operation</li></ul>	-40 +70 °C	
during storage	-40 +85 °C	
during transport	-40 +85 °C	
relative humidity		
<ul> <li>at 25 °C / without condensation / during</li> </ul>	95 %	
operation / maximum		
protection class IP	IP20	

design, dimensions and weights		
design	compact	
width	60 mm	
height	147 mm	
depth	125 mm	
net weight	0.85 kg	
material / of the enclosure	Polycarbonate (PC-GF10)	
fastening method		
<ul> <li>35 mm top hat DIN rail mounting</li> </ul>	Yes	
wall mounting	Yes	
• S7-300 rail mounting	Yes	
• S7-1500 rail mounting	Yes	

## product features, product functions, product components / general

number of automatically learnable MAC addresses 2048

oduct functions		

product function

multiport mirroring

No

• CoS

Yes

product function / switch-managed	No
product functions / redundancy	
product function	
<ul> <li>Parallel Redundancy Protocol (PRP)/operation in the PRP-network</li> </ul>	Yes
<ul> <li>Parallel Redundancy Protocol</li> </ul>	No
(PRP)/Redundant Network Access (RNA)	
standards, specifications, approvals	
standard	
for hazardous zone	EN 60079-0:2012 + A11:2013, EN60079-15:2010, II 3 G Ex nA IIC T4 Gc, KEMA 07ATEX0145 X, IEC 6079-0:2011, IEC 6079-0-15:2010
<ul><li>for safety / from CSA and UL</li></ul>	UL 60950-1, CSA C22.2 No. 60950-1
• for hazardous zone / from CSA and UL	UL 1604 and UL 2279-15 (Hazardous Location), Class 1 / Division 2 / Group A, B, C, D / T, Class 1 / Zone 2 / Group IIC / T
• for emitted interference	EN 61000-6-4 (Class B)
standards, specifications, approvals / CE	
certificate of suitability / CE marking	Yes
standards, specifications, approvals / other	
laser protection class	LED Class 1
certificate of suitability	EN 61000-6-2, EN 61000-6-4
• C-Tick	Yes
● E1 approval	Yes
<ul> <li>EC Declaration of Conformity EN 61010, IEC 61010-1, UL 61010A-1</li> </ul>	Yes
KC approval	Yes
standards, specifications, approvals / marine classi	fication
Marine classification association	
<ul> <li>American Bureau of Shipping Europe Ltd.</li> <li>(ABS)</li> </ul>	Yes
<ul> <li>French marine classification society (BV)</li> </ul>	Yes
• DNV GL	Yes
<ul><li>Korean Register of Shipping (KRS)</li></ul>	Yes
<ul><li>Lloyds Register of Shipping (LRS)</li></ul>	Yes
<ul><li>Polski Rejestr Statkow (PRS)</li></ul>	Yes
<ul> <li>Royal Institution of Naval Architects (RINA)</li> </ul>	Yes
further information / internet-Links	
Internet-Link	
• to website: Selector TIA Selection Tool	http://www.siemens.com/snst
<ul><li>to website: Industrial communication</li></ul>	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com

• to website: Information and Download Center

• to website: Image database

• to website: CAx-Download-Manager

• to website: Industry Online Support

http://www.siemens.com/industry/infocenter

http://automation.siemens.com/bilddb

http://www.siemens.com/cax

https://support.industry.siemens.com

#### security information

security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Thirdparty products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)

last modified: 11/26/2020

6GK5108-0BA00-2AC2 Page 4/4