

product description

Preset for PROFINET mode!
SCALANCE XB205-3 managed Layer 2 IE Switch 5x IEC 62443-4-2 certified; 10/100 Mbps RJ45 ports 3x MM FO ST port 1x console port, diagnostics LED redundant power supply; temp. range 0 °C to +60 °C; attachment to DIN rail; default PROFINET



product type designation	SCALANCE XB205-3
transfer rate	
transfer rate	10 Mbit/s, 100 Mbit/s
interfaces / for communication / integrated	
number of electrical connections	
• for network components or terminal equipment	5; RJ45
number of 100 Mbit/s ST(BFOC) ports	
• for multimode	3
interfaces / other	
number of electrical connections	
• for operator console	1
• for management purposes	1
• for power supply	1
type of electrical connection	
• for operator console	RJ11
• for management purposes	RJ45
• for power supply	6-pole terminal block

supply voltage, current consumption, power loss

product component / connection for redundant voltage supply	Yes
type of voltage / 1 / of the supply voltage	DC
• supply voltage / 1 / rated value	24 V
• power loss [W] / 1 / rated value	7.2 W
• supply voltage / 1 / rated value	19.2 ... 28.8 V
• consumed current / 1 / maximum	0.3 A
• type of electrical connection / 1 / for power supply	6-pole terminal block
• product component / 1 / fusing at power supply input	Yes

ambient conditions

ambient temperature	
• during operation	0 ... 60 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
relative humidity	
• at 25 °C / without condensation / during operation / maximum	95 %
protection class IP	IP20

design, dimensions and weights

design	Box
width	80 mm
height	117 mm
depth	109 mm
net weight	0.35 kg
material / of the enclosure	Plastic
fastening method	
• 35 mm top hat DIN rail mounting	Yes
• wall mounting	No
• S7-300 rail mounting	No
• S7-1500 rail mounting	No

product features, product functions, product components / general

cascading in the case of a redundant ring / at reconfiguration time of ≤ 0.3 s	50
cascading in cases of star topology	any (depending only on signal propagation time)

product functions / management, configuration, engineering

product function	
• CLI	Yes
• web-based management	Yes

• MIB support	Yes
• TRAPs via email	Yes
• configuration with STEP 7	Yes
• RMON	Yes
• port mirroring	Yes
• multiport mirroring	No
• CoS	Yes
• with IRT / PROFINET IO switch	No
• PROFINET IO diagnosis	Yes
PROFINET conformity class	B
product function / switch-managed	Yes
telegram length / for Ethernet / maximum	1522 byte
protocol / is supported	
• Telnet	Yes
• HTTP	Yes
• HTTPS	Yes
• TFTP	Yes
• FTP	Yes
• BOOTP	No
• DCP	Yes
• LLDP	Yes
• EtherNet/IP	Yes
• SNMP v1	Yes
• SNMP v2	Yes
• SNMP v3	Yes
• IGMP (snooping/querier)	Yes
identification & maintenance function	
• I&M0 - device-specific information	Yes
• I&M1 – higher level designation/location designation	Yes
product functions / diagnostics	
product function	
• port diagnostics	Yes
• statistics Packet Size	Yes
• statistics packet type	Yes
• error statistics	Yes
• SysLog	Yes
• loopback diagnostics	Yes
product functions / VLAN	
product function	
• VLAN - port based	Yes

- VLAN - protocol-based
- VLAN - IP-based
- VLAN dynamic

No
No
No

product functions / DHCP

product function

- DHCP client

Yes

product functions / redundancy

product function

- ring redundancy
- High Speed Redundancy Protocol (HRP)
- high speed redundancy protocol (HRP) with redundancy manager
- high speed redundancy protocol (HRP) with standby redundancy

Yes
Yes
Yes
Yes

protocol / is supported / Media Redundancy Protocol (MRP)

Yes

product function

- media redundancy protocol (MRP) with redundancy manager
- redundancy procedure STP
- redundancy procedure RSTP
- redundancy procedure RSTP+
- redundancy procedure MSTP
- Parallel Redundancy Protocol (PRP)/operation in the PRP-network
- Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA)
- passive listening

Yes
Yes
Yes
Yes
No
No
No
Yes

product functions / security

product function

- IEEE 802.1x (radius)
- broadcast/multicast/unicast limiter
- broadcast blocking

Yes
Yes
Yes

protocol / is supported

- SSH

Yes

product functions / time

product function

- SICLOCK support

Yes

protocol / is supported

- NTP
- SNTP

Yes
Yes

standards, specifications, approvals

standard	
<ul style="list-style-type: none"> • for FM 	FM3611: Class 1, Division 2, Group A, B, C, D / T4, CL.1, Zone 2, GP. IIC, T4
<ul style="list-style-type: none"> • for hazardous zone 	EN 60079-0 : 2006, EN 60079-15: 2005, II 3 G Ex nA II T4 KEMA 07 ATEX 0145X
<ul style="list-style-type: none"> • for safety / from CSA and UL 	UL 60950-1, CSA C22.2 No. 60950-1
<ul style="list-style-type: none"> • for hazardous zone / from CSA and UL 	ANSI / ISA 12.12.01, CSA C22.2 No. 213-M1987, CL. 1 / Div. 2 / GP. A, B, C, D T4, CL. 1 / Zone 2 / GP. IIC, T6
<ul style="list-style-type: none"> • for emitted interference 	EN 61000-6-4 (Class A)
<ul style="list-style-type: none"> • for interference immunity 	EN 61000-6-2
Security for industrial automation and control systems / acc. to IEC 62443-4-2:2019	Yes

standards, specifications, approvals / CE

certificate of suitability / CE marking	Yes
---	-----

standards, specifications, approvals / other

certificate of suitability	EN 61000-6-2, EN 61000-6-4
<ul style="list-style-type: none"> • C-Tick 	Yes
<ul style="list-style-type: none"> • railway application in accordance with EN 50155 	No
<ul style="list-style-type: none"> • railway application in accordance with EN 50124-1 	No
<ul style="list-style-type: none"> • KC approval 	Yes

further information / internet-Links

Internet-Link	
<ul style="list-style-type: none"> • to website: Selector TIA Selection Tool 	http://www.siemens.com/snst
<ul style="list-style-type: none"> • to website: Industrial communication 	http://www.siemens.com/simatic-net
<ul style="list-style-type: none"> • to website: Industry Mall 	https://mall.industry.siemens.com
<ul style="list-style-type: none"> • to website: Information and Download Center 	http://www.siemens.com/industry/infocenter
<ul style="list-style-type: none"> • to website: Image database 	http://automation.siemens.com/bilddb
<ul style="list-style-type: none"> • to website: CAx-Download-Manager 	http://www.siemens.com/cax
<ul style="list-style-type: none"> • to website: Industry Online Support 	https://support.industry.siemens.com

security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

11/26/2020