

# ARGENTA SERIES

## IP66 STEEL WALL-MOUNTING CABINETS

Description: IP66 ROLLED STEEL WALL-MOUNTING CABINET 800x600x250 OPAQUE DOOR

Reference:

**GN806025**

### Characteristics:

|                           |                                                                                                                                              |
|---------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|
| Product type:             | Wall-mounting cabinet                                                                                                                        |
| Dimensions cabinet:       | (AxBxC) 800x600x250 mm                                                                                                                       |
| Installation:             | Surface                                                                                                                                      |
| Type of door:             | Single opaque door                                                                                                                           |
| Locking:                  | 5-mm double-bit lock - Two 1-point lock                                                                                                      |
| Finish:                   | Coated with primer, and hardened polyester paint, embossed, with UV protection                                                               |
| Colour:                   | Grey RAL 7035                                                                                                                                |
| Mounting plate:           | With flat mounting plate. 2-mm galvanised sheet steel                                                                                        |
| Weight (Kg):              | 29,8                                                                                                                                         |
| Materials:                | Cold-rolled steel EN 10130+A1<br>Sheet thickness. Body: 1,5 mm. Door: 1,5 mm. Cable entry lid: 2 mm.<br>Injected polyurethane sealing gasket |
| Capacity:                 |                                                                                                                                              |
| Maximum acceptable loads: | Total load: 325 Kg. Door: 25 Kg. Plate: 300 Kg.                                                                                              |

### Technical data:

|                            |                       |
|----------------------------|-----------------------|
| Degree of protection:      | IP66 / NEMA 1, 12, 4  |
| Resistance to impact:      | IK10                  |
| Ambient temperature range: | -25 °C / +40 °C       |
| Maximum operating voltage: | 1000 V AC / 1500 V DC |

### Certificates and standards:

|               |                                                   |
|---------------|---------------------------------------------------|
| Directive:    | 2014/35/EU                                        |
| Standards:    | UNE-EN 62208 and UNE-EN 61439-1-3 (as applicable) |
| Certificates: | UL508A / Bureau Veritas                           |



### Codes:

|                        |               |
|------------------------|---------------|
| EAN:                   | 8431044491196 |
| Customs tariff number: | 85.38.10.00   |
| ETIM 6.0:              | EC000261      |

# ARGENTA SERIES

## IP66 STEEL WALL-MOUNTING CABINETS

Description: IP66 ROLLED STEEL WALL-MOUNTING CABINET 800x600x250 OPAQUE DOOR

Reference: GN806025



Standard drawing

Detailed drawing:  <http://www.ide.es/downloads/planos/pdf/GN806025.pdf>

 <http://www.ide.es/downloads/planos/dxf/GN806025.dxf>

 <http://www.ide.es/downloads/planos/stp/GN806025.stp>



|                          |                                     |                                    |                           |
|--------------------------|-------------------------------------|------------------------------------|---------------------------|
| Dimensions cabinet:      | (AxBxC) 800x600x250 mm              | Cable entry:                       | (DxE) 125x485 mm          |
| Body to be flush-fitted: | -                                   | Wall fixing:                       | (HeightxWidth) 760x560 mm |
| Inside usable space:     | (HeightxWidthxDepth) 750x550x229 mm | Glass dorr with transparent panel: | -                         |

### Sustainability:

RoHS - REACH

### Supply:

Supplied in individual packaging containing cabinet, plate and accessory bag. Mounting plate is supplied assembled inside the cabinet.

### Product end of life:

It does not require specific recycling operations.

### Recommended applications:

Industrial environments, manufacturing companies requiring a high degree of protection against dust, splashes and impacts.