

FDV – DOKUMENTASJON		Nr.: 126
		Rev.:
		Dato: 24.5.2017
Produktspesifikasjon	Polyester skap	
Produktnavn	PolySafe 220, 230, 320, 330, 340, 352, 420 430, 440, 442, 452, 530, 542, 546	
Anvisning for drift	Ingen anvisning	
Vedlikehold	Produktet er vedlikeholdsfritt	
Henvisninger Vedlegg	Produktkatalog, dokumentasjon og tekniske data	
Produsent	General Electric	
Importør	EFA Elektro AS, Postboks 593, 1411 Kolbotn, Norway Tlf. 66812400 e-mail: post@efa.no - www.efa.no	

EFA Elektro AS

Produktansvarlig GE

Multipurpose polyester cabinets



Standards

EN/IEC 60529
EN/IEC 62208
EN/IEC 62262

Approvals



- Cabinets with one door:
type 3, 3R, 3S, 4, 4X, 12, 12K and 13
- Cabinets with two doors:
type 3, 3R, 3S, 4, 4X, 12, 12K and 13
- Coupled cabinets:
type 3, 3R, 3S, 12, 12K and 13

Available on request



Lloyd's Register of Shipping

Ambient conditions

Indoor and outdoor stationary use,
at temperatures between -35°C and
70°C in continuous use and at peak
temperatures up to +150°C

Features

- 14 standard dimensions (from 500 x 500 up to 1250 x 1000) in one depth 320 mm
- Cabinets are standard factory assembled (empty or equipped)
- High protection degree **IP65 & IP54**-IK10 (20 J) according to IEC 60529 and EN/IEC 62262 (IP54 - IK07 for cabinets with glazed door)
- Material: self-extinguishing, hot moulded, halogen-free, fiberglass reinforced polyester (environment friendly)
- Colour: grey RAL7035, dyed in mass
- Designed for wall mounting, floor standing and pole fixing
- Coupling possibilities in height, width and depth
- Total insulation
- Door with 5-point latching mechanism
- Execution as pedestal possible
- Rated insulation voltage $U_i = 1000V$
- Easy recyclable: no moulded-in metal parts



Overview of the range ● Page B.3

Dimensional drawings ● Page I.22

Specifications for tender documents ● Page I.54

Power dissipation values ● Page I.72