

## Specifications for BMP61 Label Printer - QWERTY EU

<b>Approval/Compliance</b>	CE 2014/35/EU LVD, 2014/30/EU EMCD, 2011/65/EU, 2015/863/EU; UL 60950-1, 2nd Edition; EN \ IEC 60950-1:2006 + A11:2009 + A1:2010 + A12:2011+ A2:2013; WEEE; RoHS
<b>Article No.</b>	146230
<b>Barcode Capability</b>	Yes
<b>Battery Type</b>	NiMH Battery, Rechargeable Battery
<b>Brand</b>	Brady®
<b>Built-in Symbols</b>	480
<b>Colour Capability</b>	Monocolour
<b>Connectivity Options</b>	Cabled, Standalone Use, USB 2.0, USB Host
<b>Continuous vs Die Cut Labels</b>	Continuous Tape & Die Cut Labels
<b>Description</b>	The BMP™61 Label Printer matches your own performance. It is your trusted identification companion of choice, all day, every day, for years to come. It features multiple user interfaces, touchscreen capabilities and a variety of ways to connect, manage and save your data. It prints continuous, die cut labels and bulk rolls up to 50.8mm extremely fast. Also customs. This printer comes with a free Brady WorkStation Basic Design Software Suite, enabling you to immediately start designing professional labels.
<b>Display Type</b>	Colour Touchscreen, LCD backlit graphics display
<b>Drop Test</b>	up to 1.2 metres
<b>Includes</b>	This printer ships in a hard case holding a USB cable, a quick start guide, a battery pack, an AC Adapter, a CD with driver, a product CD, a hand strap, a Brady Workstation Basic Suite, a roll of PTL-19-423 and an M61-R6010 ribbon
<b>Industry</b>	Automotive, Beverage processing, Biotechnology, Buildings identification, Chemical, Education, Electrical, Electronics, Energy utilities, Food processing, Government, Healthcare, ICT, Laboratory, Manufacturing, Mass transit, Oil & gas, Pharmaceutical, Process, Security, Voice & data communication
<b>Interface Type</b>	Full QWERTY Keyboard, PC, Touchscreen
<b>Internal Memory Capacity</b>	512 MB RAM / 256MB Flash
<b>Keyboard Type</b>	QWERTY
<b>Materials Supported</b>	Freezerbondz Polyester; Heat-shrink Polyolefin Sleeve; High Temperature Heat-shrink Polyvinylidene Fluoride Sleeve; Metallised Polyester; Metallised Polyester with Polyester Overlamine; Nylon Cloth; Paper; Paper with Polyester Overlamine; Polyester; Polyester Tag; Polyethylene Foam Laminate Polyester; Polyethylene Tag; Polyimide; Polypropylene; Polypropylene Tag; Polyvinylfluoride; Rigid Insert; Self-laminating Polyester; Self-laminating Vinyl; Static Dissipative Polyester; Tamper-evident Metallised Polyester; Tamper-evident

	Polyester; Tamper-resistant Metallised Vinyl; Tamper-resistant Vinyl; Thermoplastic Polyether Polyurethane; Vinyl; Vinyl Cloth; Vinyl Tag
<b>Max. Label Width (mm)</b>	50.80 mm
<b>Max. Liner Width (mm)</b>	57.15 mm
<b>Max. Lines of Text</b>	25
<b>Max. Print Length (mm)</b>	1016.00 mm
<b>Max. Print Width (mm)</b>	48.76 mm
<b>Min. Label Length (mm)</b>	5.99 mm
<b>Min. Liner Width (mm)</b>	20.62 mm
<b>Minimum Label Height (mm)</b>	5.99
<b>Operating Temperature</b>	5°C - 40°C
<b>Order Reference</b>	BMP61-QWERTY-EU
<b>Portability</b>	Yes
<b>Power Requirements</b>	110-240V
<b>Print Rotation</b>	Yes
<b>Print Speed (mm/sec)</b>	33.80 mm/s
<b>Print Technology</b>	Thermal Transfer
<b>Recommended Usage per Day</b>	750
<b>Resolution (dpi)</b>	300 dpi
<b>Serialisation</b>	Multiple & Linked
<b>Size - Depth (mm)</b>	106.40 mm
<b>Size - Height (mm)</b>	328.42 mm
<b>Size - Width (mm)</b>	107.00 mm
<b>Smart Cell</b>	Yes
<b>Software Compatibility</b>	LabelMark
<b>Stand Alone Printing</b>	Stand-alone & Peripheral
<b>Total Qty per Pack</b>	1 Piece(s) / Pack
<b>Weight (kg)</b>	1.41 kg