

## **Data Sheet 1221418**

**Product:** 32/246 8-løp takboks

**El-number:** 1221418 **Mat.no:** EKO04026 **EAN:** 7020160402615

Packing: 50 Color: White



**Product description:** 32mm connection box for ceiling. Suitable for 1 plate of plasterboard or

woodpanel. Conduit entries: 8 entries x 16 mm  $\varnothing$  Delivered with locking spings and sealingplugs in each entry, and plastic lid. It is possible to enter a 20 mm  $\varnothing$  conduit to each entry - by use of a 20 mm sleeve. Extra mounting ring of 10 mm is available in case the box is fixed too deep. The outer

diameter of the box is 83 mm.

DCL ceilingsocket does not fit this box, use of a DCL extension ring is

necessary.

**Technical specifications:** Single box for ceiling mounting, with installation screws.

Depth: 32 mm.

Standard: EMKO-TUI (25) SF 101/76 Nordic.

Mounting screws: M4.

cc 70 mm between inside mounting screws.

Halogenfree.

Maximum temperature during casting process: 90°C


Minimum installation temperature: -25°C

Max load 14 kg

Cutting diameter: 83mm

Size

Wiring diagram



ELKO AS

E-mail: elko@elko.no
Internet: www.elko.no
Bank: 6219.05.15880
Org.no.: NO 911 382 563 MVA

ELKO Front office

Sandstuveien 68, NO-0680 Oslo P.O.Box 6598 Etterstad, NO-0607 Oslo

Tel.: +47 67 80 73 00 Fax: +47 67 80 73 01 ELKO Plant

Sporpind Industriområde, NO-3340 Åmot

Tel.: +47 32 78 91 00 Fax: +47 32 78 91 01