

CURRENT MEASURING MODULE; SET CURRENT 10...100A;
OVERALL WIDTH 55MM; STRAIGHT-THROUGH CT



Figure similar

product brandname	SIRIUS
Product designation	Current measuring module
General technical data	
Product function	
• Current measurement	Yes
• voltage measurement	No
• active power measurement	No
• Power measurement	No
• frequency measurement	No
Product component	
• input for thermistor connection	No
Insulation voltage	
• with degree of pollution 3 rated value	690 V
Surge voltage resistance rated value	6 000 V
Protection class IP	IP20
Shock resistance	
• acc. to IEC 60068-2-27	15g / 11 ms

Vibration resistance	1-6 Hz / 15 mm; 6-500 Hz / 2 g
Equipment marking	
• acc. to DIN EN 81346-2	F
Electromagnetic compatibility	
EMC emitted interference	
• acc. to IEC 60947-1	class A
Conducted interference	
• due to burst acc. to IEC 61000-4-4	2 kV
• due to conductor-earth surge acc. to IEC 61000-4-5	2 kV
• due to conductor-conductor surge acc. to IEC 61000-4-5	1 kV
Field-bound parasitic coupling acc. to IEC 61000-4-3	10 V/m
Inputs/ Outputs	
Number of outputs as contact-affected switching element	0
Protective and monitoring functions	
Product function	
• power factor monitoring	No
• voltage detection	No
Motor protection functions	
Product function	
• Current detection	Yes
• Overload protection	Yes
Installation/ mounting/ dimensions	
Mounting position	any
Mounting type	screw and snap-on mounting
Height	94 mm
Width	55 mm
Depth	72 mm
Required spacing	
• top	30 mm
• bottom	30 mm
• left	0 mm
• right	0 mm
Connections/Terminals	
Type of electrical connection	
• for main current circuit	straight-through transformers
Ambient conditions	
Ambient temperature	

• during operation • during storage • during transport	-25 ... +60 °C -40 ... +80 °C -40 ... +80 °C
Relative humidity • during operation	5 ... 95 %
Short-circuit protection	
Product function Short circuit protection	No
Main circuit	
Number of poles for main current circuit	3
Adjustable pick-up value current of the current-dependent overload release	10 ... 100 A
Operating voltage • at AC — at 50 Hz rated value — at 60 Hz rated value	110 ... 690 V 110 ... 690 V
Operating frequency rated value	50 ... 60 Hz
Control circuit/ Control	
Type of voltage	AC
Type of voltage of the control supply voltage	AC
Certificates/approvals	

General Product Approval	EMC	For use in hazardous locations
--------------------------	-----	--------------------------------



For use in hazardous locations	Declaration of Conformity	Test Certificates	Shipping Approval
--------------------------------	---------------------------	-------------------	-------------------

[Explosion Protection Certificate](#)



[Type Test Certificates/Test Report](#)

[Special Test Certificate](#)



Shipping Approval	other
-------------------	-------



[Confirmation](#)

[PROFIsafe-Certification](#)



[PROFINET-Certification](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3UF7102-1AA00-0>

Cax online generator


<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3UF7102-1AA00-0>


Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3UF7102-1AA00-0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3UF7102-1AA00-0&lang=en





last modified:

07/07/2017