

ADDRESSING PLUG, FOR ASSIGNING THE PROFIBUS ADDRESS TO A BASIC UNIT W/O PC/PG TO SIMOCODE PRO W/O PC/PG



General technical data:	
product brandname	SIRIUS
Product designation	addressing plug
Design of the product	For assigning the PROFIBUS or Modbus RTU address without using a PC/PG
Ambient temperature	
• during storage	-40 ... +80 °C
• during operation	-25 ... +60 °C
• during transport	-40 ... +80 °C
Certificates/ approvals:	

General Product Approval			EMC	Declaration of Conformity	Test Certificates
					Special Test Certificate
CSA	UL		C-Tick	EG-Konf.	

Test Certificates	Shipping Approval				
Type Test Certificates/Test Report					
	ABS	DNV	GL	LRS	RMRS

other				
Confirmation	PROFIsafe-Certification		PROFINET-Certification	
		Profibus		

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3UF7910-0AA00-0>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3UF7910-0AA00-0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3UF7910-0AA00-0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3UF7910-0AA00-0&lang=en



