

# Carbon Monoxide Alarm

## Powered-for-Life Lithium Battery RadioLINK Wireless Upgrade (optional)

- Proven electrochemical sensor (6 year operational life).
- Powered-for-Life sealed lithium battery.
- End of life indication.
- Easy to use large Test/Hush button.
- Pre-alarm indication gives early warning of CO.
- Loud distinct alarm sound (85 dB(A) minimum at 3m).
- Memory feature indicates if CO has been previously detected.
- Power, alarm and fault indicator lights.
- 5 Year guarantee (limited).
- Add Ei200MRF RadioLINK modules to interconnect 2 or more alarms (sold separately).
- Interconnected alarms will all sound if CO is detected by any alarm.



## Product Description

The Ei208W Carbon Monoxide (CO) alarm is supplied with a powered-for-life sealed lithium battery.

The alarm has a high performance, proven electrochemical sensor to sense CO presence. The sensor is individually calibrated and tested in Carbon Monoxide (CO) gas to ensure accuracy.

The memory feature records the last CO alarm level and can be useful to check if CO has been present while the home owner or tenant was absent from the property.

An easy to use Test/Hush button allows the user to check the alarm. This checks all aspects of the alarm (sensor, electronics, battery and sounder).

The alarm has an "End of Life" indicator which will notify the user when the alarm needs replacing at the end of its 6 year operational life.

The alarm has a twist on mounting base which has multiple fixing points so it can easily be secured to a ceiling or wall. The fixing screws are supplied with the alarm.

While it is always best to fix the alarm position, it is also designed for desktop and table mounting. This makes the alarm portable for use in holiday homes and for frequent travelers.

## Operation

- When toxic levels of Carbon Monoxide are detected, the alarm will sound and the red alarm light will flash as detailed below:

CO Level	Red Led	Horn
< 43 ppm	Off	Off
43 to 80 ppm	1 flash every 2 seconds	On after 60 - 90 mins
80 to 150 ppm	1 flash every second	On after 10 - 40 mins
>150 ppm	2 flashes every second	On within 2 minutes

- The alarm will automatically clear when CO gas clears.
- An 'End of Life', sensor failure or low battery condition will be notified by visual and audible indicators.
- Test/Hush button operation:
  - When 'pressed and held' it will perform a test of the sensor, electronics, battery and sounder.
  - When 'pressed briefly' it will Hush (silence) the sounding alarm and all interconnected (RadioLINK) alarms.
  - As a safety feature the Hush (silence) button will not work if the CO level detected is greater than 150ppm.

Shannon Free Zone, Shannon, Co. Clare, Ireland.  
 Ph.+353 61 471277 Fx.+353 61 471053  
 Email. admin@eielectronics.ie  
 Web: www.eielectronics.com

Made  
in Ireland



## Technical Specification

<b>Sensor</b>	Proven Electrochemical, 100% calibrated and tested with CO gas to ensure accuracy. CO level is checked every 4 seconds.	<b>Indicator Lights:</b> <ul style="list-style-type: none"><li>• Power-up &amp; Test</li><li>• Alarm</li><li>• Fault</li><li>• Test / Diagnostic</li></ul>	Green light Red light Amber Light Red, Amber & Green Lights
<b>Sensitivity</b>	Meets BS EN 50291:2010.	<b>Button Test</b>	Checks the electronics, battery, horn and sensor
<b>CE Mark</b>	BS EN 50270:2006 (EMC) BS EN 60335-1:2002 (Safety)	<b>Memory Feature</b>	Records if a previous alarm threshold has been exceeded
<b>Kitemark</b>	BS EN 50291:2010	<b>Wireless Communication</b>	When fitted with an Ei200MRF RadioLINK module
<b>Supply Voltage</b>	Powered-for-life sealed lithium battery.	<b>Fixing</b>	Screw fixing & free standing
<b>Alarm Horn</b>	Piezoelectric	<b>Product Dimensions</b>	120 x 105 x 45 mm
<b>Sound Output</b>	85dB(A) at 3m. Modulated sound gives 3 rapid pulses followed by a ½ second pause.	<b>Package Dimensions</b>	122 x 135 x 50 mm
<b>Temperature Range</b>	-10°C to 40°C	<b>Weight</b>	180g
<b>Relative Humidity</b>	15% to 95% non condensing		

## Product Family

Model Number	Description
Ei207	Stand alone with replaceable AAA Batteries
Ei207D	Stand alone with replaceable AAA Batteries and LCD Display
Ei208W	Powered for Life sealed Lithium Battery and optional RadioLINK upgrade
Ei208DW	Powered for Life sealed Lithium Battery, LCD Display and optional RadioLINK upgrade
Ei208WRF	Powered for Life sealed Lithium Battery with RadioLINK module fitted
Ei208DWRF	Powered for Life sealed Lithium Battery with LCD display & RadioLINK module fitted.
Ei200MRF	RadioLINK upgrade module for Ei208W and Ei208DW