
4 Channel Constant Voltage DALI LED Dimmer





4 Address/4 Channel/ Constant voltage/ PMW dimming



C∈ RoHS

Features

- 4 channel constant voltage DALI LED Dimmer, 5A per channel.
- . 4 DALI address, 4 channel work separately.
- In accordance with DALI standard protocol IEC 62386-102, IEC 62386-207 and in compliance with DALI products from other international incorporation.
- . DALI address will be automatically assigned by DALI master
- . PWM digital dimming, standard DALI logarithmic dimming curve.
- . Over-load / Short circuit protection, recover automatically.

Technical Parameters


Input and Output	
Input voltage	12 - 24VDC
Input current	20.5A
Output voltage	12 - 24VDC
Output current	4CH, 5A/CH
Output power	4 x (60-120)W
Output type	Constant voltage


Warranty and Protection		
Warranty	5 years	
Protection	Reverse polarity Over -l oad Short circuit	

DALI
0 -100 %
Logarithmic
2000Hz (default)


Environment	
Operationtemperature	Ta: -30°C ~ +55 °C
Case temperature (Max.)	Tc: +85 °C
I Prating	IP20

Mechanical Structures and Installations





Wiring Diagram



DALI control

This product is designed with 4 DALI address input and 4 channel output, DALI address is assigned by DALI Master controller automatically, please refer to user manuals of compatible DALI Masters for specific operations.

Safety & Warnings

- · DO NOT install with power applied to device.
- · DO NOT expose the device to moisture.