FrostGuard





PRODUCT DESCRIPTION

nVent RAYCHEM FrostGuard is a pre-terminated, self regulating, frost protection cable for pipes. The product includes a pre-installed electrical cable and plug for quick and easy connection to the power supply.

The small geometry, yet robust, cable adjusts its power output dependent upon ambient temperature. Therefore more heat is generated automatically when needed and less heat in warmer ambient conditions, saving energy.

Subject to local norms and approvals, FrostGuard can be used for in-pipe applications.

ADVANTAGES

Product selection phase

Available in 10 sizes to suit most application requirements.

Pre-installed with a plug and cold lead to avoid the need for electrical connections.

Self regulating heater to deliver just the heat that is needed.

The installation phase

The quickest and easiest installation possible. Simply plug and go!

Fix the cable to the pipe with GT-66 adhesive tape.

For in-pipe applications (where permitted) install using a RAYCHEM approved pipe entry gland assembly.

The application

Ideal for small diameter pipework.

An excellent solution for condensate pipework of condensing boilers.

The right choice for domestic and small commercial buildings.

| TECHNICAL DATA | | |
|--------------------------------|---|--|
| Nominal power | 10 W/m @ 5°C | |
| Voltage | 230 Vac | |
| Maximum exposure temperature | 65°C | |
| Min. Installation Temperature | -10°C | |
| Heating cable | Self-regulating cable with protective braid and fluoroploymer jacket in compliance with IEC62395. | |
| Approvals | SEMKO, VDE, CE, SITAC (Swedish approval for in drinking water applications.) | |
| RELATED NVENT RAYCHEM PRODUCTS | | |
| GL-T2-ETL | Straight entry gland kit for in-pipe applications. | |
| GL-T2-Y-25MM | Y-Coupling entry kit for in-pipe applications – 25 mm version | |

GL-T2-Y-32MM

Y-Coupling entry kit for in-pipe applications – 32 mm version.

PRODUCT REFERENCES

| Product Description | Heater Length (m) | PCN | EAN Code |
|---------------------|-------------------|-------------|---------------|
| FrostGuard-2m-UK | 2 | 1244-011339 | 5414506013207 |
| FrostGuard-4m-UK | 4 | 1244-011340 | 5414506013214 |
| FrostGuard-6m-UK | 6 | 1244-011341 | 5414506013221 |
| FrostGuard-8m-UK | 8 | 1244-011342 | 5414506013238 |
| FrostGuard-10m-UK | 10 | 1244-011343 | 5414506013245 |
| FrostGuard-13m-UK | 13 | 1244-011344 | 5414506013252 |
| FrostGuard-16m-UK | 16 | 1244-011345 | 5414506013269 |
| FrostGuard-19m-UK | 19 | 1244-011346 | 5414506013276 |
| FrostGuard-22m-UK | 22 | 1244-011347 | 5414506013283 |
| FrostGuard-25m-UK | 25 | 1244-011348 | 5414506013290 |

United Kingdom

Tel 0800 969 013 Fax 0800 968 624 salesthermalUK@nvent.com

Ireland

Tel 1800 654 241 Fax 1800 654 240 salesIE@nvent.com



Our powerful portfolio of brands: **nVent.com** CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER

©2018 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners nVent reserves the right to change specifications without notice.