

FREEDM™ Tight Buffer Indoor/Outdoor Cable 12F E9/125 SMF-28® ULTRA 0.9 TB3, Cca-s1a,d1,a1

CORNING

Part Number:
012Z8X-32125E2G

Corning MPC (multipurpose cable) tight-buffered cables are flame-retardant, indoor/outdoor cables designed for interbuilding and intrabuilding backbones in duct and riser applications.

The tight-buffered construction facilitates easier termination for low-fiber-count applications in the local area network (LAN) and eliminates need for fan-out kits.

These cables are designed for installation in conduits, ducts and in-house.



Features and Benefits

Waterblocking technology

OSP (outdoor) applications

All-dielectric cable construction

Requires no grounding or bonding

UV- and microbe-resistant

Can be installed in ducts or conduits

Dry cable core by means of water swellable elements

Allows efficient and craft-friendly cable preparation in outdoor or indoor/outdoor applications

Small diameter and bend radius

Easy installation in space-constrained areas

TB3 tight-buffered construction

TB3 tight-buffered construction

Flame retardant

LSZH™/FRNC

Specifications

Mechanical Specifications

Crush resistance	500 N/10 cm
Fire load	0.76 MJ/m
Min. bend radius installation	130 mm
Min. bend radius operation	97.5 mm
Nominal outer diameter	6.5 mm

FREEDM™ Tight Buffer Indoor/Outdoor Cable 12F E9/125 SMF-28® ULTRA 0.9 TB3, Cca-s1a,d1,a1

CORNING

Cable Design

Central element	Aramid yarn with swellable elements
Fibre count	12
Number of ripcords	1
Buffer tube diameter	900 mm
Outer jacket colour	Black
Buffering diameter	900 µm
Outer jacket material	Flame-retardant, non-corrosive/low-smoke, silicon-free, zero-halogen (FRNC/LSZH) material
Outer jacket nominal thickness	0.8 mm
Tensile Strength Elements and/or Armouring - Layer 1	Aramid yarn
Tensile strength elements and/or armouring - Layer 2	Aramid yarn
Tight buffer colour, layer 1	Blue, orange, green
Tight buffer colour, layer 2	Brown, grey, white, red, black, yellow, violet, pink, turquoise
Tight buffer type	TB3 (easy strip up to 10 cm)
Flame rating	LSZH™/FRNC

Environmental Conditions

Temperature range, storage	-25 °C to 70 °C (-13 °F to 158 °F)
Temperature range, installation	-5 °C to 50 °C (23 °F to 122 °F)
Temperature range, operation	-20 °C to 60 °C (-4 °F to 140 °F)

General Specifications

Environment	Indoor/Outdoor
Cable type	Tight-buffered
Product type	Dielectric
Fibre category	SMF-28® Ultra 242 Optical Fibre
Flame rating	LSZH™/FRNC

FREEDM™ Tight Buffer Indoor/Outdoor Cable 12F E9/125 SMF-28® ULTRA 0.9 TB3, Cca-s1a,d1,a1

CORNING

General Specifications

Coding according to EN 60794-1-1 (DIN VDE 0888-100-1)	U-VQ(ZN)H
Application	Direct Buried , Duct , Vertical Riser , General Purpose Horizontal

Ordering Information

Weight	40 kg/km
--------	----------

Standards

Reaction to fire	Cca, s1a, d1, a1
RoHS	Free of hazardous substances according to RoHS 2011/65/EU
Waterblocking	IEC 60794-1-2 F5
Flame propagation test	Flame retardant according to IEC 60332-1-2 (single cable) and IEC 60332-3-24 (bunch of cables)
Reaction to fire requirements	Reaction to fire according to EN 50575 and EN 13501-6
Smoke density	Low Smoke to IEC 61034
Halogen content test	Zero Halogen to IEC 60754-1
Level of corrosion	Non-corrosive according to IEC 60754-2

Optical Characteristics

Cable cutoff wavelength	1260 nm
Fibre code	Z
Fibre name	SMF-28® Ultra 242 Optical Fibre
Fibre Type	Single-mode
Fibre compliance	ITU-T G.652.D and ITU-T G.657.A1
Cladding diameter	125 µm
Dispersion @ 1550 nm	18 nm
Dispersion in the range 1285 to 1330 nm	3.5 nm

FREEDM™ Tight Buffer Indoor/Outdoor Cable 12F E9/125 SMF-28® ULTRA 0.9 TB3, Cca-s1a,d1,a1

CORNING

Optical Characteristics

Maximum Attenuation	0.34 dB/km / 0.34 dB/km / 0.20 dB/km
Mode-Field Diameter at 1310 nm	9.2 µm
Serial 1 gigabit ethernet	5000 MHz*km / -
Serial 10 gigabit ethernet	10000 MHz*km / 40000 MHz*km
Typical attenuation	0.32 dB/km / 0.32 dB/km / 0.18 dB/km
Wavelengths	1310 nm / 1383 nm / 1550 nm
PMD Link Design Value	0.04 ps/(nm*km)
PMD maximum individual fibre	0.1 ps/(nm*km)
Coating diameter	242 µm



Corning Optical Communications GmbH & Co. KG • Lelpziger Strasse 121 • 10117 Berlin, Germany
+00 800 2675 4641 • FAX: +49 30 5303 2335 • www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks.
Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2020 Corning Optical Communications. All rights reserved.