



XLED HOME 2 HVIT

ART.NR: 033088

Elnummer: 3202084

Bruksområde: Sikkerhetsbelysning på bolig, industribygg, barnehager etc.

PRODUKTFORESPØRSEL

[Brukermanual XLED Home 2](#)

[FDV](#)



LED-teknologi kombinert med deksel i opal gir maksimal belysningskomfort. Med et effektforbruk på bare 14,8 W gir denne lyskasteren 1184 lumen. IR-sensoren med en dekningsvinkel på 140° kan dreies 180° horisontalt og 90° vertikalt. 14 m rekkevidde. Høy varmeledningsevne magnesium kompositt kjølesystem (HCMC).
XLED Home 2 er tilgjengelig i hvitt, svart, grått og sølv.

Lyskasteren finnes også uten bevegelsessensor og fotocelle.

TEKNISKE DATA:

Mål (h x b x d) :	194 x 180 x 161 mm
Spennig:	230 -240 V, 50/60 Hz
Effekt:	14,8W
Lysfarge:	4000 Kelvin / SDCM 3
Lysåuks:	1184 lm / 80 lm/W
Levetid på lyskilde:	50.000 timer
LED kjølesystem:	HCMC
Sensorteknikk:	IR-sensor
Ant. som kan parallellkobles:	10 stk
Dekningsvinkel:	140° med krypedetektor
Svingvidde lyskaster:	180° horisontalt, 180° vertikalt
Svingvidde sensor:	180° horisontalt, 90° vertikalt
Dekningsrekkevidde:	maks. 14 m (temperaturstabilisert), segmenter kan utelukkes fra dekning
Skumringssinnstilling:	2 - 2000 Lux
Tidsinnstilling:	8 sek - 35 min
Beskyttelsesart:	IP 44
Beskyttelsesklasse:	II
Materiale:	UV-bestendig plast

RELATERT PRODUKT



XLED HOME 2 SORT





XLED HOME 2 SL HVIT



XLED HOME 2 SL SORT



XLED HOME 2 SL GRAFITT



XLED HOME 2 SL SØLV

