

UNICONE™ 83 ASYM


UNICONE™ 83 ASYM WARMDIM

CE □ ↺ ⚡ ⚠

220-240V 50/60Hz LED IP44*

EN: MEASUREMENT

NO: MÅL
SE: MÅTT
FI: MITAT




EN: Installation must be performed by a qualified electrician.
NO: Må installeres av autorisert el-installatør.
SE: Måste installeras av en behörig elinstallatör.
FI: Vain valtuutettu sähköasentaja saa asentaa.

OBS!

EN: CABLE CONNECTION

NO: LEDNINGSTILKOBING
SE: KABELANSLUTNING
FI: JOHTOLIITÄNTÄ




EN: Included dimmable LED driver.
NO: Inkludert dimbar LED driver.
SE: Inklusive dimbar LED drivdon.
FI: Sisältää himmennettävän LED-liitäntäliitteen.

EN: CORRESPONDING PRODUCT.






NO: TILHØRENDE PRODUKT.
SE: TILLHÖRANDE PRODUKT.
FI: AIHEESEEN LIITTYVÄ TUOTE.

UniDim™	KUD-265EV
UniDim™	KUD-500EV-L
UniDim™	KUD-500EV-LS
UniDim™	DUO
UniDim™	MINI
UniDim™	KDT-500IE
WiDim®	WI-FI system
Bluedim®	Bluetooth system
DOWNLIGHT BOX HIGH	
DRIVER PIPE HOUSING	


ALT.: 1



ALT.: 2



EN: IP44 from the luminaire underside.
NO: IP44 fra armaturens underside.
SE: IP44 från armaturens undersida.
FI: IP44 valaisimen alapuolelta.



EN: Minimum distance to flammable material in the beam direction.
NO: Minimumsavstand til brennbar materiale i armaturens stråleretning.
SE: Minsta avstånd mellan brännbart materiale och lampans ljusrättning.
FI: Vähimmäismitta lampusta palaavaan materiaaliin.