



Buntebånd i PA6.6 standard

• Serie T, nat

Materialdata

Materiale	Polyamid 6.6 (PA66)
Driftstemperatur	-40°C til +85°C varig, (+105°C i 500 t)
Brennbarhetsklasse	UL94 V2



Typebetegnelse og tekniske data

Art.nr.	El.nr.	Type	Lengde (L)	Bredde (W)	Bunte Ø max.	Min. strekkfasthet (N)	Materiale	Farge	Mont. verktøy
Polyamid 6.6 (PA66)									
111-02809	–	T18S	83	2,3	16,0	80	PA66	Nat. (NA)	1–3, 5
111-01919	13 450 01	T18R	100	2,5	22	80	PA66	Nat. (NA)	1–3, 5
111-02319	13 447 01	T18I	145	2,5	35,0	80	PA66	Nat. (NA)	1–3, 5
111-02119	–	T18L	205	2,5	55	80	PA66	Nat. (NA)	1–3, 5
111-02519	–	T25L	240	2,8	65,0	110	PA66	Nat. (NA)	1–3, 5
111-02619	13 447 04	T25LL	330	2,8	95,0	110	PA66	Nat. (NA)	1–3, 5
111-03219	–	T30R	150	3,5	35	135	PA66	Nat. (NA)	1–3, 5
111-03419	13 450 04	T30L	198	3,5	50	135	PA66	Nat. (NA)	1–3, 5
111-03549	–	T30LL	290	3,5	80,0	135	PA66	Nat. (NA)	1–3, 5
111-03819	–	T40R	175	4,0	40,0	180	PA66	Nat. (NA)	1–5
111-05819	–	T50S	150,0	4,6	35,0	225	PA66	Nat. (NA)	1–10
111-05013	13 450 05	T50R	200	4,6	50,0	225	PA66	Nat. (NA)	1–10
111-06201	13 450 10	T50M	245	4,6	65,0	225	PA66	Nat. (NA)	1–10
111-05219	13 447 08	T50I	300	4,6	85,0	225	PA66	Nat. (NA)	1–10
111-05409	13 450 06	T50L	390	4,6	110	225	PA66	Nat. (NA)	1–10
111-05019	–	T80R	210	4,7	55	355	PA66	Nat. (NA)	1–10
111-08229	–	T80I	300	4,7	85	355	PA66	Nat. (NA)	1–10
111-05419	–	T80L	390	4,7	110	355	PA66	Nat. (NA)	1–10
111-12829	–	T120S	225,0	7,6	55,0	535	PA66	Nat. (NA)	6–10
111-12219	13 447 10	T120I	300	7,6	80,0	535	PA66	Nat. (NA)	6–10
111-12019	13 450 07	T120R(E)	387	7,6	100	535	PA66	Nat. (NA)	6–10
111-12619	13 450 08	T120M	460	7,6	130	535	PA66	Nat. (NA)	6–10
111-12704	–	T120XM	600	7,6	175	535	PA66	Nat. (NA)	6–10
111-12429	13 447 12	T120L	760	7,6	225	535	PA66	Nat. (NA)	6–10
111-14819	–	T150R	365	7,6	100	670	PA66	Nat. (NA)	6–10
111-15619	13 447 14	T150M	525	8,9	150	780	PA66	Nat. (NA)	6–9
111-15419	–	T150L	820	8,9	245	780	PA66	Nat. (NA)	6–9
111-15519	–	T150XL	1095	8,9	330	780	PA66	Nat. (NA)	6–9
111-15304	–	T150XLL	1325	8,9	405	780	PA66	Nat. (NA)	6–9
111-24705	–	T250S	225	12,5	55,0	1115	PA66	Nat. (NA)	7–9
111-25103	–	T250X	370	12,5	100	1115	PA66	Nat. (NA)	7–9
111-24803	–	T250R	520	12,5	145	1115	PA66	Nat. (NA)	7–9
111-25002	–	T250M	565	12,5	150	1115	PA66	Nat. (NA)	7–9
111-25219	–	T250I	725	12,5	203	1115	PA66	Nat. (NA)	7–9
111-00466	–	T250XL	1030	12,5	305	1115	PA66	Nat. (NA)	7–9

Alle dimensjoner i mm. Med forbehold om tekniske endringer.



For produktspesifikke godkjenninger, se tilleggsmasjiner, se tilleggsmasjiner bakerst i katalogen.