Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- RussianNorw egian Bokmål

Worldwide English



PLHT-D100/3 - Miniature circuit breaker (MCB), 100A, 3p, D-Char, AC



248049 PLHT-D100/3 Overview Specifications Resources 요요모



248049 PLHT-D100/3

Mniature circuit breaker (MCB), 100A, 3p, D-Char, AC EL-Nummer (Norway) 1609557

Mniature circuit breaker (MCB) PLHT, 3 pole, Tripping characteristic: D, Rated current In: 100 A, Rated switching capacity according to IEC/EN 60947-2, Switchgear for industrial and advanced commercial applications

- Delivery program
- Technical data

• Design verification as per IEC/EN 61439

• Technical data ETIM 7.0

Delivery program

Basic function Miniature circuit-breakers Number of poles 3 pole Tripping characteristic D Application Switchgear for industrial and advanced commercial applications Rated current [I_n] 100 A Rated switching capacity acc. to IEC/EN 60947-2 [I_{cu}] 15 kA Product range PLHT

Technical data

Electrical Rated switching capacity acc. to IEC/EN 60947-2 $[I_{\rm cu}]$ 15 kA

Design verification as per IEC/EN 61439

Technical data for design verification Rated operational current for specified heat dissipation $[{\rm I_n}]$ 100 A

Heat dissipation per pole, current-dependent [P_{vid}] 0 W Equipment heat dissipation, current-dependent [P_{vid}] 27.4 W Static heat dissipation, non-current-dependent [P_{vs}] 0 W Heat dissipation capacity [Pdiss] 0 W Operating ambient temperature min. -25 °C Operating ambient temperature max. +55 °C linear, per +1 °C, results in a 0.35% reduction of current carrying capacity IEC/EN 61439 design verification 10.2 Strength of materials and parts10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2 Strength of materials and parts10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2 Strength of materials and parts 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2 Strength of materials and parts10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects Meets the product standard's requirements. 10.2 Strength of materials and parts10.2.4 Resistance to ultra-violet (UV) radiation Meets the product standard's requirements. 10.2 Strength of materials and parts 10.2.5 Lifting Does not apply, since the entire switchgear needs to be evaluated. 10.2 Strength of materials and parts 10.2.6 Mechanical impact Does not apply, since the entire switchgear needs to be evaluated. 10.2 Strength of materials and parts 10.2.7 Inscriptions Meets the product standard's requirements. 10.3 Degree of protection of ASSEVBLIES Does not apply, since the entire switchgear needs to be evaluated. 10.4 Clearances and creepage distances Meets the product standard's requirements. 10.5 Protection against electric shock Does not apply, since the entire switchgear needs to be evaluated. 10.6 Incorporation of switching devices and components Does not apply, since the entire switchgear needs to be evaluated. 10.7 Internal electrical circuits and connections Is the panel builder's responsibility. 10.8 Connections for external conductors Is the panel builder's responsibility. 10.9 Insulation properties 10.9.2 Pow er-frequency electric strength Is the panel builder's responsibility. 10.9 Insulation properties 10.9.3 Impulse withstand voltage Is the panel builder's responsibility. 10.9 Insulation properties 10.9.4 Testing of enclosures made of insulating material Is the panel builder's responsibility. 10.10 Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. 10.11 Short-circuit rating Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.12 Electromagnetic compatibility Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.13 Mechanical function The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. Technical data ETIM 7.0 Circuit breakers and fuses (EG000020) / Miniature circuit breaker (MCB) (EC000042)

Electric engineering, automation, process control engineering / Electrical installation, device / Mniature circuit breaker system (MCB) / Mniature circuit breaker (MCB) (ecl@ss10.0.1-27-14-19-01 [AAB905014]) Release characteristic D

Number of poles (total) 3 Number of protected poles 3 Rated current 100 A Rated voltage 400 V Rated insulation voltage Ui 440 V Rated impulse withstand voltage Ump 4 kV Rated short-circuit breaking capacity Icn EN 60898 at 230 V 0 kA Rated short-circuit breaking capacity Icn EN 60898 at 400 V 0 kA Rated short-circuit breaking capacity Icu IEC 60947-2 at 230 V 15 kA Rated short-circuit breaking capacity Icu IEC 60947-2 at 400 V 15 kA Voltage type AC Frequency 50 - 60 Hz **Current limiting class** 3 Suitable for flush-mounted installation No Concurrently switching N-neutral No Over voltage category 3 Pollution degree 2 Additional equipment possible Yes Width in number of modular spacings 4.5 Built-in depth 75 mm Degree of protection (IP) IP20 Ambient temperature during operating -25 - 55 °C Connectable conductor cross section multi-wired 2.5 - 50 mm² Connectable conductor cross section solid-core 2.5 - 50 mm²

CAD data

- Product-specific CAD data (Web)
- 3D Preview (Web)

DWG files

DA-CD-plht_3p
File
(Web)

edz files

• DA-CE-ETN.PLHT-D100_3 File (Web)

Step files

• DA-CS-plht_3p File (Web)

Product photo



Instruction Leaflet

 Add-on Residual Ourrent Protection Unit PBHT (IL019151ZU) Asset MA150501247 (PDF, 06/2020, Language independent)

Declaration of Conformity

EU

 DA-DC-03_PLH_180820 Asset (PDF)

Download-Center

- Download-Center (this item) Eaton EVEA Download-Center - download data for this item
- Dow nload-Center
 - Eaton EVEA Download-Center

ß

Generate data sheet in PDF format

x

Generate data sheet in Excel format

Write a comment Imprint Privacy Policy Legal Disclaimer Terms and Conditions © 2021 by Eaton Industries GmbH

