



## Phase busbar, 2-phases, 10qmm, fork connector, 12SU

**Part no.** EVG-2PHAS/12MODUL  
**Article no.** 215641

Similar to illustration

### Delivery program

|                            |  |  |                                                                                                                                                    |
|----------------------------|--|--|----------------------------------------------------------------------------------------------------------------------------------------------------|
| Basic function             |  |  | Busbar                                                                                                                                             |
| Basic function accessories |  |  | Busbar for miniature circuit-breaker<br>Busbar for residual-current circuit-breakers<br>Busbar for combined residual-current/power circuit-breaker |
| Type                       |  |  | 2 phase                                                                                                                                            |
| Product range              |  |  | EVG                                                                                                                                                |

### Technical data ETIM 6.0

|                                                                                                                                                                                                   |  |                 |      |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|-----------------|------|
| Low-voltage industrial components (EG000017) / Phase busbar (EC000215)                                                                                                                            |  |                 |      |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar (ecl@ss8.1-27-37-13-06 [ACN992008]) |  |                 |      |
| Number of phases                                                                                                                                                                                  |  |                 | 2    |
| Number of poles                                                                                                                                                                                   |  |                 | 2    |
| Suitable for number of devices                                                                                                                                                                    |  |                 | 6    |
| Pitch dimensions                                                                                                                                                                                  |  | mm              | 0    |
| Cross section                                                                                                                                                                                     |  | mm <sup>2</sup> | 10   |
| Length                                                                                                                                                                                            |  | mm              | 210  |
| Number of modular spacings                                                                                                                                                                        |  |                 | 12   |
| Rated permanent current I <sub>u</sub>                                                                                                                                                            |  | A               | 63   |
| Type of electric connection                                                                                                                                                                       |  |                 | Fork |
| Insulated                                                                                                                                                                                         |  |                 | Yes  |
| Rated surge voltage                                                                                                                                                                               |  | kV              | 4    |
| Conditioned rated short-circuit current I <sub>q</sub>                                                                                                                                            |  | kA              | 25   |
| Max. rated operation voltage U <sub>e</sub>                                                                                                                                                       |  | V               | 500  |
| Rated short-time withstand current I <sub>cw</sub>                                                                                                                                                |  | kA              | 0    |
| Suitable for devices with N-busbar                                                                                                                                                                |  |                 | No   |
| Suitable for devices with auxiliary switch                                                                                                                                                        |  |                 | No   |