



1.1

General

Residual Current Devices - General Data Short description of the most important RCD types Symbol Description Eaton standard. Suitable for outdoor installation (distribution boxes for outdoor installation and building sites) up to 1-25 Conditionally surge-current proof (>250 A, 8/20 µs) for general application. Type AC: AC current sensitive RCCB Type A: AC and pulsating DC current sensitive RCCB, not affected by smooth DC fault currents up to 6 mA Type F: AC and pulsating DC current sensitive RCCB, trips also at frequency mixtures (10 Hz, 50 Hz, 1000 Hz), min. 10 ms time-delayed, min. 3 kA surge current proof, higher load capacity with smooth DC fault currents up to 10 mA Frequency range up to 20 kHz kHz Trips also at frequency mixtures (10 Hz, 50 Hz, 1000 Hz) M///// Type B: All-current sensitive RCD switchgear for applications where DC fault currents may occur. Non-selective, nondelayed. Protection against all kinds of fault currents. Type B+: All-current sensitive RCD switchgear for applications where DC fault currents may occur. Non-selective, non-delayed. Protection against all kinds of fault currents. Provides enhanced fire safety. kHz RCD of type G (min 10 ms time delay) surge current-proof up to 3 kA. For system components where protection G against unwanted tripping is needed to avoid personal injury and damage to property. Also for systems involving long lines with high capacitive reactance. Some versions are sensitive to pulsating DC. Some versions are available in all-current sensitive design. RCD of type S (selective, min 40 ms time delay) surge current-proof up to 5 kA. Mainly used as main switch, as well as in combination with surge arresters. This is the only RCD suitable for series connection with other types if the rated tripping current of the downstream RCD does not exceed one third of the rated tripping current of the device of type S. Some versions are sensitive to pulsating DC. Some versions are available in all-current sensitive design. "X-ray-proof", for avoiding unwanted tripping caused by x-ray devices. "röntgenfest" "Frequency converter-proof", for avoiding unwanted tripping caused by frequency converters, speed-controlled umrichterfest" drives, etc.

1

Kind of residual current and correct use of RCD Types

Kind of current	Current Correct use / application field profile of RCCB types					Tripping current	
	•	AC	A	F	B / B+		
Sinusoidal AC residual current	\sim	V	~	V	✓	0.5 to 1.0 $I_{\Delta n}$	
Pulsating DC residual current (positive or negative half-wave)		-	~	V	V	0.35 to 1.4 $I_{\Delta n}$	
Cut half-wave current			V	✓	V	Lead angle 90°:	
Lead angle 90° el Lead angle 135° el	VV		~	V	•	0.25 to 1.4 $I_{\Delta n}$ Lead angle 135°: 0.11 to 1.4 $I_{\Delta n}$	
Half-wave with smooth DC current of 6 mA		-	~	V	~	max. 1.4 $I_{\Delta n}$ + 6 mA	
Half-wave with smooth DC current of 10 mA		-	-	~	~	max. 1.4 I _{Δn} + 10 mA	
Smooth DC current	=======================================	-	-	-	✓	0.5 to 2.0 I _{Δn}	

Tripping time

Break time and non-actuating time for alternating residual currents (r.m.s. values) for type AC and A RCCB

Classification	I _{∆n} mA		$\mathbf{I}_{\Delta\mathbf{n}}$	2xI _{∆n}	5xl _{∆n}	5 x I _{∆n} or 0.25A	500A
Standard RCD Conditionally surge current- proof 250 A	≤30	Max. tripping time (s)	0.3	0.15		0.04	0.04
Standard RCD Conditionally surge current- proof 250 A	>30	Max. tripping time (s)	0.3	0.15	0.04		0.04
RCCBType G (Short-time-delay) Surge current-proof 3 kA	30	Min. non actuating time(s) Max. tripping time (s)	0.01 0.3	0.01 0.15		0.01 0.04	0.01 0.04
RCCBType G (Short-time-delay) Surge current-proof 3 kA	>30	Min. non actuating time(s) Max. tripping time (s)	0.01 0.3	0.01 0.15	0.01 0.04		0.01 0.04
RCCBType S (Selective) Surge current-proof 5 kA	>30	Min. non actuating time(s) Max. tripping time (s)	0.13 0.5	0.06 0.2	0.05 0.15		0.04 0.15

Break time for half-wave pulsating residual currents (r.m.s. values) for type A RCCB


Classification	I _{∆n} mA		1.4xI _{∆n}	2xl _{∆n}	$\mathbf{2.8xl}_{\Delta\mathbf{n}}$	4xl _{∆n}	7 x I _{∆n}	0.35 A	0.5 A	350A
Standard RCD Conditionally surge current-proof 250 A	<30	Max. tripping time (s)		0.3		0.15			0.04	0.04
Standard RCD Conditionally surge current-proof 250 A	30	Max. tripping time (s)	0.3		0.15			0.04		0.04
Standard RCD Conditionally surge current-proof 250 A	>30	Max. tripping time (s)	0.3		0.15		0.04			0.04
RCCBType G (Short-time-delay) Surge current-proof 3 kA	30	Max. tripping time (s)	0.3		0.15			0.04		0.04
RCCBType G (Short-time-delay) Surge current-proof 3 kA	>30	Max. tripping time (s)	0.3		0.15		0.04			0.04
RCCBType S (Selective) Surge current-proof 5 kA	>30	Max. tripping time (s)	0.5		0,2		0.15			0.15

1.3

General

Tripping Characteristics (IEC/EN 61008)

Tripping characteristics, tripping time range and selectivity of instantaneous, surge current-proof , G'' and surge current-proof - selective ,,S'' residual current devices.



IEC 60364-4-41 deals with additional protection: The use of RCDs with a rated residual operating current not exceeding 30 mA, is recognized in a.c. systems as additional protection in the event of failure of the provision for basic protection and/or the provision for fault protection or carelessness by users.

This means when using RCDs for fault current/residual current protection two RCDs must be connected in series.

Testing:


RCDs with tripping time delay (Types -G and -S) may be function tested with conventional testing equipment which must be set according to the instructions for operation of the testing device. Due to reasons inherent in the measuring process, the tripping time determined in this way may be longer than expected in accordance with the specifications of the manufacturer of the measuring instrument.

However, the device is ok if the result of measurement is within the time range specified by the manufacturer of the measuring instrument.


General

Hints for the application of our frequency converter-proof RCDs:

Due to the currents flowing off through the filters (designated IF), the sum of currents through the RCD is not exactly zero, which causes unwanted tripping.



Tripping characteristic



Frequency converters are used in a wide variety of systems and equipment requiring variable speed, such as lifts, escalators, conveyor belts, and large washing machines. Using them for such purposes in circuits with conventional residual current devices causes frequent problems with unwanted tripping.

The technical root cause of this phenomenon is the following: Fast switching operations involving high voltages cause high interference levels which propagate through the lines on the one hand, and in the form of interfering radiation on the other. In order to eliminate this problem, a mains-side filter (also referred to as input filter or EMC-filter) is connected between the RCD and frequency converter. The anti-interference capacitors in the filters produce discharge currents against earth which may cause unwanted tripping of the RCD due to the apparent residual currents. Connecting a filter on the output side between frequency converter and 3-phase AC motor results in the same behaviour.

This sample tripping characteristic of a 100 mA RCD and a 300 mA RCD shows the following: In the frequency range around 50 Hz, the RCDs trip as required (50 - 100 % of the indicated $I_{\Delta n}$).

In the range shown hatched in the diagram, i. e. from approx. 100 to 300 Hz, unwanted tripping occurs frequently due to the use of frequency converters. Frequency converter-proof residual current devices are much less sensitive in this frequency range than in the 50 - 60 Hz range, which leads to an enormous increase in the reliability of systems.

Therefore, we recommend to use RCDs designed for applications with frequency converter!

These special residual current devices can be recognised by an extension of the type designation ("-F"). They meet the requirements of compatibility between RCDs and frequency converters with respect to unwanted tripping.

These are NOT AC/DC-sensitive (IEC 62423) RCDs of type B !!!

Our RCDs of type "-F" are characterised by SENSITIVITY TO RESIDUAL PULSATING DC And SELECTIVITY S or SHORT-TIME DELAY G

Residual Current Devices FRCmM Type AC, A, U and R

SG02612





Description

- A complete spectrum of compact residual current devices for a wide range of applications
- For fault current/residual current protection and additional protection
- Wide variety of nominal currents
- Comprehensive range of accessories
- Real contact position indicator
- Automatic re-setting possible
- Classified for the use in rail rolling stock

Residual Current Devices FRCmM

 ${\rm I_n/I_{\Delta n} \atop (A)}$ Type Designation Operating frequency Article No. Units per package

Type A

Conditionally surge current-proof 250 A, sensitive to residual pulsating DC, Type A





2-poles			
16/0.03	50/60	FRCmM-16/2/003-A	170430 1/60
16/0.1	50/60	FRCmM-16/2/01-A	170436 1/60
16/0.3	50/60	FRCmM-16/2/03-A	170278 1/60
16/0.5	50	FRCmM-16/2/05-A	170281 1/60
25/0.03	50/60	FRCmM-25/2/003-A	170431 1/60
25/0.1	50/60	FRCmM-25/2/01-A	170437 1/60
25/0.3	50/60	FRCmM-25/2/03-A	170279 1/60
25/0.5	50	FRCmM-25/2/05-A	170282 1/60
40/0.03	50/60	FRCmM-40/2/003-A	170432 1/60
40/0.1	50/60	FRCmM-40/2/01-A	170274 1/60
40/0.3	50/60	FRCmM-40/2/03-A	170280 1/60
40/0.5	50	FRCmM-40/2/05-A	170283 1/60
63/0.03	50/60	FRCmM-63/2/003-A	170433 1/60
63/0.1	50/60	FRCmM-63/2/01-A	170275 1/60
63/0.3	50/60	FRCmM-63/2/03-A	304063 1/60
63/0.5	50	FRCmM-63/2/05-A	170284 1/60
80/0.03	50/60	FRCmM-80/2/003-A	170434 1/60
80/0.1	50/60	FRCmM-80/2/01-A	170276 1/60
80/0.3	50/60	FRCmM-80/2/03-A	304064 1/60
100/0.03	50/60	FRCmM-100/2/003-A	170435 1/60
100/0.1	50/60	FRCmM-100/2/01-A	170277 1/60
100/0.3	50/60	FRCmM-100/2/03-A	304065 1/60
			· · · · · · · · · · · · · · · · · · ·



1_	n	'n	ı	٥	c
*	۲	U	•	G	J

4-poles			
16/0.03	50/60	FRCmM-16/4/003-A	170285 1/30
16/0.03	50/60	FRCmM-16/4/003-A-400	304101 1/30
16/0.1	50/60	FRCmM-16/4/01-A	170337 1/30
16/0.3	50/60	FRCmM-16/4/03-A	170340 1/30
16/0.5	50	FRCmM-16/4/05-A	170346 1/30
25/0.03	50/60	FRCmM-25/4/003-A	170332 1/30
25/0.03	50/60	FRCmM-25/4/003-A-400	304102 1/30
25/0.1	50/60	FRCmM-25/4/01-A	170338 1/30
25/0.3	50/60	FRCmM-25/4/03-A	170341 1/30
25/0.5	50	FRCmM-25/4/05-A	170347 1/30
40/0.03	50/60	FRCmM-40/4/003-A	170333 1/30
40/0.03	50/60	FRCmM-40/4/003-A-400	304116 1/30
40/0.1	50/60	FRCmM-40/4/01-A	170339 1/30
40/0.3	50/60	FRCmM-40/4/03-A	170342 1/30
40/0.5	50	FRCmM-40/4/05-A	170348 1/30
63/0.03	50/60	FRCmM-63/4/003-A	170334 1/30
63/0.03	50/60	FRCmM-63/4/003-A-400	304167 1/30
63/0.3	50/60	FRCmM-63/4/03-A	170343 1/30
63/0.5	50	FRCmM-63/4/05-A	170349 1/30
80/0.03	50/60	FRCmM-80/4/003-A	170335 1/30
80/0.03	50/60	FRCmM-80/4/003-A-400	304186 1/30
80/0.3	50/60	FRCmM-80/4/03-A	170344 1/30
80/0.5	50	FRCmM-80/4/05-A	170350 1/30
100/0.03	50/60	FRCmM-100/4/003-A	170336 1/30
100/0.03	50/60	FRCmM-100/4/003-A-400	304194 1/30
100/0.3	50/60	FRCmM-100/4/03-A	170345 1/30
100/0.5	50	FRCmM-100/4/05-A	170351 1/30

Residual Current Devices FRCmM

 $I_n/I_{\Delta n}$ (A) Type Designation Operating frequency Article No. Units per package

Type G/A

Surge current-proof 3 kA, sensitive to residual pulsating DC, Type G/A (ÖVE E 8601)







2-poles				
16/0.03	50/60	FRCmM-16/2/003-G/A	170382	1/60
16/0.1	50/60	FRCmM-16/2/01-G/A	170388	1/60
16/0.3	50/60	FRCmM-16/2/03-G/A	170290	1/60
25/0.03	50/60	FRCmM-25/2/003-G/A	170383	1/60
25/0.1	50/60	FRCmM-25/2/01-G/A	170389	1/60
25/0.3	50/60	FRCmM-25/2/03-G/A	170291	1/60
40/0.03	50/60	FRCmM-40/2/003-G/A	170384	1/60
40/0.1	50/60	FRCmM-40/2/01-G/A	170286	1/60
40/0.3	50/60	FRCmM-40/2/03-G/A	170292	1/60
63/0.03	50/60	FRCmM-63/2/003-G/A	170385	1/60
63/0.1	50/60	FRCmM-63/2/01-G/A	170287	1/60
80/0.03	50/60	FRCmM-80/2/003-G/A	170386	1/60
80/0.1	50/60	FRCmM-80/2/01-G/A	170288	1/60
100/0.03	50/60	FRCmM-100/2/003-G/A	170387	1/60
100/0.1	50/60	FRCmM-100/2/01-G/A	170289	1/60



4-poles			
16/0.03	50/60	FRCmM-16/4/003-G/A	170293 1/30
16/0.1	50/60	FRCmM-16/4/01-G/A	170299 1/30
16/0.3	50/60	FRCmM-16/4/03-G/A	170302 1/30
25/0.03	50/60	FRCmM-25/4/003-G/A	170294 1/30
25/0.1	50/60	FRCmM-25/4/01-G/A	170300 1/30
25/0.3	50/60	FRCmM-25/4/03-G/A	170303 1/30
40/0.03	50/60	FRCmM-40/4/003-G/A	170295 1/30
40/0.1	50/60	FRCmM-40/4/01-G/A	170301 1/30
40/0.3	50/60	FRCmM-40/4/03-G/A	170304 1/30
63/0.03	50/60	FRCmM-63/4/003-G/A	170296 1/30
63/0.3	50/60	FRCmM-63/4/03-G/A	170305 1/30
80/0.03	50/60	FRCmM-80/4/003-G/A	170297 1/30
80/0.3	50/60	FRCmM-80/4/03-G/A	170306 1/30
100/0.03	50/60	FRCmM-100/4/003-G/A	170298 1/30
100/0.3	50/60	FRCmM-100/4/03-G/A	170307 1/30

Residual Current Devices FRCmM

 $I_n/I_{\Delta n}$ (A) Type Designation Operating frequency Article No. Units per package

Type S

Selective + surge current-proof 5 kA, Type S



2-poles			
16/0.1	50/60	FRCmM-16/2/01-S	170314 1/60
25/0.1	50/60	FRCmM-25/2/01-S	170315 1/60
40/0.1	50/60	FRCmM-40/2/01-S	170316 1/60
63/0.1	50/60	FRCmM-63/2/01-S	170317 1/60
80/0.1	50/60	FRCmM-80/2/01-S	170318 1/60
100/0.1	50/60	FRCmM-100/2/01-S	170319 1/60



4-poles			
16/0.1	50/60	FRCmM-16/4/01-S	170320 1/30
16/0.3	50/60	FRCmM-16/4/03-S	170324 1/30
25/0.1	50/60	FRCmM-25/4/01-S	170321 1/30
25/0.3	50/60	FRCmM-25/4/03-S	170325 1/30
40/0.1	50/60	FRCmM-40/4/01-S	170322 1/30
40/0.3	50/60	FRCmM-40/4/03-S	170326 1/30
63/0.1	50/60	FRCmM-63/4/01-S	170323 1/30
63/0.3	50/60	FRCmM-63/4/03-S	170327 1/30
80/0.3	50/60	FRCmM-80/4/03-S	170328 1/30
100/0.3	50/60	FRCmM-100/4/03-S	170329 1/30

Type S/A

Selective + surge current-proof 5 kA, sensitive to residual pulsating DC, Type S/A

2-poles			
16/0.1	50/60	FRCmM-16/2/01-S/A	170330 1/60
25/0.1	50/60	FRCmM-25/2/01-S/A	170331 1/60
40/0.1	50/60	FRCmM-40/2/01-S/A	170438 1/60
63/0.1	50/60	FRCmM-63/2/01-S/A	170439 1/60
80/0.1	50/60	FRCmM-80/2/01-S/A	170440 1/60
100/0.1	50/60	FRCmM-100/2/01-S/A	170441 1/60



4-poles				
16/0.1	50/60	FRCmM-16/4/01-S/A	170442	1/30
16/0.3	50/60	FRCmM-16/4/03-S/A	170446	1/30
25/0.1	50/60	FRCmM-25/4/01-S/A	170443	1/30
25/0.3	50/60	FRCmM-25/4/03-S/A	170447	1/30
40/0.1	50/60	FRCmM-40/4/01-S/A	170444	1/30
40/0.3	50/60	FRCmM-40/4/03-S/A	170448	1/30
63/0.1	50/60	FRCmM-63/4/01-S/A	170445	1/30
63/0.3	50/60	FRCmM-63/4/03-S/A	170449	1/30
80/0.3	50/60	FRCmM-80/4/03-S/A	170450	1/30
100/0.3	50/60	FRCmM-100/4/03-S/A	170451	1/30

Residual Current Devices FRCmM

 $I_n/I_{\Delta n}$ (A) Operating frequency Туре Article No. Units per Designation package

Type U

Short-time delayed + surge current-proof 3 kA, frequency converter-proof, Type U





4-poles			
16/0.03	50/60	FRCmM-16/4/003-U	170452 1/30
25/0.03	50/60	FRCmM-25/4/003-U	170453 1/30
40/0.03	50/60	FRCmM-40/4/003-U	170454 1/30
63/0.03	50/60	FRCmM-63/4/003-U	170455 1/30
80/0.03	50/60	FRCmM-80/4/003-U	170456 1/30
100/0.03	50/60	FRCmM-100/4/003-U	170457 1/30

Type U

Selective + surge current-proof 5 kA, frequency converter-proof, Type U



4-poles			
16/0.1	50/60	FRCmM-16/4/01-U	170458 1/30
16/0.3	50/60	FRCmM-16/4/03-U	170462 1/30
25/0.1	50/60	FRCmM-25/4/01-U	170459 1/30
25/0.3	50/60	FRCmM-25/4/03-U	170463 1/30
40/0.1	50/60	FRCmM-40/4/01-U	170460 1/30
40/0.3	50/60	FRCmM-40/4/03-U	170464 1/30
63/0.1	50/60	FRCmM-63/4/01-U	170461 1/30
63/0.3	50/60	FRCmM-63/4/03-U	170465 1/30
80/0.3	50/60	FRCmM-80/4/03-U	170466 1/30
100/0.3	50/60	FRCmM-100/4/03-U	170467 1/30

Type R

Surge current-proof 3 kA, X-ray application, Type R



4-poles			
16/0.03	50/60	FRCmM-16/4/003-R	170308 1/30
25/0.03	50/60	FRCmM-25/4/003-R	170309 1/30
40/0.03	50/60	FRCmM-40/4/003-R	170310 1/30
63/0.03	50/60	FRCmM-63/4/003-R	170311 1/30
80/0.03	50/60	FRCmM-80/4/003-R	170312 1/30
100/0.03	50/60	FRCmM-100/4/003-R	170313 1/30

Residual Current Devices FRCmM - RT

 $I_n/I_{\Delta n}$ (A) Type Designation Operating frequency Article No. Units per package

Type A

Conditionally surge current-proof 250 A, sensitive to residual pulsating DC, Type A



2-poles			
16/0.03	50/60	FRCmM-16/4/003-A-RT	305061 1/30
25/0.03	50/60	FRCmM-25/4/003-A-RT	305062 1/30
40/0.03	50/60	FRCmM-40/4/003-A-RT	305063 1/30
63/0.03	50/60	FRCmM-63/4/003-A-RT	305064 1/30
16/0.3	50/60	FRCmM-16/4/03-A-RT	305067 1/30
25/0.3	50/60	FRCmM-25/4/03-A-RT	305068 1/30
40/0.3	50/60	FRCmM-40/4/03-A-RT	305069 1/30
63/0.3	50/60	FRCmM-63/4/03-A-RT	305070 1/30



4-poles			
16/0.03	50/60	FRCMM-16/4/003-A-RT	305081 1/30
25/0.03	50/60	FRCMM-25/4/003-A-RT	305082 1/30
40/0.03	50/60	FRCMM-40/4/003-A-RT	305083 1/30
63/0.03	50/60	FRCMM-63/4/003-A-RT	305084 1/30
16/0.3	50/60	FRCMM-16/4/03-A-RT	305088 1/30
25/0.3	50/60	FRCMM-25/4/03-A-RT	305090 1/30
40/0.3	50/60	FRCMM-40/4/03-A-RT	305101 1/30
63/0.3	50/60	FRCMM-63/4/03-A-RT	305102 1/30

Type S

Selective + surge current-proof 5 kA, Type S



2-poles	2-poles				
16/0.3	50/60	FRCMM-16/2/03-S/A-RT	305071 1/30		
25/0.3	50/60	FRCMM-25/2/03-S/A-RT	305073 1/30		
40/0.3	50/60	FRCMM-40/2/03-S/A-RT	305076 1/30		
63/0.3	50/60	FRCMM-63/2/03-S/A-RT	305077 1/30		

SG02613



4-poles			
16/0.3	50/60	FRCMM-16/4/03-S/A-RT	305104 1/30
25/0.3	50/60	FRCMM-25/4/03-S/A-RT	305109 1/30
40/0.3	50/60	FRCMM-40/4/03-S/A-RT	305110 1/30
63/0.3	50/60	FRCMM-63/4/03-S/A-RT	305111 1/30

FRCmM- Technical Data

Specifications | Residual Current Devices FRCmM

Description

- · Residual current devices
- Shape compatible with and suitable for standard busbar connection to other devices of the xEffect-series
- Twin-purpose terminal (lift/open-mouthed) above and below
- Busbar positioning optionally above or below
- Free terminal space despite installed busbar
- Universal tripping signal switch, also suitable for FAZ, FRBmM-1N can be mounted subsequently
- · Auxiliary switch Z-HK can be mounted subsequently
- Contact position indicator red green
- Delayed types suitable for being used with standard fluorescent tubes with or without electronical ballast (30mA-RCD: 30 units per phase conductor, 100mA-RCD: 90 units per phase conductor).

Notes: Depending of the fluorescent lamp ballast manufacturer partly more possible. Symmetrical allocation of the fluorescent lamp ballasts on all phases favourably. Shifting references of the fluorescent lamp ballast manufacturer consider.

- . The device functions irrespective of the position of installation
- Tripping is line voltage-independent. Consequently, the RCD is suitable for "fault current/residual current protection" and "additional protection" within the meaning of the applicable installation rules.
- · Mains connection at either side
- The 4-pole device can also be used for 2- or 3-pole connection:
 See connection possibilities.
- The test key "T" must be pressed every 6 months. The system operator must be informed of this obligation and his responsibility in a way that can be proven (self-adhesive RCD-label enclosed). Under special conditions (e.g. damply and/or dusty environments, environments with polluting and/or corroding conditions, environments with large temperature fluctuations, installations with a risk of overvoltages due to switching of equipment and/or atmospheric discharges, portable equipment ...), it's recommended to test in monthly intervals.
- Pressing the test key "T" serves the only purpose of function testing the residual current device (RCD). This test does not make earthing resistance measurement (R_E), or proper checking of the earth conductor condition redundant, which must be performed separately.

- Type -A: Protects against special forms of residual pulsating DC which have not been smoothed.
- Type -G: High reliability against unwanted tripping. Suitable for any circuit
 where personal injury or damage to property may occur in case of unwanted
 tripping.
- Type -G/A: Additionally protects against special forms of residual pulsating DC which have not been smoothed.
- Type -R: To aviod unwanted tripping due to X-ray devices.
- Type -S: Selective residual current device sensitive to AC, Type -S.
 Suitable for systems with surge arresters downstream of the RCD.
- Type -S/A: Additionally protects against special forms of residual pulsating DC which have not been smoothed.
- Type -U: Suitable for speed-controlled drives with frequency converters in household, trade, and industry.

Unwanted tripping is avoided thanks to a tripping characteristic designed particularly for frequency converters.


Accessories:			
Auxiliary switch for subsequent installation to the left	Z-HK	248432	
Tripping signal contact for subsequent installation to the right	Z-NHK	248434	
Automatic restarting device	Z-FW/LP	248296	
	Z-FW-LPD	265244	
Remote control	Z-FW-M0	284730	
Pre-mounted sets	Z-FW-LP/M0	290171	
	Z-FW-LPD/MO	290172	
Remote testing module	Z-FW/003	248298	
	Z-FW/010	248299	
	Z-FW/030	248300	
	Z-FW/050	248301	
Terminal cover 4-poles	Z-RC/AK-4TE	101062	

FRCmM- Technical Data


Technical Data		
		FRCmM
Electrical		
Design according to		IEC/EN 61008
		Type G acc. to ÖVE E 8601
Classified according to		IEC 61373, EN 45545-2
Current test marks as printed onto the device		
Tripping		instantaneous
Type G , R		10 ms delay @ 50 Hz
Type S		40 ms delay @ 50 Hz - with selective disconnecting function
Type U (only 30 mA)		10 ms delay @ 50 Hz
Type U (except 30 mA)		40 ms delay @ 50 Hz - with selective disconnecting function
Rated voltage	Un	240/415 V AC 50 Hz and/or 60 Hz
		 see individual article for operating frequency
Limits operation voltage test circuit		
2-poles		196 - 264 V~
4-poles 30 mA		196 - 264 V~
4-poles 30 mA -400		353 - 456 V~
4-poles 100, 300, 500 mA		196 - 456 V~
Rated tripping current	I_{\Deltan}	30, 100, 300, 500 mA
Sensitivity	'An	AC and pulsating DC
Rated insulation voltage	Ui	440 V
Rated impulse withstand voltage	U _{imp}	4 kV (1.2/50µs)
Rated short circuit capacity		10 kA with back-up fuse
Peak withstand current	I _{cn}	10 K With back up rase
Type AC, A		250 A (8/20 μs) surge current-proof
Type G, G/A		3 kA (8/20 µs) surge current-proof, 10 ms delay
Type S, S/A		5 kA (8/20 μs) surge current-proof, 40 ms delay
**		5 kA (6/20 µs) surge current-proof, 40 ms delay
Rated breaking capacitiy	I _m	
or rated fault breaking capacity	$I_{\Delta m}$	500 A
I _n = 16-40 A		500 A
$I_n = 63 \text{ A}$		630 A
$I_n = 80 \text{ A}$		800 A
I _n = 100 A		1,000 A
Endurance		
electrical components		≥ 4,000 operating cycles
mechanical components		≥ 20,000 operating cycles
Mechanical		
Frame size		45 mm
Device height		80 mm
Device width		35 mm (2MU), 70 mm (4MU)
Mounting		quick fastening with 2 lock-in positions on DIN rail IEC/EN 60715
Degree of protection, built-in		IP40
Degree of predection in moisture-proof enclosure		IP54
Upper and lower terminals		open mouthed/lift terminals
Terminal protection		finger and hand touch safe, DGUV VS3, EN 50274
Terminal capacity		1.5 - 35 mm ² single wire
		2 x 16 mm ² multi wire
Terminal screw		M5 (with slotted screw acc. to EN ISO 4757-Z2, Pozidriv PZ2)
Terminal torque		2 - 2.4 Nm
Busbar thickness		0.8 - 2 mm
Operation temperature		-25°C to +40°C (for higher values see table on ambient temperature)
Storage- and transport temperature		-35°C to +60°C
Resistance to climatic conditions		acc. to IEC/EN 61008
Contact position indicator		red / green
Tripping indicator		white / blue

FRCmM- Technical Data


Connection diagram



Dimensions (mm)




Connection of ring cable lugs (only FRC...RT)



Correct connection


2-poles

30, 100, 300, 500mA Types:




4-poles


30mA -400 Types:




4-poles


30mA Types:










L1 L2 L3







100, 300, 500mA Types:









1.17

FRCmM- Technical Data

Power Loss at I_n FRCmM

(entire unit)

Tripping: A	C		
I _n [A]	$I_{\Delta n}$ [mA]	P [W]	
2-poles			
16	10	2.9	
25	30	2.0	
25	100, 300, 500	1.3	
40	30	7.8	
40	100, 300, 500	5.5	
63	30	9.7	
63	100, 300, 500	7.2	
80	30	13.5	
80	100, 300, 500	8.6	
100	30, 100, 300	13.6	
4-poles			
25	30	3.1	
25	100, 300, 500	2.8	
40	30	13.1	
40	100, 300, 500	8.8	
63	30	13.4	
63	100, 300, 500	10.5	
80	30, 100, 300, 500	11.4	
100	30, 100, 300, 500	18.8	

I _n [A]	$I_{\Delta n}$ [mA]	P [W]
2-poles		
16	10	2.9
16	30	1.2
25	30	2.0
25	100, 300	1.3
40	30	7.8
40	100, 300, 500	5.5
63	30	9.7
63	100, 300, 500	7.2
100	30, 100, 300	13.6
4-poles		
25	30	3.1
25	100, 300, 500	2.8
40	30	13.1
40	100, 300, 500	8.8
63	30, 100, 300, 500	10.5
80	30, 300	11.4
100	30, 100, 300, 500	18.8

Tripping: G, G/A				
I _n [A]	$I_{\Delta n}$ [mA]	P [W]		
2-poles				
25	30, 100 (G)	2.0		
40	30, 100 (G)	7.8		
4-poles				
40	30 (G)	13.1		
40	100 (G, G/A)	8.8		
40	30 (G/A)	13.1		
63	30 (G)	13.4		
63	100 (G, G/A)	10.5		
63	30 (G/A)	13.4		
100	30, 300 (G/A)	18.8		

Tripping: S, S/A				
I _n [A]	$I_{\Delta n}$ [mA]	P [W]		
2-poles				
40	100 (S, S/A)	7.8		
40	300 (S)	5.5		
4-poles				
25	100, 300 (S)	2.8		
25	100 (S/A)	2.8		
40	100, 300 (S, S/A)	8.8		
63	100, 300 (S)	10.5		
63	100, 300 (S/A)	10.5		
80	100, 300 (S)	11.4		
80	300 (S/A)	11.4		
100	300 (S/A)	18.8		

Tripping:	R, U	
I _n [A]	$I_{\Delta n}$ [mA]	P [W]
4-poles		
40	100, 300 (U)	8.4
63	30 (R)	13.4
63	100, 300 (U)	10.5
100	300 (U)	18.8

1.18

FRCmM- Technical Data

Impact of ambient tem	perature on the maximum	permanent current allowed	(A) FRCmM

	25A		40A		63A		80A		100A	
Ambient temperature	2р	4р	2 p	4р	2p	4p	2p	4р	2р	4р
40°	25	25	40	40	63	63	80	80	100	100
45°	21	22	37	37	59	59	76	76	95	95
50°	18	19	33	34	55	55	72	72	90	90
55°	14	16	30	31	50	50	68	68	85	85
60°	-	_	26	27	45	45	64	64	80	80
65°	-	_	20	24	40	41	60	60	75	75
70°	-	_	14	19	34	37	56	56	70	70
75°	_	_	8	15	28	32	52	52	65	65

Note: Please make sure that these values are not exceeded and that any upstream thermal overload protection switches off in time.

Max. back-up fuse FRCmM

Rating	Fuses		MCB's (Characteristic B/C		
In [A]	Short Circuit [A]	Overload [A]	Short Circuit [A]	Overload [A]	
25	63 gG/gl	25 gG/gl	FAZ-C40	FAZ-C25	
40	63 gG/gl	40 gG/gl	FAZ-C40	FAZ-C40	
63	63 gG/gl	63 gG/gl	FAZ-C40	FAZ-C40	
80	80 gG/gl	80 gG/gl	-	-	
100	100 gG/gl	80 gG/gl	-	-	

Important:

In the case that the maximal possible operating current of the
 electrical installation don't exceed the rated current of the RCD
 only short circuit protection must be implemented. Overload
 protection must be implemented in the case if the maximal
 possible operating current of the electrical installation can exceed
 the rated current of the RCD.

Residual Current Devices FRCmM-110

 $I_n/I_{\Delta n}$ (A) Type Designation Article No. Units per package

Type AC

Conditionally surge current-proof 250 A, Type AC



FRCmM-25/2/003-110	180585 1/60
FRCmM-25/2/03-110	180586 1/60
FRCmM-40/2/003-110	180587 1/60
FRCmM-40/2/03-110	180588 1/60
FRCmM-63/2/003-110	180589 1/60
FRCmM-63/2/03-110	180590 1/60
FRCmM-80/2/003-110	180591 1/60
FRCmM-80/2/03-110	180592 1/60
FRCmM-100/2/003-110	180593 1/60
FRCmM-100/2/03-110	180594 1/60
	FRCmM-25/2/03-110 FRCmM-40/2/003-110 FRCmM-40/2/03-110 FRCmM-63/2/03-110 FRCmM-63/2/03-110 FRCmM-80/2/03-110 FRCmM-80/2/03-110 FRCmM-80/2/03-110 FRCmM-100/2/03-110



FRCmM-25/4/003-110	180595 1/30
FRCmM-25/4/03-110	180596 1/30
FRCmM-40/4/003-110	180597 1/30
FRCmM-40/4/03-110	180598 1/30
FRCmM-63/4/003-110	180599 1/30
FRCmM-63/4/03-110	180600 1/30
FRCmM-80/4/003-110	180601 1/30
FRCmM-80/4/03-110	180602 1/30
FRCmM-100/4/003-110	180603 1/30
FRCmM-100/4/03-110	180604 1/30
	FRCmM-25/4/03-110 FRCmM-40/4/003-110 FRCmM-40/4/03-110 FRCmM-63/4/003-110 FRCmM-63/4/03-110 FRCmM-80/4/03-110 FRCmM-80/4/03-110 FRCmM-80/4/03-110 FRCmM-100/4/003-110

Type A

Conditionally surge current-proof 250 A, sensitive to residual pulsating DC, Type A



2-poles		
25/0.03	FRCmM-25/2/003-A-110	180605 1/60
25/0.3	FRCmM-25/2/03-A-110	180606 1/60
40/0.03	FRCmM-40/2/003-A-110	180607 1/60
40/0.3	FRCmM-40/2/03-A-110	180608 1/60
63/0.03	FRCmM-63/2/003-A-110	180609 1/60
80/0.03	FRCmM-80/2/003-A-110	180610 1/60
100/0.03	FRCmM-100/2/003-A-110	180611 1/60




4-poles			
25/0.03	FRCmM-25/4/003-A-110	180612	1/30
25/0.3	FRCmM-25/4/03-A-110	180613	1/30
40/0.03	FRCmM-40/4/003-A-110	180614	1/30
40/0.3	FRCmM-40/4/03-A-110	180615	1/30
63/0.03	FRCmM-63/4/003-A-110	180616	1/30
63/0.3	FRCmM-63/4/03-A-110	180617	1/30
80/0.03	FRCmM-80/4/003-A-110	180618	1/30
80/0.3	FRCmM-80/4/03-A-110	180619	1/30
100/0.03	FRCmM-100/4/003-A-110	180620	1/30
100/0.3	FRCmM-100/4/03-A-110	180621	1/30


FRCmM-110- Technical Data

Technical Data		
		FRCmM-110
Electrical		
Design according to		IEC/EN 61008
Classified according to		IEC 61373, EN 45545-2
Current test marks as printed onto the device		
Tripping		instantaneous
Rated voltage	U _n	110/190V AC, Type AC: 50 Hz, Type A: 50/60 Hz
Limits operation voltage test circuit		2-poles 94 - 121 V~
		4-poles 30 mA 94 - 121 V~
		4-poles 300 mA 94 - 210 V~
Rated tripping current	$I_{\Delta n}$	30, 300 mA
Sensitivity		AC and pulsating DC
Rated insulation voltage	Ui	440 V
Rated impulse withstand voltage	U_{imp}	4 kV (1.2/50μs)
Rated short circuit capacity	l _{cn}	10 kA with back-up fuse
Peak withstand current		
Type AC, A		250 A (8/20 μs) surge current-proof
Rated breaking capacitiy	I _m	
or rated fault breaking capacity	$I_{\Delta m}$	
$I_n = 16-40 \text{ A}$		500 A
$I_{n} = 63 \text{ A}$		630 A
$I_{n} = 80 \text{ A}$		800 A
$I_{n} = 100 \text{ A}$		1,000 A
Endurance		
electrical components		≥ 4,000 operating cycles
mechanical components		≥ 20,000 operating cycles
Mechanical		
Frame size		45 mm
Device height		80 mm
Device width		35 mm (2MU), 70 mm (4MU)
Mounting	,	quick fastening with 2 lock-in positions on DIN rail IEC/EN 60715
Degree of protection, built-in		IP40
Degree of predection in moisture-proof enclosure	,	IP54
Upper and lower terminals		open mouthed/lift terminals
Terminal protection		finger and hand touch safe, DGUV VS3, EN 50274
Terminal capacity		1.5 - 35 mm ² single wire
,		2 x 16 mm ² multi wire
Terminal screw		M5 (with slotted screw acc. to EN ISO 4757-Z2, Pozidriv PZ2)
Terminal torque		2 - 2.4 Nm
Busbar thickness		0.8 - 2 mm
Operation temperature		-25°C to +40°C (for higher values see table on ambient temperature)
Storage- and transport temperature		-35°C to +60°C
Resistance to climatic conditions		acc. to IEC/EN 61008
Contact position indicator		red / green
Tripping indicator		white / blue
	,	

Connection diagram



Dimensions (mm)



1.24

FRCmM-110- Technical Data

Power Loss at I_n FRCmM-110

(entire unit)

Tripping: AC		
I _n [A]	$I_{\Delta n}$ [mA]	P [W]
2-poles		
25	30	2.0
25	100, 300, 500	1.3
40	30	7.8
40	100, 300, 500	5.5
63	30	9.7
63	100, 300, 500	7.2
80	30	13.5
80	100, 300, 500	8.6
100	30, 100, 300	13.6
4-poles		
25	30	3.1
25	100, 300, 500	2.8
40	30	13.1
40	100, 300, 500	8.8
63	30	13.4
63	100, 300, 500	10.5
80	30, 100, 300, 500	11.4
100	30, 100, 300, 500	18.8

Tripping: A		
I _n [A]	$I_{\Delta n}$ [mA]	P [W]
2-poles		
16	30	1.2
25	30	2.0
25	100, 300	1.3
40	30	7.8
40	100, 300, 500	5.5
63	30	9.7
63	100, 300, 500	7.2
100	30, 100, 300	13.6
4-poles		
<u>25</u>	30	3.1
25	100, 300, 500	2.8
40	30	13.1
40	100, 300, 500	8.8
63	30, 100, 300, 500	10.5
80	30, 300	11.4
100	30, 100, 300, 500	18.8

Residual Current Devices FRCmM Type F

sg01616





Description

- Increased protection in applications with
 1-phase frequency converter due to the detection of mixed frequencies
- Reduction of nuisance tripping thanks to
- time delayed tripping
- increased current withstand capability > 3kA
- Higher load rating with DC residual currents up to 10 mA
- For fault current/residual current protection and additional protection
- Wide variety of nominal currents
- Comprehensive range of accessories
- Real contact position indicator
- Fault current tripping indicator
- Transparent designation plate
- Classified for the use in rail rolling stock

Residual Current Devices FRCmM Type F

 $I_n/I_{\Delta n}$ (A) Type Designation Article No. Units per package

Type G/F

Surge current-proof 3 kA, sensitive to residual pulsating DC, Type G/F (ÖVE E 8601)



2-poles			
16/0.03	FRCMM-16/2/003-G/F	187365	1/60
16/0.1	FRCMM-16/2/01-G/F	187371	1/60
16/0.3	FRCMM-16/2/03-G/F	187377	1/60
25/0.03	FRCMM-25/2/003-G/F	187366	1/60
25/0.1	FRCMM-25/2/01-G/F	187372	1/60
25/0.3	FRCMM-25/2/03-G/F	187378	1/60
40/0.03	FRCMM-40/2/003-G/F	187367	1/60
40/0.1	FRCMM-40/2/01-G/F	187373	1/60
40/0.3	FRCMM-40/2/03-G/F	187379	1/60
63/0.03	FRCMM-63/2/003-G/F	187368	1/60
63/0.1	FRCMM-63/2/01-G/F	187374	1/60
63/0.3	FRCMM-63/2/03-G/F	187380	1/60
80/0.03	FRCMM-80/2/003-G/F	187369	1/60
80/0.1	FRCMM-80/2/01-G/F	187375	1/60
80/0.3	FRCMM-80/2/03-G/F	187381	1/60
100/0.03	FRCMM-100/2/003-G/F	187370	1/60
100/0.1	FRCMM-100/2/01-G/F	187376	1/60
100/0.3	FRCMM-100/2/03-G/F	187382	1/60



4-poles			
16/0.03	FRCMM-16/4/003-G/F	187407	1/30
16/0.1	FRCMM-16/4/01-G/F	187413	1/30
16/0.3	FRCMM-16/4/03-G/F	187419	1/30
25/0.03	FRCMM-25/4/003-G/F	187408	1/30
25/0.1	FRCMM-25/4/01-G/F	187414	1/30
25/0.3	FRCMM-25/4/03-G/F	187420	1/30
10/0.03	FRCMM-40/4/003-G/F	187409	1/30
40/0.1	FRCMM-40/4/01-G/F	187415	1/30
10/0.3	FRCMM-40/4/03-G/F	187421	1/30
63/0.03	FRCMM-63/4/003-G/F	187410	1/30
63/0.1	FRCMM-63/4/01-G/F	187416	1/30
63/0.3	FRCMM-63/4/03-G/F	187422	1/30
30/0.03	FRCMM-80/4/003-G/F	187411	1/30
30/0.1	FRCMM-80/4/01-G/F	187417	1/30
80/0.3	FRCMM-80/4/03-G/F	187423	1/30
100/0.03	FRCMM-100/4/003-G/F	187412	1/30
00/0.1	FRCMM-100/4/01-G/F	187418	1/30
00/0.3	FRCMM-100/4/03-G/F	187424	1/30

1.27

Residual Current Devices FRCmM Type F

 $\mathbf{I}_{m}\mathbf{I}_{\Delta n}$ Type Article No. Units per (A) Designation Type

Type S/F

Selective + surge current-proof 5 kA, sensitive to residual pulsating DC, Type S/F	\propto	WW.
--	-----------	-----

sg01516



2-poles			
16/0.1	FRCMM-16/2/01-S/F	187389	1/60
16/0.3	FRCMM-16/2/03-S/F	187395	1/60
25/0.1	FRCMM-25/2/01-S/F	187390	1/60
25/0.3	FRCMM-25/2/03-S/F	187396	1/60
40/0.1	FRCMM-40/2/01-S/F	187391	1/60
40/0.3	FRCMM-40/2/03-S/F	187397	1/60
63/0.1	FRCMM-63/2/01-S/F	187392	1/60
63/0.3	FRCMM-63/2/03-S/F	187398	1/60
80/0.1	FRCMM-80/2/01-S/F	187393	1/60
80/0.3	FRCMM-80/2/03-S/F	187399	1/60
100/0.1	FRCMM-100/2/01-S/F	187394	1/60
100/0.3	FRCMM-100/2/03-S/F	187400	1/60

:d01616



4-poles			
16/0.1	FRCMM-16/4/01-S/F	187431	1/30
16/0.3	FRCMM-16/4/03-S/F	187437	1/30
25/0.1	FRCMM-25/4/01-S/F	187432	1/30
25/0.3	FRCMM-25/4/03-S/F	187438	1/30
40/0.1	FRCMM-40/4/01-S/F	187433	1/30
40/0.3	FRCMM-40/4/03-S/F	187439	1/30
63/0.1	FRCMM-63/4/01-S/F	187434	1/30
63/0.3	FRCMM-63/4/03-S/F	187440	1/30
80/0.1	FRCMM-80/4/01-S/F	187435	1/30
80/0.3	FRCMM-80/4/03-S/F	187441	1/30
100/0.1	FRCMM-100/4/01-S/F	187436	1/30
100/0.3	FRCMM-100/4/03-S/F	187442	1/30

FRCmM Type F- Technical Data

Specifications | Residual Current Devices FRCmM, Type F

Description

- Residual current devices
- Shape compatible with and suitable for standard busbar connection to other devices of the xEffect-series
- Twin-purpose terminal (lift/open-mouthed) above and below
- · Busbar positioning optionally above or below
- Free terminal space despite installed busbar
- Universal tripping signal switch, also suitable for FAZ, FRBmM-1N can be mounted subsequently
- · Auxiliary switch Z-HK can be mounted subsequently
- Contact position indicator red green
- Delayed types suitable for being used with standard fluorescent tubes with or without electronical ballast (30mA-RCD: 30 units per phase conductor, 100mA-RCD: 90 units per phase conductor).

Notes: Depending of the fluorescent lamp ballast manufacturer partly more possible. Symmetrical allocation of the fluorescent lamp ballasts on all phases favourably. Shifting references of the fluorescent lamp ballast manufacturer consider.

- The device functions irrespective of the position of installation
- Tripping is line voltage-independent. Consequently, the RCD is suitable for "fault current/residual current protection" and "additional protection" within the meaning of the applicable installation rules.
- · Mains connection at either side
- The 4-pole device can also be used for 2- or 3-pole connection:
 See connection possibilities.
- The test key "T" must be pressed every 6 months. The system operator must be informed of this obligation and his responsibility in a way that can be proven (self-adhesive RCD-label enclosed). Under special conditions (e.g. damply and/or dusty environments, environments with polluting and/or corroding conditions, environments with large temperature fluctuations, installations with a risk of overvoltages due to switching of equipment and/or atmospheric discharges, portable equipment ...), it's recommended to test in monthly intervals.
- Pressing the test key "T" serves the only purpose of function testing the residual current device (RCD). This test does not make earthing resistance measurement (R_E), or proper checking of the earth conductor condition redundant, which must be performed separately.

 Type -F: Increased protection in applications with 1-phase frequency, higher load rating with DC residual currents up to 10 mA.

Accessories:			
Auxiliary switch for subsequent installation to the left	Z-HK	248432	
Tripping signal contact for subsequent installation to the right	Z-NHK	248434	
Automatic restarting device	Z-FW/LP	248296	
	Z-FW-LPD	265244	
Remote control	Z-FW-MO	284730	
Pre-mounted sets	Z-FW-LP/MO	290171	
	Z-FW-LPD/MO	290172	
Remote testing module	Z-FW/003	248298	
	Z-FW/010	248299	
	Z-FW/030	248300	
	Z-FW/050	248301	
Terminal cover 2-poles	Z-RC/AK-2TE	285385	
Terminal cover 4-poles	Z-RC/AK-4TE	101062	

1.29


FRCmM Type F- Technical Data

Technical Data		
		FRCmM, Type F
Electrical		
Design according to		IEC/EN 62423
		Type G acc. to ÖVE E 8601
Classified according to		IEC 61373, EN 45545-2
Current test marks as printed onto the device		
Tripping		10
Type G		10 ms delay
Type S		40 ms delay - with selective disconnecting function
Rated voltage	U _n	240/415 V AC, 50/60 Hz
Limits operation voltage test circuit		100 2041/
2-poles		196 - 264 V~
4-poles 30 mA		196 - 264 V~
4-poles 100, 300 mA		196 - 456 V~
Rated tripping current	$I_{\Delta n}$	30, 100, 300 mA
Sensitivity		AC and pulsating DC 440 V
Rated insulation voltage	U _i	
Rated impulse withstand voltage	U _{imp}	4 kV (1.2/50µs) 10 kA with back-up fuse
Rated short circuit capacity	I _{cn}	TU KA WITH Dack-up Tuse
Peak withstand current		21.4 (0/20)
Type G/F		3 kA (8/20 μs) surge current-proof, 10 ms delay
Type S/F Rated breaking capacitiy		5 kA (8/20 μs) surge current-proof, 40 ms delay
	I _m	
or rated fault breaking capacity	$I_{\Delta m}$	Γ00 Λ
$I_n = 16-40 \text{ A}$		500 A
$I_n = 63 \text{ A}$		630 A 800 A
$I_n = 80 \text{ A}$		
I _n = 100 A		1,000 A
Endurance electrical components		> 4,000 energing avalog
•		≥ 4,000 operating cycles
mechanical components		≥ 20,000 operating cycles
Mechanical		AE mm
Frame size Device height		45 mm 80 mm
Device width		35 mm (2MU), 70 mm (4MU)
Mounting		quick fastening with 2 lock-in positions on DIN rail IEC/EN 60715
Degree of protection, built-in		1P40
Degree of protection, bull-in Degree of predection in moisture-proof enclosure		IP54
Upper and lower terminals		open mouthed/lift terminals
Terminal protection		finger and hand touch safe, DGUV VS3, EN 50274
Terminal capacity		1.5 - 35 mm² single wire
Terminal capacity		2 x 16 mm² multi wire
Terminal screw		M5 (with slotted screw acc. to EN ISO 4757-Z2, Pozidriv PZ2)
Terminal torque		2 - 2.4 Nm
Busbar thickness		0.8 - 2 mm
Operation temperature		-25°C to +40°C (for higher values see table on ambient temperature)
Storage- and transport temperature		-35°C to +60°C
Resistance to climatic conditions		acc. to IEC/EN 62423
Contact position indicator		red / green
Tripping indicator		white / blue
mpping indicator		Willia / Dido

Connection diagram 2-poles 4-poles








FRCmM Type F- Technical Data

Correct connection


2-poles


30, 100, 300mA Types:





4-poles

30mA Types:













100, 300mA Types:









Impact of ambient temperature on the maximum permanent current allowed (A) FRCmM, Type F

	25A		40A		63A		80A		100A	
Ambient temperature	2 p	4р	2р	4р	2p	4p	2p	4p	2р	4p
40°	25	25	40	40	63	63	80	80	100	100
45°	21	22	37	37	59	59	76	76	95	95
50°	18	19	33	34	55	55	72	72	90	90
55°	14	16	30	31	50	50	68	68	85	85
60°	_	_	26	27	45	45	64	64	80	80
65°	_	_	20	24	40	41	60	60	75	75
70°	_	_	14	19	34	37	56	56	70	70
75°	_	_	8	15	28	32	52	52	65	65

Note: Please make sure that these values are not exceeded and that any upstream thermal overload protection switches off in time.

1.31

FRCmM Type F- Technical Data

Max. back-up fuse FRCmM, Type F

Rating	Fuses		MCB's (Characteristic B/C)			
In [A]	Short Circuit [A]	Overload [A]	Short Circuit [A]	Overload [A]		
25	63 gG/gl	25 gG/gl	FAZ-C40	FAZ-C25		
40	63 gG/gl	40 gG/gl	FAZ-C40	FAZ-C40		
63	63 gG/gl	63 gG/gl	FAZ-C40	FAZ-C40		
80	80 gG/gl	80 gG/gl	-	-		
100	100 gG/gl	80 gG/gl	-	-		

Important

In the case that the maximal possible operating current of the
electrical installation don't exceed the rated current of the RCD
only short circuit protection must be implemented. Overload
protection must be implemented in the case if the maximal
possible operating current of the electrical installation can exceed
the rated current of the RCD.

Eaton's electrical business is a global leader with deep regional application expertise in power distribution and circuit protection; power quality, backup power and energy storage; control and automation; life safety and security; structural solutions; and harsh and hazardous environment solutions. Through end-to-end services, channel and an integrated digital platform & insights Eaton is powering what matters across industries and around the world, helping customers solve their most critical electrical power management challenges.

For more information, visit **Eaton.com**.



Eaton Industries (Austria) GmbH Scheydgasse 42 1210 Vienna

Eaton EMEA Headquarters Route de la Longeraie 7 1110 Morges, Switzerland

© 2021 Eaton All Rights Reserved Printed in Austria Publication No. CA003018EN Article number 302003-MK April 2021 Grafics: SRA, Schrems

Changes to the products, to the information contained in this document, and to prices are reserved; as are errors and omissions. Only order confirmations and technical documentation by Eaton is binding. Photos and pictures also do not warrant a specific layout or functionality. Their use in whatever form is subject to prior approval by Eaton. The same applies to trademarks (especially Eaton, Moeller, and Cutler-Hammer). The Terms and Conditions of Eaton apply, as referenced on Eaton Internet pages and Eaton order confirmations.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.











