

TS 35X15/2.3 2M/CU/BK**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Product image**

Copper has the best electrical conductivity of all metals used. The copper rail has the highest short-circuit protection.

General ordering data

Version	Rail, TS 35, TS 35 x 15, without slot, Copper, untreated
Order No.	0270100000
Type	TS 35X15/2.3 2M/CU/BK
GTIN (EAN)	4008190105136
Qty.	2 m

TS 35X15/2.3 2M/CU/BK

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	15 mm	Depth (inches)	0.591 °C
Height	35 mm	Height (inches)	1.378 °C
Width	2,000 mm	Width (inches)	78.74 °C
Net weight	940 g		

Mounting rail

Installation advice	Direct mounting	
Length of the terminal rail	min.	0 mm
	max.	2,000 mm
	nominal	2,000 mm
Material	Copper	
Permitted thermal current for PEN function, max.	309 A	
Pre-punched mounting rail	No	
Short circuit strength corresponds to E-Cu wire	150 Nm	
Short-time withstand current according to IEC 60947-7-2	18 V AC/DC ±10 %	
Slit gap		
Slit length		
Slit width		
Standards	DIN EN 60715	
Surface finish	untreated	
Thickness	2.3 mm	

Classifications

ETIM 6.0	EC001285	ETIM 7.0	EC001285
ETIM 8.0	EC001285	ECLASS 9.0	27-40-06-02
ECLASS 9.1	27-40-06-02	ECLASS 10.0	27-40-06-02
ECLASS 11.0	27-40-06-02		

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	STEP
Engineering Data	EPLAN, WSCAD, Zuken E3.S
User Documentation	StorageConditionsTerminalBlocks
Catalogues	Catalogues in PDF-format
Brochures	