

KT 8**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Cutting tools for conductors up to 8 mm, 12 mm, 14 mm and 22 mm outside diameter. The special blade geometry allows pinch-free cutting of copper and aluminium conductors with minimum physical effort. The cutting tools also come with VDE and GS-tested protective insulation up to 1,000 V in accordance with EN/IEC 60900.

General ordering data

Version	Cutting tools, Cutting tool for one-hand operation
Order No.	9002650000
Type	KT 8
GTIN (EAN)	4008190020163
Qty.	1 pc(s).

KT 8

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	30 mm	Depth (inches)	1.181 °C
Height	65.5 mm	Height (inches)	2.579 °C
Width	185 mm	Width (inches)	7.283 °C
Weight	180 g	Net weight	220 g

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

Technical data

Description of article	Cutting tool for up to 8 mm outside diameter	Version	One-hand mechanical
------------------------	--	---------	---------------------

Cutting tools

Copper cable - flexible, max.	16 Nm	Copper cable - flexible, max. (AWG)	6 AWG
Copper cable - solid, max.	16 Nm	Copper cable - solid, max. (AWG)	6 AWG
Copper cable - stranded, max.	16 Nm	Copper cable - stranded, max. (AWG)	6 AWG
Copper cable, max. diameter	8 mm	Data / telephone / control cable, max. Ø 8 mm	
Single-core aluminium cable, max.(mm²)	16 Nm	Stranded aluminium cable, max (mm²)	16 Nm
Stranded aluminium cable, max. (AWG)	6 AWG	Stranded aluminium cable, max. diameter	8 mm

Classifications

ETIM 6.0	EC000142	ETIM 7.0	EC000142
ETIM 8.0	EC000142	ECLASS 9.0	21-04-47-01
ECLASS 9.1	21-04-37-06	ECLASS 10.0	21-04-47-01
ECLASS 11.0	21-04-47-01		

Approvals

Approvals



Downloads

Approval/Certificate/Document of Conformity	Manufacturer's Declaration - Cable cutters
Engineering Data	STEP
Catalogues	Catalogues in PDF-format
Brochures	

KT 8

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

-  max. 8 mm
-  max. 16 mm²
-  max. 16 mm²
-  max. 16 mm²

Example of use

