

Product Description

Glas fibre reinforced for maximum mechanical stability; Bearing surface avoids scratchings on the housing while mounting with an wrench



Application range

- For locking of SKINTOP® cable glands in boreholes without thread.

Benefits

- Glas fibre reinforced for maximum mechanical stability
- Bearing surface avoids scratchings on the housing while mounting with an wrench

Design

- Metric connection thread acc. to EN 50262

Note

- UL approval only when used with the UL approved SKINTOP® polyamide cable glands
- Designed for use in connection with metric SKINTOP® cable glands

Technical Data

On request

Available without collar (without surface for assembling tool)

Colour delivered

RAL 7001 silver-grey RAL 7035 light grey RAL 9005 black / UV resistant

Material

Polyamide, glass fibre reinforced

Range of temperature

Static: -40°C up to +100°C

Dynamic: -20°C up to +100°C

Article List

Part number	Part designation / size	SW mm	Pieces / PU
SKINTOP® GMP-GL-M silver grey			
53119000	12 x 1,5	17	100
53119010	16 x 1,5	22	100
53119020	20 x 1,5	27	100
53119030	25 x 1,5	34	100
53119040	32 x 1,5	41	100
53119050	40 x 1,5	50	25
53119060	50 x 1,5	60	25
53119070	63 x 1,5	75	25
SKINTOP® GMP-GL-M black			
53119100	12 x 1,5	17	100
53119110	16 x 1,5	22	100
53119120	20 x 1,5	27	100
53119130	25 x 1,5	34	100
53119140	32 x 1,5	41	100
53119150	40 x 1,5	50	25
53119160	50 x 1,5	60	25
53119170	63 x 1,5	75	25
SKINTOP® GMP-GL-M light grey			
53119003	12 x 1,5	17	100
53119013	16 x 1,5	22	100
53119023	20 x 1,5	27	100
53119033	25 x 1,5	34	100
53119043	32 x 1,5	41	100
53119053	40 x 1,5	50	25



53119063	50 x 1,5	60	25
53119073	63 x 1,5	75	25

Footnote:

Photographs are not to scale and do not represent detailed images of the respective products.