

SKINDICHT® BL-M

SKINDICHT® BL-M, brass blind plugs for closing pre-threaded holes, assembling with screwdriver



Corrosion-resistant



Robust



Reliability



Temperature-resistant



Application range

Machine and equipment manufacturing
Electric motor manufacturing

Benefits

For closing pre-threaded holes
Assembling with screwdriver

Product Make-up

Metric connection thread acc. to DIN EN 60423
Basis for technical information EN 50262

Note

Drawing on request

Technical Data

On request:

Fitted with FKM O-ring

Classification:

ETIM 5.0 Class-ID: EC000032

ETIM 5.0 Class-Description: Plug for cable screw gland

Material:

Body: nickel-plated brass

Sea water-resistant

Protection rating:

IP 54

IP 68 (with O-Ring)

Temperature range:

With O-ring: -30 °C to +100 °C

Without O-ring: -60 °C to +200 °C

Note

Photographs are not to scale and do not represent detailed images of the respective products.

**SKINDICHT® BL-M**

Part number	Article designation / size	Outer Ø (mm)	Pieces / PU
SKINDICHT® BL-M			
52103100	12 x 1,5	14.0	100
52103110	16 x 1,5	18.0	100
52103120	20 x 1,5	22.0	100
52103130	25 x 1,5	28.0	100
52103140	32 x 1,5	35.0	50
52103150	40 x 1,5	44.0	25
52103160	50 x 1,5	54.0	10
52103170	63 x 1,5	70.0	10
SKINDICHT® BL-M with O-ring			
52103105	12 x 1,5	14.0	100
52103115	16 x 1,5	18.0	100
52103125	20 x 1,5	22.0	100
52103135	25 x 1,5	28.0	100
52103145	32 x 1,5	35.0	50
52103155	40 x 1,5	44.0	25
52103165	50 x 1,5	54.0	10
52103175	63 x 1,5	70.0	10
52103190	75 x 1,5	80.0	1

SKINDICHT® BL-M

