

Products → Low Voltage Products and Systems → Fusegear → Fuse Switch Disconnectors → Kabeldon IP-System

General Information

Global Commercial Alias:	6303.0267.1
Extended Product Type:	AD 400
Product ID:	2CGX063030267
EAN:	7331980047833
Catalog Description:	AD 400 Insulated connector
Long Description:	Insulated connector

Ordering

EAN:	7331980047833
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85369010

Dimensions

Product Net Width:	42 mm
Product Net Height:	101 mm
Product Net Depth / Length:	100 mm
Product Net Weight:	0.47 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	110 mm
Package Level 1 Height:	100 mm
Package Level 1 Depth / Length:	40 mm
Package Level 1 Gross Weight:	0.47 kg
Package Level 1 EAN:	7331980047833
Package Level 2 Units:	3 piece
Package Level 2 Width:	1100 mm
Package Level 2 Height:	450 mm
Package Level 2 Depth / Length:	330 mm
Package Level 2 Gross Weight:	1,465 kg

Additional Information

Cable Cross-Section:	50 ... 400 mm ²
Conventional Thermal Current (I_{the}):	630 A

Degree of Protection:	acc. to IEC 60529 IP2X
Product Main Type:	Connector
Product Name:	Insulated connector
Rated Insulation Voltage (U_i):	1000 V
Rated Operational Current (I_e):	630 A
Rated Operational Voltage:	690 V
Suitable For:	Kabeldon busbar
Tightening Torque:	20 N·m Wire-Clamp 20 ... 45 N·m

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	2CGC0036
Declaration of Conformity - CE:	2CGC0021
Environmental Information:	1SCC100001D0201
Instructions and Manuals:	4390826910

Classifications

E-number:	0732613
ETIM 5:	EC000001 - Busbar terminal
ETIM 6:	EC000001 - Busbar terminal

