

ABB SpA
Via Dell'industria, 18
20009 – Vittuone – Milano
Italy
Tel. +39 02 2415 0000
<https://new.abb.com/low-voltage>

© Copyright 2020 ABB SpA. All rights reserved.
Specification subject to change without notice.

B21/B23/B24
INSTALLATION MANUAL

2CMC485019M0201 September 2020 Rev E



Warning! Installation by person with electrotechnical expertise only.
Warnung! Installation nur durch elektrotechnische Fachkraft.
Avvertenza! Fare installare solo da un elettricista qualificato.

Avertissement! Installation uniquement par des personnes qualifiées en électrotechnique.
Advertencia! La instalación deberá ser realizada únicamente por electricistas especializados.

1 Mounting

1.1 Mounting all model

PZ2
5.5 mm
13 mm
13 mm
6 mm
0.25 Nm

1.2 Connection -B24

L3
L2
L1
N
3 x ≤ 10 A
13 mm
6 mm
0.25 Nm

1.3 Connection -B23

L3
L2
L1
N
3 x ≤ 65 A
13 mm
6 mm
0.25 Nm

1.4 Connection -B21

L
N
1 x ≤ 65 A
13 mm
6 mm
0.25 Nm

2 Explanations

Table 1 Button instruction

Button	Function
	Down / Up
	OK / Exit
	Set

Table 2 Symbol instruction

Symbol	Action
	Press this button
	Press and hold button
	Setting sequence
	Screen is flashing
	Number of keystrokes
	Setting finished

3 Basic settings

3.1 Default settings

B21/B23

Pulse output
Pulse 1
Quantity : Active Energy Import
Frequency: 100 Imp/kWh
Length: 100 ms
Output: 1
Pulse 2
Quantity : Active Energy Export
Frequency: 100 Imp/kWh
Length: 100 ms
Output: 2

B24

Pulse output
Pulse 1
Quantity : Active Energy Import
Frequency: 10 Imp/kWh
Length: 100 ms
Output: 1
Pulse 2
Quantity : Active Energy Export
Frequency: 10 Imp/kWh
Length: 100 ms
Output: 2

3.2 B21/B23/B24 - Pulse output

3.3 B23/B24 - Wires

3.4 B24 - CT Ratios

3.5 Change / Select values

1. Select a value

Select a value when the digit blinks.

2. Cancel a value

Cancel a value when the digit blinks.

3. Change Value

Enter the value when the digit blinks.

Table 3 Technical data

	B21	B23	B24
Nominal voltage	230 V AC	230 V AC	3x230 / 400 V AC
Voltage range	220-240 VAC (-20% to +15%)	220-240 VAC (-20% to +15%)	3x220-240 V AC (-20% to +15%)
Base current I _b	5 A	5 A	-
Rated current I _n	-	-	1 A
Reference current I _{ref}	5 A	5 A	-
Maximum current I _{max}	65 A	65 A	6 A
Terminal wire area	1.5 - 25 mm ²	50 or 60 Hz ± 5%	0.5 - 10 mm ²
Frequency	50 or 60 Hz ± 5%	50 or 60 Hz ± 5%	50 or 60 Hz ± 5%
Accuracy Class	B (Cl. 1) and Reactive Cl. 2	B (Cl. 1) and Reactive Cl. 2	B (Cl. 1) or C (Cl. 0.5 S) and Reactive Cl. 2
Active energy	1%	1%	0.5%, 1%
Environmental			
Operating temperature	-40 to +70°C	-40 to +70°C	-40 to +70°C
Storage temperature	-40°C to +85°C	-40°C to +85°C	-40°C to +85°C
Humidity	75% yearly average, 95% on 30 days/year	75% yearly average, 95% on 30 days/year	75% yearly average, 95% on 30 days/year
Resistance to water and dust	IP20 on terminal block without protective enclosure and IP51 in protective enclosure, according to IEC 60529.	IP20 on terminal block without protective enclosure and IP51 in protective enclosure, according to IEC 60529.	IP20 on terminal block without protective enclosure and IP51 in protective enclosure, according to IEC 60529.
Mechanical env.	Class M2 for MID meters	Class M2 for MID meters	Class M2 for MID meters
Electromagnetic env.	Class E2 for MID meters	Class E2 for MID meters	Class E2 for MID meters
LED pulse inductor	Frequency 1000 imp/kWh	Frequency 1000 imp/kWh	Length 40 ms
Outputs			
Current	2 - 100 mA	2 - 100 mA	2 - 100 mA
Voltage	5 - 240 V AC/DC. 5 - 40 V DC. For meters with only 1 output.	5 - 240 V AC/DC. 5 - 40 V DC. For meters with only 1 output.	5 - 240 V AC/DC. 5 - 40 V DC. For meters with only 1 output.
Pulse output frequency	Programmable: 1 - 999999 imp/kWh	Programmable: 1 - 999999 imp/kWh	Programmable: 1 - 999999 imp/kWh
Pulse length	Programmable: 10 - 990 ms	Programmable: 10 - 990 ms	Programmable: 10 - 990 ms
Terminal wire area	0.5 - 1 mm ²	0.5 - 1 mm ²	0.5 - 1 mm ²
Inputs			
Voltage	0 - 240 V AC/DC	0 - 240 V AC/DC	0 - 240 V AC/DC
OFF	0 - 12 V AC/DC	0 - 12 V AC/DC	0 - 12 V AC/DC
ON	57 - 240 V AC/24 - 240 V DC	57 - 240 V AC/24 - 240 V DC	57 - 240 V AC/24 - 240 V DC
Min. pulse length	30 ms	30 ms	30 ms
Terminal wire area	0.5 - 1 mm ²	0.5 - 1 mm ²	0.5 - 1 mm ²
Standards	IEC 62052-11, IEC 62053-21 class 1 & 2, IEC 62053-22 class 0.5 S, IEC 62053-23 class 2, IEC 62054-21, GB/T 17215.211-2006, GB/T 17215.312-2008 class 1 & 2, GB/T 17215.322-2008 class 0.5 S, GB 4208-2008, EN 50470-1, EN 50470-3 category A, B & C	IEC 62052-11, IEC 62053-21 class 1 & 2, IEC 62053-22 class 0.5 S, IEC 62053-23 class 2, IEC 62054-21, GB/T 17215.211-2006, GB/T 17215.312-2008 class 1 & 2, GB/T 17215.322-2008 class 0.5 S, GB 4208-2008, EN 50470-1, EN 50470-3 category A, B & C	IEC 62052-11, IEC 62053-21 class 1 & 2, IEC 62053-22 class 0.5 S, IEC 62053-23 class 2, IEC 62054-21, GB/T 17215.211-2006, GB/T 17215.312-2008 class 1 & 2, GB/T 17215.322-2008 class 0.5 S, GB 4208-2008, EN 50470-1, EN 50470-3 category A, B & C
Material	Polycarbonate in transparent front glass. Glass reinforced polycarbonate in bottom case and upper case. Polycarbonate in terminal cover.	Polycarbonate in transparent front glass. Glass reinforced polycarbonate in bottom case and upper case. Polycarbonate in terminal cover.	Polycarbonate in transparent front glass. Glass reinforced polycarbonate in bottom case and upper case. Polycarbonate in terminal cover.

