
PRODUCT-DETAILS

AD 2150

AD 2150 Insulated connector



General Information

Extended Product Type	AD 2150
Product ID	2CGD000310A1000
EAN	7331980053414
Catalog Description	AD 2150 Insulated connector
Long Description	Insulated connector for parallel conductors

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85369010
Country of Origin	Sweden (SE)

Popular Downloads

Data Sheet, Technical Information	2CGC0036
Instructions and Manuals	4380002700

Dimensions

Product Net Width	35 mm
Product Net Height	80 mm
Product Net Depth / Length	88 mm
Product Net Weight	0.225 kg

Technical

Conventional Thermal Current (I_{the})	400 A
Rated Insulation Voltage (U_i)	690 V
Rated Operational Voltage	690 V
Rated Short-time Withstand Current (I_{ow})	for 0.2 s 30 kiloampere rms
Rated Conditional Short-Circuit Current (I_{nc})	(2//200 A fuse, 690 V) 50 kiloampere rms
Cable Cross-Section	35...2x150 mm ²
Degree of Protection	acc. to IEC 60529 IP2X
Tightening Torque	20 N·m Wire-Clamp 20...45 N·m

Environmental

Environmental Information	1SCC100001D0201
---------------------------	-----------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CGC0021
Environmental Information	1SCC100001D0201
Instructions and Manuals	4380002700
REACH Declaration	2CGC0049

Container Information

Package Level 1 Units	1 bag
Package Level 1 Width	100 mm
Package Level 1 Depth / Length	100 mm
Package Level 1 Height	35 mm
Package Level 1 Gross Weight	0.235 kg

Classifications

ETIM 6	EC000001 - Busbar terminal
ETIM 7	EC000001 - Busbar terminal
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Fusegear → Fuse Switch Disconnectors → Kabeldon IP-System

