


PRODUCT-DETAILS

6303.0267.1

AD 400 Insulated connector



General Information

Global Commercial Alias	6303.0267.1
Extended Product Type	AD 400
Product ID	2CGX063030267
EAN	7331980047833
Catalog Description	AD 400 Insulated connector
Long Description	Insulated connector

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85369010
Country of Origin	Sweden (SE)

Popular Downloads

Data Sheet, Technical Information	2CGC0036
Instructions and Manuals	4390826910

Dimensions

Product Net Width	42 mm
-------------------	-------

Product Net Height	101 mm
Product Net Depth / Length	100 mm
Product Net Weight	0.47 kg

Technical

Conventional Thermal Current (I _{the})	630 A
Rated Insulation Voltage (U _i)	1000 V
Rated Operational Voltage	690 V
Cable Cross-Section	50 ... 400 mm ²
Degree of Protection	acc. to IEC 60529 IP2X
Tightening Torque	20 N·m Wire-Clamp 20 ... 45 N·m

Environmental

Environmental Information	1SCC100001D0201
---------------------------	-----------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CGC0021
Environmental Information	1SCC100001D0201
Instructions and Manuals	4390826910
REACH Declaration	2CGC0049
RoHS Information	2CGC0040

Container Information

Package Level 1 Units	1 bag
Package Level 1 Width	110 mm
Package Level 1 Depth / Length	40 mm
Package Level 1 Height	100 mm
Package Level 1 Gross Weight	0.47 kg
Package Level 1 EAN	7331980047833
Package Level 2 Units	3 bag
Package Level 2 Width	1100 mm
Package Level 2 Depth / Length	330 mm
Package Level 2 Height	450 mm
Package Level 2 Gross Weight	1.465 kg

Classifications

ETIM 5	EC000001 - Busbar terminal
ETIM 6	EC000001 - Busbar terminal
ETIM 7	EC000001 - Busbar terminal

ETIM 8	EC000001 - Busbar terminal
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	5411041
E-Number (Sweden)	0732613

Categories

Low Voltage Products and Systems → Fusegear → Fuse Switch Disconnectors → Kabeldon IP-System

