



Each PRT64LT reader can be used as a universal identification point connected to the access controller. PRT64LT readers can operate in many common communication standards (e.g. Wiegand, Magstripe, Clock and Data, RACS), so they can cooperate with majority of controllers from different vendors available on the market.

**Features:**

- power supply 12 VDC
- EM 125 kHz cards
- programmable data output format: Wiegand 26-66bit, Magstripe (Clock and data), RACS (Roger) and others
- various ways of PIN and keypad codes transmission
- LED and Buzzer controlled through separate inputs
- outdoor installation (except PRT32LT, PRT42LT and PRT42LT-BK)
- tamper
- average current consumption 65 mA
- reading distance up to 15 cm
- environmental conditions of operation:
  - temperature from -25°C to +60°C
  - humidity from 10% to 95%
- dimensions: 115.0 x 80.0 x 35.0 mm (height x width x thickness)
- weight: ≈120.0 g
- CE mark

| Order guide      |                                                 |
|------------------|-------------------------------------------------|
| Item             | Description                                     |
| <b>PRT64LT-G</b> | EM 125 kHz outdoor proximity reader with keypad |

**Legal Notice**

This document is not intended to be a technical specification of the product and has informative character only. The Manufactures of product reserves right to change its characteristic without notice. The product features listed in this document refer to the entire series and depends on particular product version, configuration and additional equipment.

RevB © 2017 ROGER sp. z o.o. sp. k. All rights reserved.

This document is a subject to the Terms of Use in their current version published at the [www.roger.pl](http://www.roger.pl)