## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark:	LEDVANCE		
Supplier's address: LEDVANCE (	GmbH, Parkring 29-3	3, 85748 Garching, DE	
Model identifier: AC42654			
Type of light source:			
Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	20 mA		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Yes
	Product para	meters	
Parameter	Value	Parameter	Value
	General product p	parameters:	
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	5	Energy efficiency class	F
Useful luminous flux (фuse), indicating if it refers to the flux in	480 in Sphere (360°)	Correlated colour temperature,	3 000

General product parameters:						
Energy consur mode (kWh/10 up to the neare	00 h), rounded	5	Energy efficiency class	F		
dicating if it refe a sphere (360º)	s flux (фuse), in- ers to the flux in , in a wide cone errow cone (90º)	480 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000		
On-mode pow pressed in W	ver (P <sub>on</sub> ), ex-	5,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,50		
(P <sub>net</sub> ) for CLS, 6	candby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80		
Outer dimen-	Height	250	Spectral power dis-	See image		
sions without	Width	8	tribution in the	in last page		
separate con- trol gear, light- ing control	Depth	1	range 250 nm to 800 nm, at full-load			

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-			
		Chromaticity coordi-	0,434			
		nates (x and y)	0,403			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	5	Survival factor	0,90			
the lumen maintenance factor	0,96					

(a)'-': not applicable; (b)'-': not applicable;

