Product Information Sheet

sions without

separate con-

trol gear, light-

control

ing

Width

Depth

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources						
Supplier's name or t	trade mark:	LEDVANCE				
Supplier's address: LEDVANCE GmbH, Parkring 29-33, 85748 Garching, DE Model identifier: AC44154						
Lighting technology used:		LED	Non-directional or directional:	NDLS		
Light source cap-typ	е	G5				
(or other electric int	erface)					
Mains or non-mains	:	NMLS	Connected light source (CLS):	No		
Colour-tuneable ligh	t source:	No	Envelope:	-		
High luminance light source:		No				
Anti-glare shield:		No	Dimmable:	No		
		Product para		ı		
Parameter		Value	Parameter	Value		
		General product p	T			
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		18	Energy efficiency class	D		
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		2 800 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000		
On-mode power (P _{on}), expressed in W		18,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00		
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80		
Outer dimen- Hei	ight	1 449	Spectral power dis-	See image		

19

19

tribution in the

range 250 nm to 800

nm, at full-load

in last page

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordi-	0,382			
		nates (x and y)	0,380			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	80	Survival factor	0,90			
the lumen maintenance factor	0,70					

(a)'-': not applicable; (b)'-': not applicable;

