

LED DEC FG P45 4,5W/830 E27 DIM BX

The unique feature of this series is the lamps' fully comprehensive 360-degree light distribution. The lamp also emits light in the direction of the base, which is particularly useful for ceiling luminaires, for example. An opal cover makes the light glareless. Models that are dimmable with LED dimmers can be recognised by the DIM symbol on the package. The lamps have a pleasant pure white tone (3000 K). Their ecofriendly cardboard packages are colour-coded. The colour indicates the corresponding incandescent bulb, making the choice simpler for the consumer. Technical specifications are also clearly presented.



Bulb type compact



PRODUCT CODE	GTIN1	LXHXW	KG	PRODUCT FAMILY	
LED DEC FG P45 4,5W/830 E	ED DEC FG P45 4,5W/830 E27 DIM BX				
9410726	6435200276148	45 x 78 x 45	0.020	DECOR	

Radiation angle (°)	360	Nominal voltage (min) (V)	220	
Beam angle (°)	360 Weighted energy consumption in 1,000		5	
ETIM class EC001959		hours (kWh)		
Energy Efficiency Index (EEI)	0,107	Length (mm)	78	
Energy efficiency class	A++	Colour housing	White	
Photobiological safety according to EN	RG1	Min. number of switching cycles	50000	
62471		Power factor	0,7	
Diameter (mm)	45	Colour of light	830	
Filament lamp	No	Colour of light acc. EN 12464-1	Warm <3300 K	
Dimmable	Yes	Light colour category	Warm	
Voltage type	AC	Colour of light (max)	3000	
Socket	E27	Colour of light (min)	3000	
With remote control	No	Lamp efficacy (lm/W)	104	
Remote operation possible	No	Luminous flux (Im)	470	
Average nominal lifespan (h)	15000	Luminous flux (max) (lm)	470	
Degree of protection (IP)	Other	Luminous flux (min) (lm)	470	
Lamp designation	Other	Colour	White	
Lamp power (W)	4,5	Colour controllable (RGB)	No	
Lamp power (max) (W)	4,5	Colour temperature (K) (numeric)	3000	
Lamp power (min) (W)	4,5	Colour temperature (max) (K)	3000	
Lamp shape	Round/globe	Colour temperature (min) (K)	3000	
Type of glass/cover	Opal	Colour rendering index CRI	80-89	
Nominal voltage (max) (V)	240	Colour consistency (McAdam ellipse)	SDCM5	

