

Product Environmental Profile

TeSys D






General information

Representative product	TeSys D - LC1D80P7
Description of the product	3-poles contactors; supplied with AC currents of between 24 and 600 V
Functional unit	Switch on and off during 20 years electrical power supply of a downstream installation with an electrical and/or mechanical control. The functional unit is characterized by a type 1NO + 1NC, a control circuit voltage 230V AC, a power circuit voltage 1000V and a maximum allowed intensity by the power circuit 990A.



Constituent materials

Reference product mass	1757,5 g including the product, its packaging and additional elements and accessories
------------------------	---



Plastics	20,3%
Metals	69,9%
Others	9,7%



Substance assessment

Products of this range are designed in conformity with the requirements of the RoHS directive (European Directive 2011/65/EU of 2 January 2013, amended in March 2015, 2015/863/EU and in November 2017, 2017/2102/EU) and do not contain, or only contain in the authorised proportions, lead, mercury, cadmium, hexavalent chromium or flame retardants (polybrominated biphenyls - PBB, polybrominated diphenyl ethers – PBDE), Bis (2-ethylhexyl)phthalate - DEHP, Benzyl butyl phthalate– BBP, Dibutyl phthalate - DBP, Diisobutyl phthalate - DIBP) as mentioned in the Directive.

Details of ROHS and REACH substances information are available on the Schneider-Electric Green Premium website

<http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page>



Additional environmental information

The TeSys D presents the following relevant environmental aspects


Manufacturing	Manufactured at a Schneider Electric production site ISO14001 certified		
Distribution	Weight and volume of the packaging optimized, based on the European Union's packaging directive Packaging weight is 167,5 g, consisting of cardboard (93%), paper (7%) Packaging recycled materials is 85% of total packaging mass. Product distribution optimised by setting up local distribution centres		
Installation	Ref LC1D80P7 does not require any installation operations		
Use	The product does not require special maintenance operations.		
End of life	End of life optimized to decrease the amount of waste and allow recovery of the product components and materials This product contains that should be separated from the stream of waste so as to optimize end-of-life treatment. Recyclability potential: 70%		
	Based on "ECO'DEEE recyclability and recoverability calculation method" (version V1, 20 Sep. 2008 presented to the French Agency for Environment and Energy Management: ADEME).		

Environmental impacts

Reference life time	20 years			
Product category	Contactor, remote control switch, combinations, starters			
Installation elements	The disposal of the packaging materials are accounted for during the installation phase (including transport to disposal).			
Use scenario	Load factor : 50% of 990 Amps Use rate: 50% of reference life time			
Geographical representativeness	Europe			
Technological representativeness	The Modules of Technologies such as material production, manufacturing process and transport technology used in this PEP analysis (LCA-EIME in this case) are Similar and representative of the actual type of technologies used to make the product.			
Energy model used	Manufacturing	Installation	Use	End of life
	Energy model used: China	Electricity Mix; AC; consumption mix, at consumer; < 1kV; EU-27	Electricity Mix; AC; consumption mix, at consumer; < 1kV; EU-27	Electricity Mix; AC; consumption mix, at consumer; < 1kV; EU-27

Compulsory indicators		TeSys D - LC1D80P7					
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to mineral resources depletion	kg Sb eq	1,05E-02	1,04E-02	0*	0*	3,74E-05	0*
Contribution to the soil and water acidification	kg SO ₂ eq	6,28E+00	6,54E-02	1,04E-03	0*	6,21E+00	0*
Contribution to water eutrophication	kg PO ₄ ³⁻ eq	2,41E-01	7,91E-03	2,38E-04	0*	2,33E-01	1,18E-04
Contribution to global warming	kg CO ₂ eq	8,31E+02	9,35E+00	2,27E-01	0*	8,21E+02	1,97E-01
Contribution to ozone layer depletion	kg CFC11 eq	2,00E-04	7,94E-07	0*	0*	1,99E-04	0*
Contribution to photochemical oxidation	kg C ₂ H ₄ eq	2,98E-01	4,29E-03	7,39E-05	0*	2,93E-01	4,83E-05
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Net use of freshwater	m3	2,59E+00	4,44E-01	0*	0*	2,14E+00	0*
Total Primary Energy	MJ	1,68E+04	1,56E+02	3,21E+00	0*	1,66E+04	2,50E+00





Optional indicators		TeSys D - LC1D80P7					
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to fossil resources depletion	MJ	8,56E+03	9,51E+01	3,19E+00	0*	8,46E+03	2,05E+00
Contribution to air pollution	m³	3,84E+04	3,15E+03	9,65E+00	0*	3,52E+04	1,61E+01
Contribution to water pollution	m³	3,62E+04	1,67E+03	3,73E+01	0*	3,45E+04	1,84E+01
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Use of secondary material	kg	9,91E-02	9,91E-02	0*	0*	0*	0*
Total use of renewable primary energy resources	MJ	1,19E+03	3,15E+00	0*	0*	1,19E+03	0*
Total use of non-renewable primary energy resources	MJ	1,56E+04	1,53E+02	3,20E+00	0*	1,54E+04	2,49E+00
Use of renewable primary energy excluding renewable primary energy used as raw material	MJ	1,19E+03	3,15E+00	0*	0*	1,19E+03	0*
Use of renewable primary energy resources used as raw material	MJ	0,00E+00	0*	0*	0*	0*	0*
Use of non renewable primary energy excluding non renewable primary energy used as raw material	MJ	1,56E+04	1,43E+02	3,20E+00	0*	1,54E+04	2,49E+00
Use of non renewable primary energy resources used as raw material	MJ	9,25E+00	9,25E+00	0*	0*	0*	0*
Use of non renewable secondary fuels	MJ	0,00E+00	0*	0*	0*	0*	0*
Use of renewable secondary fuels	MJ	0,00E+00	0*	0*	0*	0*	0*
Waste categories	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Hazardous waste disposed	kg	1,32E+02	1,30E+02	0*	0*	0*	2,01E+00
Non hazardous waste disposed	kg	3,08E+03	3,93E+00	0*	0*	3,07E+03	0*
Radioactive waste disposed	kg	2,51E+00	1,98E-03	0*	0*	2,50E+00	0*
Other environmental information	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Materials for recycling	kg	1,42E+00	1,66E-01	0*	1,67E-01	0*	1,09E+00
Components for reuse	kg	0,00E+00	0*	0*	0*	0*	0*
Materials for energy recovery	kg	1,74E-02	0*	0*	0*	0*	1,74E-02
Exported Energy	MJ	5,26E-04	4,65E-05	0*	4,80E-04	0*	0*

* represents less than 0.01% of the total life cycle of the reference flow

Life cycle assessment performed with EIME version EIME v5.8.1, database version 2018-11 in compliance with ISO14044.

The use phase is the life cycle phase which has the greatest impact on the majority of environmental indicators (based on compulsory indicators).

Please note that the values given above are only valid within the context specified and cannot be used directly to draw up the environmental assessment of an installation.

Registration number :	SCHN-2015-086-EN	Drafting rules	PCR-ed3-EN-2015 04 02
Verifier accreditation N°	VH25	Supplemented by	PSR-0005-ed2-EN-2016 03 29

Date of issue	03/2020	Information and reference documents www.pep-ecopassport.org Validity period	5 years
Independent verification of the declaration and data, in compliance with ISO 14025 : 2010 Internal External X			
The PCR review was conducted by a panel of experts chaired by Philippe Osset (SOLINNEN) PEP are compliant with XP C08-100-1 :2016 The elements of the present PEP cannot be compared with elements from another program. Document in compliance with ISO 14025 : 2010 « Environmental labels and declarations. Type III environmental declarations »			



Schneider Electric Industries SAS
ROSELYNE THAI
roselyne.thai@schneider-electric.com

35, rue Joseph Monier
CS 30323
F- 92506 Rueil Malmaison Cedex
RCS Nanterre 954 503 439
Capital social 896 313 776 €

www.schneider-electric.com

Published by Schneider Electric

SCHN-2015-086-EN

© 2019 - Schneider Electric – All rights reserved

03/2020