



Teknisk informasjon

Serie	TeSys
Produktnavn	TeSys LRD
Produkt eller type komponent	Differensial termisk overlast relé
Kortnavn utstyr	LRD
Reléfunksjon	Motorbeskyttelse
Produktkompatibilitet	LC1D09 LC1D32 LC1D38 LC1D12 LC1D18 LC1D25
Type nettverk	DC AC
Overload tripping class	Class 10A conforming to IEC 60947-4-1
Termisk beskyttelse justeringsområde	4...6 A
[Ui] isolasjonsspenning	Power circuit: 600 V conforming to CSA Power circuit: 600 V conforming to UL Power circuit: 690 V conforming to IEC 60947-4-1

Komplementær

Nettverksfrekvens	0...400 Hz
Monteringssupport	Plate, with specific accessories Rail, with specific accessories Under contactor
Tripping threshold	1.14 +/- 0.06 Ir conforming to IEC 60947-4-1
Hjelpkontakt sammensetning	1 NO + 1 NC
[Ith] fri luft termisk strøm	5 A for signalling circuit
Tillatt strøm	3 A at 120 V AC-15 for signalling circuit 0.22 A at 125 V DC-13 for signalling circuit
[Ue] merkespenning	690 V AC 0...400 Hz for power circuit conforming to IEC 60947-4-1
Sikringsstørrelse	4 A gG for signalling circuit 4 A BS for signalling circuit
[Uimp] Nominell impuls-spenning	6 kV
Phase failure sensitivity	Tripping current 130 % of Ir on two phase, the last one at 0
Start/stopp	Red push-button: stop Blue push-button: reset
Temperaturkompensasjon	-20...60 °C
Tilkoblingsklemmer	Control circuit: screw clamp terminals 2 cable(s) 1...2.5 mm ² flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 1...2.5 mm ² flexible with cable end Control circuit: screw clamp terminals 2 cable(s) 1...2.5 mm ² solid without cable end Power circuit: screw clamp terminals 1 cable(s) 1.5...10 mm ² flexible without cable end Power circuit: screw clamp terminals 1 cable(s) 1...4 mm ² flexible with cable end Power circuit: screw clamp terminals 1 cable(s) 1...6 mm ² solid without cable end
Tiltrekningsmoment	Control circuit: 1.7 N.m - on screw clamp terminals Power circuit: 1.7 N.m - on screw clamp terminals
Høyde	66 mm
Bredde	45 mm

Dybde	70 mm
Vekt	0,124 kg

Miljø

Protective treatment	TH i samsvar med IEC 60068
IP-grad	IP20 i samsvar med IEC 60529
Omgivelsestemperatur for drift	-20...60 °C without derating conforming to IEC 60947-4-1
Omgivelsestemperatur for lagring	-60...70 °C
Flammehemming	V1 i samsvar med UL 94
Mekanisk robusthet	Vibrations: 6 Gn conforming to IEC 60068-2-6 Støt: 15 Gn for 11 ms i samsvar med IEC 60068-2-7
Dielektrisk styrke	1.89 kV at 50 Hz conforming to IEC 60947-1
Standarder	EN/IEC 60947-4-1 EN/IEC 60947-5-1 UL 60947-4-1 UL 60947-5-1 CSA C22.2 No 60947-4-1 CSA C22.2 No 60947-5-1 GB/T 14048.4 GB/T 14048.5 EN 50495
Produktsertifikater	IEC UL CSA CCC EAC BV RINA DNV-GL LROS (Lloyds register of shipping) ATEX INERIS UKCA

Packing Units

Enhetstype forpakning 1	PCE
Antall enheter forpakning 1	1
Forpakning 1 vekt	142 g
Forpakning 1 høyde	8,8 cm
Forpakning 1 bredde	7,8 cm
Forpakning 1 lengde	5 cm
Enhetstype forpakning 2	S02
Antall enheter forpakning 2	24
Forpakning 2 vekt	3,723 kg
Forpakning 2 høyde	15 cm
Forpakning 2 bredde	30 cm
Forpakning 2 lengde	40 cm
Enhetstype forpakning 3	P06
Antall enheter forpakning 3	384
Forpakning 3 vekt	68,068 kg
Forpakning 3 høyde	77 cm
Forpakning 3 bredde	80 cm
Forpakning 3 lengde	60 cm

Offer Sustainability

Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	 REACH-erklæring
EU RoHS-direktiv	I samsvar  EU RoHS-erklæring
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	 Ja

Kinas RoHS-forskrift	 Kinas RoHS-Erklæring
Miljøinformasjon	 Produktmiljøprofil
Produktets livssyklus	 Informasjon Om Levetidsslutt
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.

Contractual warranty

Garanti	18 months
---------	-----------